

# COUNTY SURVEYOR'S RECORD, DOUGLAS COUNTY, OREGON

MEMORANDUM & CO. PORTLAND, ORE. 87545

Survey No.	Made on	August, 1934	Survey No.	Made on	
In Town. 27 S	Range	5 & 6 W	Sec.	6	
Made for	County		Made for		
Purpose of	to establish corners on Range lines 5 & 6 and donation claim corners along the line		Purpose of		

thence N 0° 37' E, 1526.1 ft. to 1/2 cor. bet. Sec. 18 & 13 on Range line, which is marked by 1/2" x 48" iron pipe inside a 2" x 48" Iron pipe which is about 250' South & West of Horace Burg's house in fence N/W & from which, A W Oak 10" diam. bears S 57° W, 223.5 ft. marked 1/2 Sec. 13, Cs. Bt. A W oak 18" diam. bears S 24° 15' W, 242.3 ft. marked 1/2 Sec. 13, Cs. Bt. A W Oak This corner is N 0° 37' E, 2638.4 ft from the section cor. common to secs. 18, 19, 13 & 24 on Range line 5 & 6 W.

Thence N 0° 37' E, 2641.42 ft; A 10" x 10" x 14" sandstone with cross on top marked CS & marked 2 notches on North and 4 notches on south faces 12" under ground, making the corner of section 7, 18, 12 & 13, from which, an Iron pipe is the SW cor. to lot 15 of Fruitvale bears S 1° 58' E 1026 ft.

Thence N 0° 37' E, 2641.42 ft. to 24" machine cut barrel driven 10" under ground, tin collar; 1 brick on top with 3 bricks placed around; A 4" x 4" x 48" post 24" in ground marked 1/2 S on N face, C.S. on south face S. 7 on East face & S 12 on West face, from which NE cor. of A. L. C. No. 37 in T 27 S - R 5W bears N 75° 12' E, 924.9 ft. which is the 1/2 section cor. between section 7 & 12.

Thence N 0° 37' E, 2641.42 ft to 5/8" iron bolt 42" long driven 15" under ground and Oak chunk 4" x 6" on top, which is the cor. to secs. 6, 7, 1 & 12 T 27 S - R 5 & 6 W, from which, A W oak 12" diam. bears N 40° E, 75.6 ft. ( marked T 27 S ° R 5 W Sec. 6 C. S. Bt.) A.W. oak 20" Diam. Bears N 46° W 132.0 ft. ( marked T 27 S R 6 W, Sec. 10, ET. ) ( No other tree near).

Thence N 0° 37' E, 2641.4 ft. ( proportional measurement ) to 1" x 24" gun barrel driven 23" in ground & set yellow pine post 3" x 3" x 36", marked N 5-W, Sec. 6 1/2 S, & R 5W, Sec. 10. ST. 27 S. for the 1/2 cor. between sec. 6 & 1 from which.

W Oak 14" diam. bears S 68° 45' E, 59.5 ft.  
Marked 1/2 S 6 CS BT,  
W Oak 20" diam. bears S 83° 10' W 77.7 Ft.  
Marked 1/2 S. L. CS. BT.

Thence N 0° 37' E, 2746.35 ft. to twp. cor. of T 26 & 27 S R 5 & 6 W. where two of old witness trees were found and the corner set; A 1" x 48" pipe 42" in Ground with a mound of rock 20" base and 12" high from which the following new bearing trees were made.

