

COUNTY SURVEYOR'S RECORD, DOUGLAS COUNTY, OREGON

BUSHORS & CO. PORTLAND, ORE. 87545

<i>Survey No.</i>	<i>Made on</i> August 1934	<i>Survey No.</i>	<i>Made on</i>
<i>In Town.</i> 27 S	<i>Range</i> 5 & 6 W <i>Sec.</i> 6 miles	<i>In Town.</i>	<i>Range</i> <i>Sec.</i>
<i>Made for</i> County		<i>Made for</i>	
<i>Purpose of</i> to establish corners on range lines & 6 end donation claim corners along the line		<i>Purpose of</i>	

Crew ran $30^\circ - 56'$ W and at 2643.6 feet found one old bearing tree and stump of another one from which set a $\frac{1}{2}$ " x 16" Gal. iron Pipe for Corner from which new Bearing trees was marked as follows

8" white oak bears n $44^\circ - 30'$ E 8.2 feet marked $\frac{1}{2}$ " S. C. S. B.T.

10" white Oak bears N 46° W 137.8 feet marked $\frac{1}{4}$ " S. C. S. P.T.

Continuing on South the line bears was run from the $\frac{1}{4}$ corner between Sections 25 & 30, 2640.0 feet but as witness trees was gone corner could not be found so continued line south and at 5295.3 found witness trees of the $\frac{1}{4}$ corner between section 31 & 36, which was set by a post from which the following New Witness trees was made, 10" W Oak bears S 54° E 24.6 feet marked $\frac{1}{4}$ " S. C. S. P.T.

10" White Oak bears S $57^\circ - 30'$ W 165.1 feet, marked $\frac{1}{4}$ " S. C. S. P.T.

This line bears S $0^\circ - 41'$ W 5295.3 feet. then by proportional distance

$$\frac{52.80}{5295.3} \times \frac{2640}{x}$$

or the Section Corner Common to section 25-36-31 & 30 bears S $0^\circ - 41'$ W 2647.7 feet from the $\frac{1}{4}$ corner between section 30 & 25 and the line from this Section Corner South to $\frac{1}{4}$ Corner between Section 31 & 36 bears

S $0^\circ - 41'$ W 2647.7 feet The section corner of sections 30 & 31 township 27 south range 5 west & sections 25 & 36 township 27 South, Range 6 West, is a $\frac{3}{4}$ " x 30" iron Rod from which the following New Bearing trees were marked

24" white Oak bears N30E 340 feet

4" laurel, bark blaze, bears n 87° E 158.5 feet

6" Black Oak, bears S 2° E 41.5 feet

18" White Oak, bears N 1° W 146.0 feet.

Thence the line was continued south from the $\frac{1}{4}$ corner, common to Sections 31 & 36 to the section corner of section 31 & 36 or South-West corner of Township 27 South, Range 5 West. This corner was set from one original bearing tree. Set $\frac{3}{4}$ " x 36" round iron bolt for Corner from which new bearing tree

are a 12" white Oak, bears N 22° W 58.5 feet

14" white Oak, bears N $81^\circ - 21'$ E 20.0 feet,

True line ran $30^\circ - 19'$ W 2651.7 feet between $\frac{1}{4}$ corner and township corner.

Thence ran East from South west township corner of Township 27 south range 5 west to the the North west corner of township 28 South Range 5 West. This corner was established from old bearing trees by setting a $\frac{3}{4}$ " x 36" iron bolt for corner.

Marked new bearing trees:

A Black Oak bears S $62^\circ - 15'$ E 152.0 feet

B Black Oak bears S $76^\circ - 20'$ W 226.6 feet.

The true bearing and distance of this line is N $88^\circ - 04'$ E 374.5 feet.

From the North east corner of township 28 South Range 6 West ran East to the $\frac{1}{4}$ Section corner on the South Side of Section 31 Township 27 South, range 5 West,

which $\frac{1}{4}$ section post set from old bearing trees, by driving a $\frac{3}{4}$ " x 36"

iron bolt for corner, r