

COUNTY SURVEYOR'S RECORD, DOUGLAS COUNTY, OREGON

BUSHONG & CO. PORTLAND, ORE. 87545

Survey No.	Made on August, 1934	Survey No.	Made on
In Town. 27 s	Range 5 & 6 W Sec. 6	In Town.	Range Sec.
Made for	County	Made for	
Purpose of	to establish corners on range lines	Purpose of	
	5 & 6 and donation claim corners along the line		

1 1/2" Forked Fir N 56° E 18.6 feet
 16" White Oak N 52° W 20.5 feet

This line is S 89° 52' E. 2580.8 feet. The line on true line S 89° 44' E. 88.0 feet from 1/4 corner on South side of Section 31 to 1/4 corner on the North side of Section 6 Township 27 South Range 5 West, which is section corner on North side of section 6, was located from one old bearing tree. Set a 3/4" x 3/6" round iron bolt for corner & marked New Bearing trees

Notes this insert New Bearing Trees Marked, **HERE.**

14" Fir bears S 22° 25' E 120.3 feet
 8" White Oak bears S 46° - 45' W 17.3 feet.

From this 1/4 corner on the North side of Section 6 the true line ran N 89° - 54' E 2650.6 feet to the corner of section 31 & 32 township 27 South, Range 5 West, which was established from original trees by setting 3/4" x 3/6" round iron Bolt from which,

30" Fir Bears N 70° - 45' W 65.3 feet old bearing tree
 24" Fir bears N 9° E 11.4 feet new bearing tree.

The corner to section 5 & 6 in township 28 South Range 5 West was set but the line between the corner 31 & 32 to corner 5 & 6 was not run.

This corner was set from old Bearing trees by setting a 3/4" by 3/6" round iron Bolt. remarked on new blaze, B.T. on old bearing trees but did not cut out old markings. These trees are-

36" Fir bears S 65° - 30' E 56 lks.
 16" Fir bears S 1° W 16 lks.

Thence from the corner to sections 31 & 32 in Township 27 South, Range 5 west ran North on line between Section 31 & 32 to 1/4 corner where one old bearing tree was found. This line ran N 0° - 16' W, 2661.9 feet, set a point for corner and marked two new bearing trees

24" Pine S 36° - 45' W 18.0 feet marked **15.04 FT.**
 12" Fir S 54° E 28.0 feet Marked 1/4 B. O. S. B.T.

Thence from 1/4 Section Corner between Section 31 & 32, continued N. 0° - 17' W 2668.1 feet to the section corner, common to section 29, 30, 31, 32, which is a 3/4" iron pipe in place, from which two old bearing trees still standing with scribe marks visible. Four new bearing trees was marked for this corner as follows

16" white Oak S 76° - 45' W 77.2 feet
 12" white Oak N 40° - 30' W 57.3 feet
 24" White Oak S 5° - 15' W 71.5 feet
 16" white Oak N 17° - 00' E, 88.9 feet

Thence from the corner of Section 29-30-31-&32, an S 89° 24' W 2670.8 feet to the 1/4 corner between Section 30 & 31, which corner is 1" Iron pipe in place, with one of the Original bearing trees in evidence, other gone. Marked new Bearing trees as follows.

8" white Oak N 10° W 69.0 feet
 6" white Oak South 190.0 feet

Thence from 1/4 corner between section 30 & 31 continued S 89° - 12' W 2083.6 ft.