

# COUNTY SURVEYOR'S RECORD, DOUGLAS COUNTY, OREGON

BUSHONG & CO. PORTLAND, ORE. 87545

<p>Survey No.                      Made on April-May 1949</p> <p>In Town. 29 S      Range 4W              Sec. 25</p> <p>Made for Harvey Potter &amp; Ivan Taylor</p> <p>Purpose of Subdividing Sec. 25.</p> <p style="text-align: center;">CONTINUED</p>	<p>Survey No.                      Made on</p> <p>In Town.                      Range                      Sec.</p> <p>Made for</p> <p>Purpose of</p>
---	---

The E 1/16 Cor. S 25-36 was established at the mid-point on the line between 1/4 Cor. 25-36, and Sec. Cor. 25-36, by setting a 3/4" Galv. Iron Pipe from which a 20" Fir bears S 24 1/2° W, 9.7 ft., blazed and scribed E 1/16 S 36, C.S.B.T., and a 24" Fir bears N 33° E 20.7 ft., blazed and scribed E 1/16 S 25, C.S.B.T.

The W 1/16 Cor. S 25-36 was established at the mid-point on the line between 1/4 Cor. 25-36 and Sec. Cor. 25-26-35-36 by setting a 3/4" Galv. Iron Pipe, from which a 10" Cedar bears S 5° E 7.1 ft., blazed and scribed W 1/16 S 36, C.S.B.T., and an 18" Fir bears N 28° E 5.1 ft., blazed and scribed W 1/16 S 25 C.S.B.T.

A traverse was run from the cor. to Secs. 25-26-35-36 to the cor. to Secs. 23-24-25-26, the point of beginning. Bearing and distance of this line was N 3° 53' E 4845.2 ft.

A careful search failed to reveal any evidence of the 1/4 cor. between S 25-26 and this Cor. was reestablished by proportionate measurement at the mid-point of the line between Secs. 25-26-35-36 and Secs. 23-24-25-26 by setting a 1 1/4" x 36" Iron Pipe, from which a 14" Laurel bears N 46° E 24.4 ft., blazed and scribed T 29 S, R 4 W, S 25 C.S.B.T. and a 14" Fir bears S 35° W 11.3 ft., blazed and scribed T 29 S, R 4 W S 26 C.S.B.T. (Nailed brass disk to above B.T. marked Co. Surveyor's Office 1/4 Sec. Cor. 25-26 set by Reg. Engr. Ore. No. 2741)

The location of the N 1/16 Cor. 25-26 at the mid-point on the line between 1/4 Cor. 25-26 and Sec. Cor. 23-24-25-26 was in the center of a large sawdust pile and a 1 1/4" Iron Pipe was set S 43° 30' E 170.6 ft. for a witness corner, no trees were available for B.T.s.

A traverse was run from the 1/4 cor. of Secs. 24-25 to the 1/4 Cor. of Secs. 25-36, resultant bearing and distance S 2° 14' W 4937.6 ft.

And a traverse was run between the 1/4 Cor. East side of Sec. 25 to the 1/4 cor. of Secs. 25-26 with a resultant bearing and distance of S 77° 44' W 5139.3 ft.

The intersection of the center lines of the section was computed and at that point a 3/4" x 36" Galv. Iron Pipe was set from which an 18" Fir bears N 42° E 57.4 ft. and a 15" Cedar bears S 65° W 78.2 ft., both blazed and scribed T 29 S, R 4 W, C 1/4 S 25, C.S.B.T.

- 1/4 Cor. Secs. 24-25-
  - S 2° 14' W 2468.6 ft.
- C 1/4 Cor. Sec. 25
  - S 2° 14' W 2468.9 ft.
- 1/4 Cor. Secs. 25-36
  -
- 1/4 Cor. E. side Sec. 25
  - S 77° 44' E 2569.2 ft.
- C 1/4 Cor. Sec. 25
  - S 77° 44' E 2570.1 ft.
- 1/4 Cor. 25-26

At the mid-point of the line between 1/4 cor. E. side Sec. 25, and the C 1/4 Cor. Sec. 25, a 3/4" Galv. Iron Pipe was set for the CE 1/16 cor. Sec. 25, from which a 20" Fir bears S 18° W 12.6 ft. and a 20" Cedar bears N 50° W 9.8 ft., both blazed and scribed C E 1/16 S 25, C.S.B.T.

At the mid-point of the line between 1/4 Cor. Secs. 25-26 and C 1/4 Cor. Sec. 25 a 3/4" Galv. Iron Pipe was set for the C W 1/16 Cor. Sec. 25, from which a 26" Fir bears S 15° E 19.6 ft., and an 18" Fir bears N 65° W 16.3 ft., both blazed and scribed CW 1/16 S 25 C.S.B.T.

At the mid-point of the line between 1/4 Cor. Sec. 24-25 and C 1/4 Cor. Sec. 25, a 48" Fir was blazed and scribed for the CN 1/16 Cor. Sec. 25, blazed on three sides and scribed on E face, CN 1/16 Cor. S 25 C.S.B.T. R.E. 2741, from which a 12" Cedar bears N 85° W 20.6 ft., blazed and scribed CN 1/16 Cor S 25, C.S.B.T.

A traverse was run from the CW 1/16 cor. to the W 1/16 cor. Secs. 24-25 with a resultant bearing and distance N 3° 03' E 2445.8 ft.

The bearing and distance of the line between the CN 1/16 Cor. Sec. 25 and N 1/16 cor. Sec. 25-26 was computed to be S 77° 02' W 2542.1 ft.

The intersection of the center lines of the NW 1/4 was computed and at that point a 1/2" Iron Pipe was set for the NW 1/16 Cor., from which an 18" Cedar bears S 5° E 14.9 ft. blazed and scribed NW 1/16 S 25, C.S.B.T.

A traverse was run from the NW 1/16 Cor., Sec. 25 to the CN 1/16 Cor. Sec. 25, resultant bearing and distance N 77° 02' E 1270.9 ft.

All bearings in this survey were computed from angles turned in deflection from a meridian established by Solar Observation at the East 1/4 Cor. Sec. 24, T 29 S, R 4 W, taken during the course of a power line survey for the Hollinger Tap-line by Ben B. Irving, Deputy County Surveyor, in October 1940.