

COUNTY SURVEYOR'S RECORD, DOUGLAS COUNTY, OREGON

BUSHONG & CO. PORTLAND, ORE. 87545

<i>Survey No.</i>	<i>Made on</i>		<i>Survey No.</i>	<i>Made on</i>	
<i>In Town.</i>	<i>Range</i>	<i>Sec.</i>	<i>In Town.</i>	<i>Range</i>	<i>Sec.</i>
<i>Made for</i>			<i>Made for</i>		
<i>Purpose of</i>			<i>Purpose of</i>		

~~6-5-48~~

The intersection of the center lines of the NE $\frac{1}{4}$ was computed and an 8" x 12" granite stone in place was marked with a cross for the NE 1/16 corner Section 32, from which

A 50 in. Cedar bears S 24° E, 7.5 ft. and

A 20 in. Hemlock bears N 80° W 11.6 ft., both blazed and scribed NE 1/16 S 32 C. S. B. T.

The various properties were then subdivided and monumented as shown on the accompanying map which is a part of this record. All bearings in this survey were computed from angles turned in deflection from a meridian established by solar observation taken at the Section Corner to Sections 28 - 29 - 32 - 33, April 23, 1951.

A Buff and Buff transit with plates reading to one minute of arc, in good adjustment was used and all angles were doubled. All chaining was carefully done by experienced chainmen, using a 300 ft. Keufel and Esser steel tape in good condition. Measurements were made on the slope, vertical angles were carefully recorded and distances reduced to the horizontal.

A closed traverse was run around the North $\frac{1}{2}$ of the NE $\frac{1}{4}$ which contained the most valuable portion of the properties surveyed, and a good closure was obtained.



ARTHUR R. EVANS
Deputy County Surveyor