RM 3-55

N 89°58'21.2" E , 2637.30
(U.S.G.L.O. Record N 89°44'E , 2649.24)

6 5 — 7 8 — 5 1/4 S — 8

1318.65 — W 1/16 — 1318.65

Found Brass cap mkd.
"T30S, R2W
S5, S6, S7, S8
B.L.M. 1970
From which a ;

24" Madrone, original BT.
Scribes visible
Bears N 75 1/2°E, 15.8 ft.

38" Douglas Fir, original BT.
Bark scribes visible
Bears S 43 1/2°E, 27.7 ft.

14" Madrone, original BT.
No scribes visibles, Rotted face
Bears S 23 1/2°W, 24.4 ft.

24" Madrone, original BT.
Bark scribes visible
Bears N 70°W, 17.3 ft.
(Record 18.5 ft.)

6" Douglas Fir BT.
Healed over face
Bears S 15°W, 7.3 ft.

14" Madrone BT.
Scribes visible
Bears N 1°W, 18.5 ft.

N 0°04'00" W, 1326.53
(U.S.B.L.M. 1970 Record N 0°04' W, Basis of Bearings, 1326.60)

Set Brass cap mkd.
"T30S, R2W, W.M.
W 1/16, S5, S8
Shaner Engineering
R.L.S. 430, 1981"
From which a ;

56" Douglas Fir BT, I scribed
"W 1/16, S5 BT"
Bears N 60°E, 42.7 ft.

16" Hemlock BT, I scribed
"W 1/16, S8 BT"
Bears S 18°E, 50.0 ft.

Steel fence post set alongside.

Found Brass cap mkd.
"T30S, R2W
1/4, S5, S8
County Surveyor, 1968"
From which a ;

32" Douglas Fir, original BT.
Healed over face
Bears North, 19.8 ft.

28" Madrone BT.
Healed over face
Bears N 69°W, 29.4 ft.

8" Cedar BT.
Scribes visible
Bears S 16°E, 14.0 ft.

LEGEND

Corners Found ◉
Corners Set ◎
Lines Traversed ———
Lines Computed — — —

Basis of Bearings is
West Line NW 1/4 NW 1/4
as per U.S.B.L.M. 1970 Survey

200 0 200 400
Scale 1 inch = 200 feet

N 1/16 ◉

W 1/2 NW 1/4
Paul Barber

E 1/2 NW 1/4
Longview Fibre Co.

N 0°01'57.6" W, 2655.49

S 0°01'14.5" E, 2657.62

NE 1/4
Roseburg Lumber Co.

Found Brass cap mkd.
"N 1/16, S7, S8
B.L.M. 1970"
From which a ;

12" Douglas Fir BT.
Healed over face
Bears S 28°E, 53.5 ft.

16" Douglas Fir BT.
Healed over face
Bears N 83°W, 40.9 ft.

N 0°01'25.7" W, 1326.83
(U.S.B.L.M. 1970 Record N 0°04'W, 1326.60)

Found Brass cap mkd.
"T30S, R2W
S8, S9
County Surveyor, 1968"
From which a;

10"X 9"X 5" Stone
No marks
Lays alongside

16" Split Maple, original BT.
No scribes visible
Bears S 53 1/2°W, 4.2 ft.
(Record 5.9 ft.)

8" Douglas Fir stump BT.
Tin covering stump
No scribes visible
Bears N 55°E, 54.0 ft. (Record N 60°E)

12" White Fir BT, Dead & Down, scribes visible
Bears N 61°W, 32.7 ft.
(Record N 65°W)

14" Douglas Fir BT, I scribed
" 1/4, S8 BT"
Bears S 76°W, 63.3 ft.

16" Douglas Fir BT, I scribed
"1/4, S9 BT"
Bears S 40°E, 48.9 ft.

Set Brass cap mkd.
"T30S, R2W, W.M.
C 1/4, S8
Shaner Engineering
R.L.S. 430, 1981"
From which a ;

14" Douglas Fir BT, I scribed
"C 1/4, S8 BT"
Bears S 5°W, 8.4 ft.

10" Douglas Fir BT, I scribed
"C 1/4, S8 BT"
Bears N 53°W, 16.7 ft.

Steel fence post set alongside.

1/4 S — 7 8 — CW 1/16 — C 1/4 — 8 9 — 1/4 S

1318.10 — 1318.10

N 89°56'05" W, 2636.20 — S 89°56'05" E, 2642.79

Found Brass cap mkd.
"T30S, R2W
1/4, S7, S8
B.L.M. 1970"
From which a;

14" Pine BT.
Healed over face
Bears N 57°E, 14.8 ft.
(Record 18.5 ft.)

10" White Fir BT.
Healed over face
Bears N 60 1/2°W, 22.4 ft.

Set Brass cap mkd.
"T30S, R2W, W.M.
CW 1/16, S8 BT.
Shaner Engineering
R.L.S. 430, 1981"
From which a ;

8" Douglas Fir BT, I scribed
"CW 1/16, S8 BT"
Bears N 27°E, 26.0 ft.

6" Douglas Fir BT, I scribed
"CW 1/16, S8 BT"
Bears N 67°W, 6.0 ft.

Steel fence post set alongside.

landing

N 1/2 SE 1/4
Roseburg Lumber Co.

1311.40

Set Brass cap mkd.
"T30S, R2W, W.M.
CS 1/16, S8
Shaner Engineering
R.L.S. 430, 1981"
From which a ;

16" Douglas Fir BT, I scribed
"CS 1/16, S8 BT"
Bears S 1°E, 7.0 ft

14" Douglas Fir BT, I scribed
"CS 1/16, S8 BT"
Bears S 53°W, 26.5 ft.

Steel fence post set alonside.

1314.26

Set Brass cap mkd.
"T30S, R2W, W.M.
S 1/16, S8, S9
Shaner Engineering
R.L.S. 430, 1981"
From which a ;

16" Douglas Fir BT, I scribed
"S 1/16, S9 BT"
Bears S 54°E, 41.4 ft.

24" Cedar BT, I scribed
"S 1/16, S8 BT"
Bears S 60°W, 55.5 ft.

Steel fence post set alongside.

S 0°06'42" W, 2628.51
(U.S.G.L.O. Record S 0°03'E, 2640.00)

N 0°01'14.5" W, 2622.80

CS 1/16 — S 89°52'21.4" E, 2639.76 — S 1/16

SE 1/4
Longview Fibre Co.

S 1/2 SE 1/4
Longview Fibre Co.

Found Brass cap mkd.
"T30S, R2W
1/4, S8
County Surveyor, 1968"
From which a ;

10"X 8"X 7" Stone mkd. "X"
Lays alongside

24" Douglas Fir stump, original BT.
Scribe "B" visible
Bears N 41 1/2°W, 21.8 ft.

12" Maple, original BT.
Rotted
Bears N 40°E, 29.0 ft.

12" Hemlock BT
Scribes visible
Bears N 2°W, 24.6 ft.

12" Hemlock BT, Dead & Down, no scribes visible
Bears N 67°W, 21.2 ft.

8" White Fir BT, I scribed
"1/4, S17 BT"
Bears S 68°W, 21.9 ft.

1311.40

Found Brass cap mkd.
"T30S, R2W
S8, S16, S17
County Surveyor, 1968"
From which a ;

12"X 8"X 6", original stone
4 notches on top
Lays alongside

18" Maple, original BT, Dead & Down, reverse scribes visible
Bears S 57°W, 25.7 ft.

10" Cedar BT.
Scribes visible
Bears S 81°W, 48.6 ft.

12" Cedar BT.
Scribes visible
Bears N 69°E, 23.2 ft.

1314.25

Found Brass cap mkd.
"T30S, R2W
S8, S9, S16
County Surveyor, 1968"
From which a ;

7" Douglas Fir, original BT.
Down and burnt
Bears N 24°E, 13.2 ft, is now gone.

14" Douglas Fir BT.
Healed over face
Bears N 56°W, 65.0 ft.

12" Douglas Fir BT.
Healed over face
Bears S 25°W, 18.2 ft.
(Record 17.0 ft.)

8" Douglas Fir BT, I scribed
"T30S, R2W, S9 BT"
Bears N 65°E, 21.4 ft.

Found Brass cap mkd.
"T30S, R 2W
1/4, S17
County Surveyor, 1968"
From which a ;

Stone 12"X 7"X 7", mkd.
"1/4" lays alongside.

36" Cedar, original BT.
Healed over face
Bears S 49 1/2°E, 23.8 ft.

56" Douglas Fir, original BT.
Healed over face
Bears S 67°W, 19.8 ft.

N 89°48'38" W, 2636.73
(U.S.G.L.O. Record West, 2640.00)

1/4, S17 — 1/4, S8 — 8 9

2522.47

N 89°53'10.3" W, 115.42
(U.S.G.L.O. Record West, 115.50

Closing Corner falls South, 0.91 feet from True Line.

114.26
(Record 115.50)

17 16

NARRATIVE

Survey was performed for the purpose of setting property corners as shown hereon. A Franke 20" theodolite and a "Mac I" Electronic Distance Meter were the instruments used. The original survey of the Section was accomplished by Fred Mensch, U.S.G.L.O., 1909. The U.S.B.L.M. (Harvey Wofford) resurveyed the West line of the the Section in 1970

All Brass Caps set were 2 1/2" Diameter, on a 2"X 32" Iron Pipe.

PROPERTY LINE SURVEY TO SET CORNERS IN SECTION 8, T30S, R2W, W.M., DOUGLAS COUNTY, OREGON

For : Longview Fibre Company
P.O. Box 598
Roseburg, Oregon 97470

By : Shaner Engineering, Inc.
P.O. Box 1430
Roseburg, Oregon 97470

BA Shaner

October, 1981 thru January, 1982
(Roads added Feb. 22, 82. BAS)

RM 3-55