

COUNTY SURVEYORS FILE DATA  
DO NOT REMOVE FROM OFFICE

NE 1/4, NW 1/4 & SE 1/4 SEC. 17, T. 22 S., R. 10 W., W.M.

FILED

Date: 11/30/2000 By: JP  
This survey consists of: 5 Pgs.  
Map: M136-14D  
Narrative: \_\_\_\_\_  
Corner Rpt: \_\_\_\_\_

DOUGLAS COUNTY  
JP SURVEYOR

POINT ID	LDP NORTHING	LDP EASTING	DESCRIPTION
5	226588.354	1224749.922	SET 16 mm X 762 mm IRON REBAR W/A 38 mm ALUMINUM CAP STAMPED "ODOT HORIZ. CONTROL 5".
7	226688.818	1224590.536	SET 16 mm X 762 mm IRON REBAR W/A 38 mm ALUMINUM CAP STAMPED "ODOT HORIZ. CONTROL 7".
10	226715.759	1224568.223	SET 16 mm X 762 mm IRON REBAR W/A 38 mm ALUMINUM CAP STAMPED "ODOT HORIZ. CONTROL 10".
16	226595.501	1224713.898	SET 16 mm X 762 mm IRON REBAR W/A 38 mm ALUMINUM CAP STAMPED "ODOT HORIZ. CONTROL 16".
LUDER	226605.572	1224821.489	FOUND 3" BRASS DISK SET IN CONCRETE, FLUSH WITH SURFACE IN GOOD CONDITION. STAMPED "OREGON D.O.T. DO NOT DISTURB 1995 LUDER GEODETIC CONTROL POINT".
C17	226801.636	1224456.392	FOUND 3/4" I. REBAR SET IN VALVE BOX. 50 mm BELOW AC IN GOOD CONDITION. CENTER OF SEC. 17, T22S, R10W, W.M.
1000	226712.114	1224587.540	FOUND 5/8" I. REBAR W/A 1 1/4" YELLOW PLAST. CAP STAMPED "LS 1091" 15 mm ABOVE SURFACE IN GOOD CONDITION. (DCSO MAP NO. M123-26) - "RW" 17+747.915, 22.852 m LT.
1001	226620.636	1224709.798	FOUND 5/8" I. REBAR W/A 1 1/4" YELLOW PLAST. CAP STAMPED "LS 1091" FLUSH W/SURFACE IN GOOD CONDITION. (DCSO MAP NO. M123-26) - "RW" 17+903.228, 22.858 m LT.
1004	226673.254	1224739.863	FOUND 5/8" I. REBAR W/A 1 1/4" YELLOW PLAST. CAP STAMPED "LS 1091" 350 mm BELOW SURFACE IN GOOD CONDITION. (DCSO MAP NO. M123-26).
1005	226601.551	1224733.650	FOUND 3/4" I. REBAR 290 mm BELOW SURFACE IN GOOD CONDITION - "RW" 17+934.098, 19.838 m LT.
1006	226637.360	1224685.198	FOUND 5/8" I. REBAR W/A 1 1/4" YELLOW PLAST. CAP STAMPED "LS 1091" 80 mm ABOVE SURFACE IN GOOD CONDITION. (DCSO MAP NO. M123-26) - "RW" 17+872.987, 22.847 m LT.
1007	226651.441	1224763.721	FOUND 5/8" I. REBAR W/A 1 1/4" YELLOW PLAST. CAP STAMPED "LS 1091" 200 mm BELOW SURFACE IN GOOD CONDITION. (DCSO MAP NO. M123-26).
1008	226693.411	1224610.891	FOUND 5/8" I. REBAR W/A 1 1/4" YELLOW PLAST. CAP STAMPED "LS 1091" 60 mm ABOVE SURFACE IN GOOD CONDITION. (DCSO MAP NO. M125-64) - "RW" 17+778.332, 23.205 m LT.
1009	226732.568	1224563.717	FOUND 1 1/4" YELLOW PLAST. CAP STAMPED "LS 1091" SET FLUSH IN AC IN GOOD CONDITION. (DCSO MAP NO. M123-26) - "RW" 17+715.994, 22.853 m LT.
1010	226792.680	1224598.075	FOUND 5/8" I. REBAR W/A 1 1/4" YELLOW PLAST. CAP STAMPED "LS 1091" 30 mm ABOVE SURFACE IN GOOD CONDITION. (DCSO MAP NO. M123-26).
1011	226770.140	1224620.716	FOUND 5/8" I. REBAR W/A 1 1/4" YELLOW PLAST. CAP STAMPED "LS 1091" FLUSH W/SURFACE IN GOOD CONDITION. (DCSO MAP NO. M123-26).
1012	226750.335	1224643.447	FOUND 5/8" I. REBAR W/A 1 1/4" YELLOW PLAST. CAP STAMPED "LS 1091" FLUSH W/SURFACE IN GOOD CONDITION. (DCSO MAP NO. M125-64).
1013	226729.334	1224667.546	FOUND 5/8" I. REBAR W/A 1 1/4" YELLOW PLAST. CAP STAMPED "LS 1091" FLUSH W/SURFACE IN GOOD CONDITION. (DCSO MAP NO. M123-26).
1014	226687.297	1224713.757	FOUND 5/8" I. REBAR W/A 1 1/4" YELLOW PLAST. CAP STAMPED "LS 1091" FLUSH W/SURFACE IN GOOD CONDITION. (DCSO MAP NO. M123-26).
1015	226673.539	1224635.673	FOUND 5/8" I. REBAR W/A 1 1/4" YELLOW PLAST. CAP STAMPED "LS 1091" FLUSH W/SURFACE IN GOOD CONDITION. (DCSO MAP NO. M123-26) - "RW" 17+810.629, 22.848 m LT.
1022	226603.517	1224736.376	FOUND 5/8" I. REBAR W/A 1 1/4" YELLOW PLAST. CAP STAMPED "LS 1091" 340 mm BELOW SURFACE IN GOOD CONDITION. (DCSO MAP NO. M123-26) - "RW" 17+935.369, 22.956 m LT.

TO CONVERT A METRIC DISTANCE TO FEET, DIVIDE BY 0.3048

REGISTERED  
PROFESSIONAL  
LAND SURVEYOR

*Christine V. Blevins*

OREGON  
JULY 19, 1994  
CHRISTINE V. BLEVINS  
2669

EXPIRES: DEC. 31, 2001



OREGON DEPARTMENT OF TRANSPORTATION  
HORIZONTAL CONTROL,  
RECOVERY AND RETRACEMENT MAP  
CHARLOTTE CR. - LUDER CR. PASSING LANE SEC.  
UMPOUA HWY. (HWY. 38)  
DOUGLAS COUNTY  
3500 STEWART PARKWAY, SUITE 140  
ROSEBURG, OREGON 97470

NOVEMBER 17, 2000  
PROJECT KEY \*10842

SHEET 4 OF 5

ST. HWY. 38-008D