


AFFIDAVIT OF CORRECTION:
RECORDED NOV. 15, 2007 AS
INSTRUMENT No. 2007-024428
COUNTY CLERK RECORDS
C.S. FILE 65/62-7

DETAIL H
SCALE: NTS



CURVE	CHORD BEARING	CHORD LENGTH	RADIUS	CURVE LENGTH	DELTA
C1	S49°02'30"W	13.75'	12.00'	14.65'	69°56'12"
C2	N11°01'05"E	95.63'	50.00'	127.39'	145°59'01"
C3	S24°31'30"E	18.24'	15.00'	19.61'	74°53'51"
C4	N09°03'38"E	29.65'	220.00'	29.67'	7°43'35"
C5	S49°31'47"W	16.77'	12.00'	18.57'	88°39'53"
C6	S31°17'44"W	28.40'	50.00'	28.80'	32°59'54"
C8	N06°29'00"E	57.83'	200.00'	58.04'	16°37'35"
C9	N67°46'33"W	81.91'	130.00'	83.32'	36°43'26"
C10	N69°27'26"W	102.82'	150.00'	104.95'	40°05'13"
C11	N68°48'38"W	112.92'	170.00'	115.10'	38°47'36"
C12	S54°27'05"E	29.86'	170.00'	29.89'	10°04'31"
C13	S65°19'00"E	82.20'	150.00'	83.27'	31°48'21"
C14	S57°31'10"E	36.66'	130.00'	36.78'	16°12'40"
C15	S70°21'16"E	64.09'	170.00'	64.48'	21°43'50"
C16	S73°25'20"E	35.27'	130.00'	35.38'	15°35'41"
C17	S89°25'55"E	85.71'	300.00'	86.00'	16°25'30"
C18	S81°37'43"E	4.57'	320.00'	4.57'	0°49'05"
C19	S87°21'26"E	59.87'	280.00'	59.99'	12°16'32"
C20	S89°50'28"E	86.90'	320.00'	87.17'	15°36'25"
C21	N80°25'45"E	34.96'	520.00'	34.96'	3°51'09"
C22	N80°09'42"E	36.75'	480.00'	36.76'	4°23'15"
C23	N73°42'22"E	86.97'	520.00'	87.07'	9°35'39"
C24	N70°52'45"E	118.47'	480.00'	118.78'	14°10'41"
C25	N64°06'43"E	86.97'	520.00'	87.07'	9°35'39"
C26	N68°29'10"E	239.71'	500.00'	242.07'	27°44'20"
C27	N59°35'19"E	70.33'	480.00'	70.40'	8°24'11"

CURVE	CHORD BEARING	CHORD LENGTH	RADIUS	CURVE LENGTH	DELTA
C28	N57°18'03"E	36.55'	520.00'	36.56'	4°01'42"
C29	N27°22'21"E	15.97'	17.00'	16.62'	56°01'44"
C30	S82°37'23"W	15.61'	17.00'	16.22'	54°40'22"
C31	S20°20'58"W	34.39'	48.00'	35.17'	41°58'57"
C32	N80°45'02"E	46.85'	48.00'	48.94'	58°25'03"
C33	N23°09'45"E	45.63'	48.00'	47.55'	56°45'33"
C34	S78°39'50"W	58.21'	48.00'	62.54'	74°38'48"
C35	N34°36'54"W	47.12'	48.00'	49.26'	58°47'44"
C36	S49°12'43"E	15.10'	12.00'	16.33'	77°59'25"
C38	N11°24'42"W	7.09'	170.00'	7.09'	2°23'22"
C56	N84°25'49"E	20.27'	280.00'	20.28'	4°08'58"
C57	S64°30'26"W	28.76'	50.00'	29.17'	33°25'31"
C58	N80°22'37"W	31.57'	50.00'	32.12'	36°48'23"

LINE	BEARING	LENGTH
L1	N75°12'13"W	20.00'
L2	S89°30'03"E	24.67'
L3	N01°49'48"W	5.08'
L4	N01°49'48"W	4.21'
L5	S81°13'10"E	19.84'
L6	S81°13'10"E	19.84'
L7	S81°13'10"E	19.84'

LEGEND

- ◻ SET 5/8" x 30" IR w/CAP MARKED "I.E. ENGINEERING" UNLESS OTHERWISE NOTED
- FOUND 5/8" IRON ROD UNLESS OTHERWISE NOTED
- ⊙ FOUND 3/4" IRON PIPE
- △ CALCULATED POSITION
- () R1 RECORD AS PER LP 2005-0069

REGISTERED PROFESSIONAL LAND SURVEYOR

Ronald A. Gumbay

OREGON
JULY 14, 1978
RONALD A. GUMBAY
1954

EXPIRES: 12/31/2006

WAREWOOD TERRACE P.U.D.
LYING IN THE NW 1/4 OF SECTION 11, TOWNSHIP 27 SOUTH, RANGE 6 WEST, WILLAMETTE MERIDIAN, DOUGLAS COUNTY, OREGON

SURVEYED FOR:
JERRY TABOR
615 DAIRY LOOP RD.
ROSEBURG, OR 97470

SURVEYED BY:
i.e.
ENGINEERING
741 SE Jackson Street
Roseburg, Oregon 97470
PHONE (541) 673-0166
FAX (541) 440-9392
jemail@ieengineering.com

DWG. BY: JAC

SCALE: AS SHOWN DATE: JULY, 2006 JOB NO: 104-30 PAGE: 2 OF 3