



Description of Corners

Corner	Marked by	Witness Trees
1/4	Pipe	20' W.O. N78 1/2° W 36.3 ft 15' B.O. S19° W 39.2
2	Claim & Section	I. Bar 4' Prune N57 1/2° E 61
3	SW. Cl. 48	I. Bar 20' W.O. N18° E 98.6 B. Rock N78° W 21.8
4	SE. Cl. 47	I. Bar 14' W.O. S73° E 223.3
5	W.C. 191.2 ft E. of Sec. Cor	I. Pipe 6' B.O. S31° W 18.5
6	W.C. 245.8 S of Sec. Cor	Rock 6' W.O. S39° E 43.2
7	1/16	Rock 18' B.O. S33° E 26.1 16' Y. Pine N73° E 54.2
8	W.C. Cl. 47	Rock 8' Fir S12° E 18.2 18' Laurel (O.B.T.) 21.7
9	Cent NW 1/4	I. Bar 18' Fir S87 1/2° E 81.3
10	1/16 Cor	Cedar Stk. 16' Fir N12° 10' E 107.4
11	1/4	Pitch Knot 12' Fir S28° E 45.2 48' " N38° W 36.2
12	1/16	I. Pipe 12' Fir S60° E 5.2 12' " N18 1/2° W 37.5
13	1/4	Stk and Rock Mound 18' B.O. N56° W 41.2 12' W.O. N80° E 66.2
14	1/4	I. Pipe 14' W.O. N17° 40' W 325.7 Boulder S13° W 70.6

Subdivision of NW 1/4 of
Sec. 15 T. 30S. R. 4W
Douglas Co. Ore.

Surveyed Dec. 29 1922
By G. G. Stewart, Deputy Co. Sur.
Licensed Engineer No. 1250

Variation 21° 05' E Bearings Magnetic
Scale 1 inch = 500 ft

**COUNTY SURVEYORS FILE DATA
DO NOT REMOVE FROM OFFICE**

C.S. File No. 7/31
AND Vol. 3, PAGE 136

M 2-9