

28 27  
33 34

FOUND 3/4" IRON PIPE SET FOR  
CORNER BY G. B. STEWART FEB.  
1922 SEE VOL. 3, PAGE 113 & 115  
SURVAY RECORDS  
RENEW CORNER BLAZE & SCRIBE  
6" W.D. EAST 87' 58" T28S R4W  
C.S. BT. BLAZE & SCRIBE 10" MAPLE  
570N 29.6' S33 T28S, R4W C.S. BT  
BLAZE & SCRIBE 10" W. O. S37A  
64.5' ON SLOPE, S34 T28S R4W SBT  
BLAZE & SCRIBE 16" PIN N86°W  
1000' ON SLOPE S28 T28S, R4W C.S. BT

MAR 20' 30"

RENEW N 1/4 S33/34 T28S, R4W  
FOUND 1/2" IRON PIPE & BASE OF  
PUTTING STUMP, WHICH CHECKS  
BEARING & DISTANCE FOR STEWART  
B.T.; BLAZE & SCRIBE 10" CEDAR  
WEST 342' N 1/4 W 534 C.S. BT.

NOTE  
THE 1/4 COR. SET AS PER POSITION  
CALL ON THE BASIS OF "THE LINEAL  
METHOD OF ADJUSTMENT, BASED UPON  
THE 1/4 COR. AS FOUND

NOTE:  
BEARINGS ARE BASED ON  
N 45° 35' 55" N BETWEEN ENG'S  
STATION 427+36.51 & 429+54.52

RENEW 1/4 COR. 33/34 T28S, R4W, SET BRASS  
COR. MKD 1/4 S33/34 T28S, R4W COUNTY  
SURVEYORS OFFICE 1957. BLAZED & SCRIBED  
14" MAPLE S38°E MKD 145.34 C.S. BT. BLAZED  
& SCRIBED 10" ENEWOOD COR. FENCE POST  
540N 45°45' 33" C.S. BT.

RENEW C.W. 1/4 S34 T28S, R4W  
FOUND 1/2" IRON PIPE & STUMP  
OF BT.; BLAZE & SCRIBE 16"  
CEDAR N 163°W 150' C.W. 1/4  
S34 C.S. BT.

FOUND C.S. 1/4 S33 3/4" PIPE  
FOUND STEWARTS BT. NOV 28"  
CEDAR BEARS N 12°N 50.0"  
CALLED NORTH 50.0' BY STEWART  
N 89° 30' 15" E

1342.32'

589°43'25" E

1311.5'

FOUND 3/4" IRON PIPE SET BY  
STEWART FOR S 1/4 S33/34 AT  
N. R/W FENCE OF SLIDE CREEK  
ROAD

FOUND 1/2" IRON PIPE B.T.S. O.K.  
CHECK BEARING & DISTANCE  
SEE STEWART SURVAY, 1922

COUNTY SURVEYORS  
DO NOT REMOVE FROM

COUNTY SURVEYOR'S OFFICE  
DOUGLAS COUNTY, OREGON

SURVEY TO RENEW 1/4 CORNER TO  
SECTION 33 & 34 T28S, R4W, WM.

FRED M. DARBY COUNTY SURVEYOR  
SURVEYED APRIL 23, 1957 BY  
JAMES W. BYRON - DEPUTY SCALE 1" = 200'  
SURVEYED FOR DOUGLAS COUNTY

James W. Byron