

NOTE: BEARINGS SHOWN ARE MAGNETIC
BASED ON A COMPASS BEARING
OF EAST.

VAR.: 20°30'

RENEW 31/32 T33S, R5W, FOUND PIPE
AT COR. AND ALL B.T.S. SET BRASS CAP AT
COR. MKD. COUNTY SURVEYORS OFFICE 1958
T33S, R5W; NEW BT. 5" W. FIR 5.65W 11.6'
C.S. BT. 5.31-32 C.S. BT.
NOTE: DESTROYED ALL EVIDENCE OF
STANDARD COR.

3.38' NORTH FROM COR. TO
TRUE LINE.
FOUND STONE AT COR. MKD. 6.5 T33S, R5W
BT. SET BRASS CAP AT COR. MKD. 6.5 T33S, R5W
COUNTY SURVEYORS OFFICE 1958. NEW BT. 5" W. FIR 5.65W 11.6'
FIR BEARS SIDE 18.0' SCRIBED T33S, R5W C.S. BT.
C.S. BT. 16" ACORN OAK 5.40' W 12.8' SCRIBED
T33S, R5W C.S. BT.

SET 1/4 COR. BY PROPORTION; SET BRASS CAP AT
COR. MKD. COUNTY SURVEYORS OFFICE 1958
SOUTH 1/4 S. 31' SCRIBED 1/4 S. 31' C.S. BT.; 10" W. FIR BEARS
N33°0'E 3.5' SCRIBED 1/4 S. 31' C.S. BT.; 10" LAUREL BEARS
N27°30' W 33.2' SCRIBED 1/4 S. 31' C.S. BT.

380.0'
SET 1/4 COR. BY PROPORTION; SET BRASS CAP
AT COR. MKD. 1/4 S. 6 T33S, R5W. COUNTY
SURVEYORS OFFICE 1958.
NEW BT. 14" R. FIR BEARS 5.80W 20.5'
SCRIBED 1/4 S. 6 C.S. BT.; 8" LAUREL BEARS
54.0'E 10.5' SCRIBED 1/4 S. 6 C.S. BT.

SET 1/16 S. 6 T33S, R5W. MKD.
SET BRASS CAP AT COR. MKD.
W 1/16 S. 6 T33S, R5W. COUNTY SURVEYORS
OFFICE 1958. BT. 16" R. FIR BEARS
5.34° E 18.7' SCRIBED W 1/16 S. 6 C.S. BT.
6" MAPLE BEARS 5.80W 20.5' SCRIBED
W 1/16 S. 6 C.S. BT.

FD 1/4" AXLE AT COR. E LARGE FIR
STUMP 5.37' W 45.5'
NEW BT. 8" R. FIR N3°30' W 15.4'
40" R. FIR N7° E 42.0'

NORTH 112' 88'
SOUTH 29'
FD 1/4" PIPE AT COR.
AND ALL B.T.S.

589° 02' 30" E

1329.88

COUNTY SURVEYOR'S OFFICE
DOUGLAS COUNTY OREGON

SURVEY TO ESTABLISH SECTION LINE
SECTION 6, T33S, R5W, W.M.

FRED M. DARBY COUNTY SURVEYOR
SURVEYED AUG. 19, 1958 BY
JAMES W. BYRON - DEPUTY SCALE 1" = 200'
SURVEYED FOR C. & D. LUMBER CO.

James W. Byron

COUNTY SURVEYORS OFFICE
DOUGLAS COUNTY OREGON

18-2114
211/68 5715 353

C.S. FILE 49/142
M.P. 51

CS FILE FOLDER

CONTAINS

MORE

INFORMATION