



RENEWED CORNERS & COR'S SET

Sec. Cor. 3-4-33-34, set from O.B.T. S. 80° E. 235 lks. which Eugene Ollivant testifies is Orig. B.T. This tree has deep cut on N.W. face and old axemarks in cut and is E 2647'. from N 1/4 Cor Sec 4 - Drove 2" sq. hd. bolt & remarked Orig B.T. scribed new trees: - 24" Ced. S 27 1/2° E. 44.5" S 3 T 29S, R7W 1581 BT" also 14" Forked W. Oak N. 34° E. 181.0" S 34 T 29S, R7W and a 7" W.O.S. 89° W. 61.0" S 4 T 29S, R7W 1581 BT" Corner is abt 300' W. of Cen. Olalla Crk. and on N side of dry Creek.

Set Apr. 18, 1957 Arthur Boyer H.L. Northcraft wit John Fletcher

1/4 Sec. Cor. bet. Secs. 3 & 4 - Set on line at mid pt bet. Cor's. 1/2 mi to E 2 W - Drove Cedar Post & buried rock 4x8x10 & scribed 48" Oak N 32° E. 254" 1/4 S 34 T 29S, R7W 1581 BT" also 48" Oak N 59° E. 259" 1/4 S 34 T 29S, R7W 1581 BT" A 15" Forked W. Oak S. 80° E. 294" 1/4 S 3 T 29S, R7W 1581 BT" & a 10" W. Oak on an E & W. Fence line N. 58° W. 386" 1/4 S 34 T 29S, R7W 1581 BT Set Apr 30, 1957 Arthur Boyer H.L. Northcraft Wit.

1/4 Sec Cor. bet. Secs. 3 & 4 Set by propnl. msmt. on line bet. NW 2 S.W. Cor. of Sec. 3. Drove 1 1/2" i. p. & scribed following trees 24" Fir, N 19° 21' E 410.4" 1/4 S 3 T 29S, R7W 1581 BT" 24" B. Oak, S 86° 40' W. 444" 1/4 S 4 T 29S, R7W " 30" Fir, N 0° 40' E. 329" 1/4 S 3 T 29S, R7W " " Set Apr. 21, 1957 Arthur Boyer H.L. Northcraft Wit.

Cen Sec. 3, set at intersec. N & S and E & W, mid sec. lines - Drove 3"x3" Fir Stake - Scribed 24" Fir Stump N 10° E 34' on slope, Cen S 3 T 29S, R7W 1581 BT and a 12" leaning Fir S 33° E 14.3" Cen S 3 1/4 S 3 T 29S, R7W BT. Apr 30, 1957 Arthur Boyer - H.L. Northcraft Wit.

NE Cor. NW 1/4 SW 1/4 Sec. 3 for this Cor. scribed a 12" Fir 1/4 S 3 T 29S, R7W 1581 from wh. a 12" Cedar brs. S 86° W 36.5" mka. 1/4 S 3 T 29S, R7W 1581 BT Apr. 30, 1957 Arthur Boyer H.L. Northcraft Wit.

SE Cor. SW 1/4 SW 1/4 Sec 3. Set at pt. midway bet. S.W. cor. & S 1/4 Cor Sec 3, on line bet. these two corners, the tot. dist bet. these corners being 1952' so this 1/4 cor. is set 976' from SW Cor Sec 3. The cor. has tagged a 12" Oak BT for this cor. which brs N 20° W 11' on S side skid road, 262' E of Creek. (scribed tree)

THIS COPY MADE FROM
A XEROX 2510
DATE 3-30-89

FILED
RECEIVED
Oct 16 1958
COUNTY SURVEYOR
DOUGLAS COUNTY, ORE.

ARTHUR GILBERT
SURVEY FOR EAST LINE OF
W 1/2 SW 1/4 SEC 3, T29S, R7W, W.M.
DOUGLAS COUNTY
APR - MAY, 1957 1" = 500'

Arthur Boyer