

RENEW SEC CORNER:- FOUND 2" PIPE  
AT CORNER & BOTH FIR BT'S. ALSO FIND  
30" B. OAK. N 18° E 122', RESCRIBE 30" B.  
OAK. N 18° E 16.7' SCRIBED S. 27 T30S, R.5W  
C.S. BT. 13" CEDAR 355° E 34.5' SCRIBED  
S34, T30S, R.5W. C.S. BT.

28 27  
33 34

NOTE: BEARINGS ARE TRUE, BASED  
ON A SOLAR OBSERVATION TAKEN  
JULY 23, 1959

A 12" CEDAR BEARS 554° W 15.3'  
SCRIBED C.S. BT.; 6" R. FIR, N 26° E  
5.0' SCRIBED C.S. BT.

SET 3/4" IRON

990.0'

S 88° 18' 10" W 5131.26'

SET BRASS CAP AT CORNER MKD.  
COUNTY SURVEYOR'S OFFICE, 1959  
1/4 33 34 T30S, R.5 W  
NEW BT'S, 16" CEDAR S 36° E 54.0'  
SCRIBED 1/4 S. 34 C.S. BT.  
18" LAUREL, NORTH 2.0' SCRIBED  
1/4 S. 33, C.S. BT.  
SET BY PROPORTIONATE MEASUREMENT

NOTE:  
INAPPROPRIATELY SET  
By Byron. Per F.I.  
Hn/71  
JK

FOUND 1" PIPE AT CORNER &  
REMAINS OF 4 BT'S.  
RENEW 1/4 CORNER; BLAZE &  
SCRIBE AN 8" OAK S 59° 30' E  
31.2', SCRIBED 1/4 S. 33, C.S. BT.

COUNTY SURVEYOR'S OFFICE  
DOUGLAS COUNTY, OREGON

SURVEY TO SET PROPERTY CORNERS,  
SECTION 33, T30S., R.5 W., W.M.

FRED M. DARBY COUNTY SURVEYOR  
SURVEYED JULY 23, 1959 BY  
JAMES W. BYRON - DEPUTY SCALE 1" = 200'  
SURVEYED FOR C. & D. LUMBER CO.

James W. Byron

COUNTY SURVEYORS FILE DATA  
TO THE PUBLIC

RENEW SEC. CORNER, FOUND ORIG. 20" NOW 36" FIR  
S 38° W 13.3'; FOUND ORIG 5" NOW 10" FIR SNAG N 83° W  
11.9', FOUND POINTED SANDSTONE AT CORNER 12" X  
12", 10" ABOVE GROUND, MARKED 6 NOTCHES ON  
SOUTH & 4 NOTCHES ON EAST; ALSO FIND 26"  
R. FIR, S 85° E 28.1' E R. FIR, S 55° W 38.1'  
NEW BT'S 15" E. FIR N 87° W 17.2' SCRIBED S 33 T30  
S, R.5 W. C.S. BT.; 36" R. FIR, S 38° W 14.5' SCRIBED  
S 4 C.S. (MARK SCRIBED).

80' WEST TO CREEK, & 33' NORTH TO CREEK.

33 34  
4 3

347 only  
Per F.I.  
Hn/71  
JK

CS FILE FOLDER

CONTAINS

MORE

INFORMATION