

92-61 W

COUNTY SURVEYORS FILE NO. **DO NOT REMOVE FROM OFFICE**

FILED *[Signature]*
RECEIVED

AUG 30 1960

COUNTY SURVEYOR
DOUGLAS COUNTY, ORE.

SURVEY OF SECTION 12 & 13, T. 25 S., R. 1 W., W.M.

SURVEYED FOR: U. S. PLYWOOD CORP.
SURVEYED BY: G. R. LECKLIDER - ENGINEER

AUGUST, 1960
SCALE: 1" = 500'

SEC. COR. SEC. 1, 2, 11, & 12
FD: Orig. Post - Badly Decayed
10" Yaw - N 04 1/2° E - 48.8'
12" Fir - S 12° E - 21.1'
SET: Steel Tube with Survey Cap
10" Fir - N 43° W - 36.5'
40" Fir - S 37° W - 40.3'

1/4 COR. SEC. 1 & 12
Orig. Cor. Not Fd.
SET: Steel Tube with Survey Cap
18" Fir - N 48° E - 5.0'
8" Fir - S 18° W - 23.1'

SEC. COR. SEC. 1 & 12
FD: G.L.O. Brass Cap
60" Fir - S 48° W - 19.1'
34" W. Fir - N 71° W - 27.1'

N 03° 57' W - 147.66'
C.C. SEC. 6 & 7, T. 25 S., R. 1 E.
FD: G.L.O. Brass Cap
22" Fir - N 61° E - 6.6'
24" W. Fir - S 17° E - 49.5'

NOTE: ALL BEARINGS BASED ON SOLAR OBSERVATION.

1/4 COR. SEC. 11 & 12
FD: "X" & "1/4" Mkd. on Vertical
Rock Face.
6" Cedar - S 89° W - 9.9' - Dead
SET: 14" Cedar - S 38° W - 9.0

1/4 COR. SEC. 12
FD: Cor. Stone
24" Fir - N 49° W - 35.0'
36" Fir - S 21° W - 39.6'
SET: Steel Tube with Survey Cap

N 00° 30' E - 194.35'
1/4 COR. SEC. 7, T. 25 S., R. 1 E.
FD: G.L.O. Brass Cap
28" Fir - N 49° E - 46.9'
56" Fir - S 51° E - 42.9'

12

W.C. SEC. 12 & 13
FD: Cor. Stone
16" Fir - N 10° W - 29.7' - Down
SET: Steel Tube with Survey Cap
Mkd. "S 12 B.O." on 20" X 20"
Rock Face - N 16° W - 17.7'

N 00° 58' W - 1.32'
C.C. SEC. 7 & 18, T. 25 S., R. 1 E.
FD: G.L.O. Brass Cap
32" Fir - N 24° E - 90.4'
20" Fir - S 37 1/2° E - 99.7'

SEC. COR. SEC. 11, 12, 13, & 14
FD: Cor. Stone
13" Fir - N 88° E - 20.5'
15" Fir - N 39° W - 17.8' - Dead
Stump Hole - S 53° E
SET: 32" Fir - S 60° W - 33.7'
30" Fir - N 10° E - 42.0'
14" Fir - S 36° E - 57.6'

W.C. SEC. 12 & 13
FD: Cor. Stone
30" Fir - S 24° W - 31.7'
40" Fir - N 89° W - 13.2'

13

1/4 COR. SEC. 13
FD: 48" Fir - S 27° W - 20.5'
12" Cedar - N 42° W - 56.2'
Rec. - 11.9'
SET: Steel Tube with Survey Cap

N 00° 45' W - 169.25'
1/4 COR. SEC. 18, T. 25 S., R. 1 E.
FD: G.L.O. Brass Cap
14" Cedar - N 48° E - 36.3'
11" Cedar - S 85° E - 25.7'

1/4 COR. SEC. 13 & 14
FD: Cor. Stone
14" Fir - S 62° W - 8.8'
Rec. - N 33° W - 18.5'
SET: 5/8" Steel Tube
32" Fir - N 45° E - 22.0'

SEC. COR. SEC. 13, 14, 23, & 24
FD: Cor. Stone
12" Madrone - S 05° W - 7.9'
26" Fir - N 77° E - 27.0'
36" Fir - N 18° W - 15.7'
26" Fir - S 66° E - 30.0'

SEC. COR. SEC. 13 & 24
FD: Cor. Stone
60" Fir - N 74° W - 29.0'
42" Fir - S 19° W - 7.9'
SET: Steel Tube with Survey Cap

1/4 COR. SEC. 13 & 24

N 88° 57' E - 2705.2'
Prior Survey - N 88° 40' E

N 89° 28' E - 2737.0'
Prior Survey - N 89° 11' E