



Fd. Brass Cap  
C.C. 531432  
T. 22S, R5W  
(Not on line)

Fd 2 Stumps that fit  
for bearing and dist.  
of orig. B.Ts.  
20" fir 6x19 scribed  
to S. B.T. S. 86° W. 13.25 ft

set 1" x 1" x 36"  
T. iron  
scribed:  
8" fir S. 01° E. 26.2  
6" fir S. 06° W. 27.5

set 1" x 1" x 36"  
T. iron, 48.32  
(Not on line)  
Standard 1/4 S. 5  
Fd. orig. 10" fir S 28° W 204-115  
Now 36"  
set 1" x 1" x 36" T. iron  
scribed  
16" fir S 32° W 34.9 ft.

DO NOT REMOVE SURVEY MARKS

SECTS. 5+6, T 23 S., R 5 W. W.M.  
Yoncalla Lumber Co. Yoncalla, Oregon,  
Scale 1" = 400'  
June 1960

1/4 S 5/6 - set 1" x 1" x 36"  
T. iron  
scribed  
16" fir S. 50° W. 9.8 ft.  
Fd. 16" fir S 85° E 10.0 ft.  
scribed to S. B.T. when about  
10"

REGISTERED  
OREGON  
LAND SURVEYOR  
Wilford N. Haines  
MAY 7, 1948  
WILFORD N. HAINES  
239

FILED  
RECEIVED

JUN 21 1960  
COUNTY SURVEYOR  
DOUGLAS COUNTY, ORE.

S. 7/8 S 5/6 set 1" x 1" x 36"  
T. iron  
scribed  
30" fir N 06° E 31.0 ft.  
22" fir N 55° W 26.1 ft.

Fd. Brass Cap  
6 5  
7 8