

COUNTY SURVEYORS FILE DATA
DO NOT REMOVE FROM OFFICE

CORNERS FOUND OR SET

- ① CTR. 1/4 S 15, FOUND SQUARED BURNT PITCH KNOT & ROTTED SNAG 8.T. W/DIM FACE VISIBLE, S 28° E 44.8'. A 54" BURNT STUB W/DIM FACES BRG. N 38° W 36.8', AS ESTAB. BY G.G. STEWART, DEP. COUNTY SURVEYOR, 1922, C.S. FILE # 7/31. I. SET 1" I. PIPE BESIDE PITCH KNOT, RESCRIBE 54" BURNT O.B.T. STUB, & BARK SCRIBE 28" D. FIR, N 42° E 119.7' (BOTH "C 1/4 S 36 83 BT").
- ② C.W. 1/4 S 15, FOUND O.B.T. ESTAB. BY STEWART, 1922 (C.S. FILE # 7/31), FACE BURNT, NOW 40" D. FIR, N 12° 10' E 107.4', SCRIBE VISIBLE. I. SET 1" I. PIPE, SCRIBED 12" Y. PINE, N 37° 50' E, 50.22' (1/4 B.T.).
- ③ 1/4 COR. 1615 IN RIVER, POSITION PER 1959 COUNTY SURVEY, FILE # A9/134.
- ④ FOUND 40" Y. PINE 8.T. 6' WEST OF STONE FOR WITNESS COR., " " "
- ⑤ FOUND UNRECORDED IRON BAR UNDER STONE, 0.8' N 2° 05' E & 5.95' WEST OF TRUE POINT FOR 1/6 COR.
- ⑥ FOUND 1/2" I. PIPE 1.6' SOUTH & 4.13' EAST OF TRUE POINT FOR SW 1/4 COR. (PIPE UNRECORDED).
- ⑦ PROPERTY COR., SET 1/2" I. ROD, SCRIBED 16" W. OAK N 64° 45' E 74.2' & 20" B. OAK N 14° 30' W (BOTH "36 83 BT").
- ⑧ SET 1/2" I. ROD AT INTERSECTION OF PROPERTY LINE WITH SEC. LINE BET. 1615.
- ⑨ SET 1/2" I. ROD FOR PROPERTY CORNER, SCRIBED 4" W. OAK N 69° E 22.12' "36 83 BT", & 10" MADRONE S 0° 20' W 27.1' ("36 83 BT").
- ⑩ FOUND E 1/4 S 15 AS RENEWED BY 1959 COUNTY SURVEY, FILE # A9/134.
- ⑪ SECTION CORNER, FOUND I. PIPE W/BASS CAP & B.T.'S AS RENEWED BY 1959 COUNTY SURVEY, FILE # A9/134.
- ⑫ SET 1" I. PIPE ON SEC. LINE 15/22, SCRIBED 14" W. OAK, S 87° 19' 15" E 2561.72' & 8" W. OAK N 39° 5' W 18.11'.
- ⑬ W 1/4 S 15, FOUND 1/2" I. PIPE & B.T.'S MARKED BY G. WENDEROTH, C.S. FILE # M14/53, & UNRECORDED 1/2" I. ROD IN ROCK MOUND N 39° 13' W 254.04'; ALSO FD. O.B.T.'S ESTAB. BY C.E. ROBERTS, C.S., 1912, (FIELD BK. #12), DOWN & DEAD 36" OAK, S 17° 45' E 259.3', FACE DESTROYED, & ROTTED 28" W. OAK S 13° 45' W 210.22' & ROTTED 36" D. FIR SNAG N 38° 15' W 394.74'.
- ⑭ 1/4 COR. 15, FOUND 1/2" I. PIPE IN ROCK MOUND, BOULDER OUTCROP (3'x4'x8') S 13° W 70.6' PER G.G. STEWART, 1922, C.S. FILE # 7/31. TO RENEW I SCRIBE 28" MAPLE N 20° 49' E 51.17' (1/4 S 15 "36 83 BT").
- ⑮ CN 1/4 S 22, FOUND ORIG. B.T. AS MKD BY ROBERTS COUNTY SURVEYOR, 1912 (1/4 " & BT" BARK SCRIBE VISIBLE, NOW 70" D. FIR N 17° 40' W 45.8'. DIM STUMP HOLE OF 13" CEDAR B.T. BRG. N 40° E 55.5', BURNT STEM ON GROUND. TO RENEW I SET 1" I. PIPE, SCRIBED 10" W. OAK N 24° 33' W 25.09' & 28" I. CEDAR S 72° 13' E 43.45' (1/4 S 22 "36 83 BT").
- ⑯ NW 1/4 S 22, I FIND 3 ORIG. B.T.'S AS MARKED BY C.E. ROBERTS, C.S., 1912, IN GOOD CONDITION WITH FACES INTACT, NOW: 26" W. OAK N 79° E 64.7', 22" W. OAK N 68° 00' W (REC. N 69° 50' W) 190.0', 24" W. OAK S 78° 00' E (REC. S 78° 00' E) 179.0'. ALSO FIND 1/2" DRILL STEEL NOT IN AGREEMENT WITH B.T.'S. TO RENEW I SET 1" I. PIPE FROM O.B.T.'S. COR OF FENCES BRG. S 29° 15' W 10.3'; DRILL STEEL BRG. S 9° 49' W 8.35'.
- ⑰ SET 1" I. PIPE ON HWY R/W LINE, SCRIBE 36" MAPLE N 59° 30' E 19.66' "36 83 BT".

NOTE: THIS SURVEY BASED ON PREVIOUS SURVEYS AND CORNERS ESTABLISHED:

- C. E. ROBERTS, COUNTY SURVEYOR, MARCH, 1912, FIELD BOOK NO. 12
- G. G. STEWART, DEP. CO. SURVEYOR, DEC. 29, 1922, C.S. FILE # 7/31
- G. WENDEROTH, MARCH 1947, C.S. FILE # M14-53
- FRED M. DARBY, COUNTY SURVEYOR, JAN.-FEB., 1959, FILE # A9/134

BEARINGS BY SOLAR OBSERVATIONS TAKEN DURING THE COURSE OF THIS SURVEY.
CENTER LINE & R/W OF STATE HWY. NO. 227 PLOTTED FROM PEEDS TO STATE, & STATE HWY. DEPT. MAP.

SURVEY AND RETRACEMENT TO LOCATE CERTAIN PROPERTY LINES
IN SECTIONS 15, 16, 21, & 22, TWP. 30S, RGE. 4W, W. M., OREGON

SCALE: 1 INCH = 200 FEET

OCTOBER, 1962

ROBERT M. THOMPSON



FILED & RECEIVED
JUL 18 1963
COUNTY SURVEYOR
DOUGLAS COUNTY, ORE.

COUNTY SURVEYORS FILE DATA
DO NOT REMOVE FROM OFFICE

