



Fd. T. iron  
 Orig. 10" Fir (Now 20") S. 91° W. 40-16s  
 Scribed B.T. in wood below old  
 Bark Scribe  
 Scribed 2 New B.Ts.  
 20" Fir S. 24° E. 49.4 ft  
 14" Hemlock N. 75° W. 34.0 ft.

C. of sect. 10  
 Fd. T. iron  
 30" D. Fir  
 S. 05° W. 2.5'

4/3 19/11  
 Fd. T. iron  
 8" Fir N. 62° W. 5.9'  
 8" Fir N. 73° E. 10.0'

E. of S. 10  
 Set 1" x 1" x 36"  
 T. iron  
 Scribed  
 10" Fir S. 74° E. 13.3'  
 8" Fir N. 10° E. 14.1'

SE C. of S. 10  
 Set 1" x 1" x 36"  
 T. iron  
 Scribed  
 20" Fir S. 60° E. 13.0'  
 30" Fir N. 28° W. 10.5'

St. 5 10/11  
 Set 1" x 1" x 36"  
 T. iron  
 Scribed  
 18" Fir S. 60° E. 23.0'  
 8" Fir N. 94° W. 11.6'

4/5 19/11  
 Fd. old blaze out no  
 original orig. & Cor.  
 Set 1" x 1" x 36"  
 T. iron  
 Scribed  
 8" Hemlock N. 78° E. 4.3'  
 11" Hemlock S. 72° W. 11.2'

Fd. T. iron  
 4 orig. B.Ts.

Fd. T. iron  
 and B.Ts. as  
 shown on 1907  
 survey

REGISTERED  
 OREGON  
 LAND SURVEYOR  
 Wilford N. Haines  
 MAY 7, 1948  
 WILFORD N. HAINES  
 239



SECT. 10, T. 21 S., R. 7 W. W.M.  
 Survey to determine lines & corners in S.E. 4

For  
 Woolley Logging Co. Drain, Oregon.  
 scale: 1" = 400' April 7, 1965

FILED  
 RECEIVED  
 MAY 2 1965  
 COUNTY SURVEYOR  
 DOUGLAS COUNTY, ORE.

F.B. # - M, H-58, H-59  
 H-66  
 M 29 - 67

H-14, H-59  
 F.B. # - 26, H-58  
 M 29 - 67