



N.W. corner
 D.L.C. # 38 T.22S., R.5W. W.M.
 Fd. T. iron 2 B.Ts.

Calculated position for
 N.E. corner calls in air count
 N.S. 00 N 31° 20' E
 and I don't think it ever did.
 No corner set

South-S.W. Cor. Claim #43
 Fd.
 Stone post UNRECORDED
 a plow share
 in a buried mound of stones
 drove a steel fence post
 by stone post.
 fence is about 3ft west

SE. Cor. D.L.C. # 43
 Fd 24" fir 568°W. 32-112
 Now 48" ± stump
 Set 5/8" steel Rod
 Scribed
 9" fir 562°W 84'
 12" fir N31°W 88'

Not To Scale ↑

• SET 5/8" X 36" steel Rods

CORNER D.L.C. # 38
 Fd. 30" OAK S. 89° E. 583' Lks.
 down
 Set 5/8" X 36" steel Rod
 scribed
 8" OAK N. 39° E 120.7ft
 one of clump of trees
 18" MAPLE N. 79° E 91.0ft

SECTS. 21-22-27-28, T.22S., R.5W. WM

SOUTH LINE DLC # 43
 NORTH LINE DLC # 38

Scale: 1" = 500'

August 1967

FOR JAMES LHAMAN

REGISTERED
 OREGON
 LAND SURVEYOR
 Wilford N. Haines
 MAY 7, 1948
 WILFORD N. HAINES
 239

FILED
 RECEIVED

AUG 25 1967

COUNTY SURVEYOR
 DOUGLAS COUNTY, ORE.

F.B. H-98
 FILE M34-T-44

F.B. H-98
 FILE M34-T-44