COUNTY SURVEYORS FILE DATA
DO NOT REMOVE FROM OFFICE

MAP FILE M 49 - 33

Fd. brass cap mkd.
County Surveyor's Office
1/4 S27, S26 1961
From which a:

60" original Douglas fir BT
Rotting snag, "1/4 S" vis.
Bears N2 1/2°E, 144.5 ft.

15" Douglas fir BT
Face vis.
Bears S71°E, 6.8 ft.

12" Douglas fir BT
Face vis.
Bears N44 1/2°W, 14.0 ft.

27 ◉ 26

S0°36'E, 1413.10
(Record N0°02'W, 1320.00)

Set brass cap mkd.
T26S, R8W, WM
S1/16 S27, S26 1973
From which a:

30" Douglas fir, 1 scribed
"S 1/16 S26 BT"
Bears N74°E, 37.8 ft.

21" Douglas fir, 1 scribed
"S1/16 S27 BT"
Bears S33°W, 40.5 ft.

S0°36'E, 1413.10
(Record N0°02'W, 1320.00)

Fd. brass cap mkd.
County Surveyor's Office
T26S, R8W
S27, S34 1970
From which a:

74" original Douglas fir BT
Snag, scribing vis.
Bears S24°W, 30.4 ft.

15" Douglas fir BT
Scribing vis.
Bears S7°E, 20.3 ft.
(Record 7.3 ft.)

15" Douglas fir BT
Scribing vis.
Bears N67°E, 21.4 ft.

27 — S89°15'E, 1332.18 — 34
(Record N89°52'E, 1321.98)

S89°15'E, 1332.17
(Record N89°52'E, 1321.98)

27 — 34

Set brass cap mkd.
T26S, R8W, WM
E1/16 S27, S34 1973
From which a:

14" Douglas fir, 1 scribed
"E1/16 S27 BT"
Bears North, 22.4 ft.

12" Douglas fir, 1 scribed
"E1/16 S34 BT"
Bears S32°E, 117.4 ft.

26 — 35

S89°15'E, 2643.16
(Record N89°51'E, 2640.00)

Set brass cap mkd.
T26S, R8W, WM
S27, S26, S34, S35 1973
From which a:

12" Douglas fir, 1 scribed
"T26S, R8W S27 BT"
Bears N84°W, 27.4 ft.

10" Douglas fir, 1 scribed
"T26S, R8W, S26 BT"
Bears N43°E, 32.1 ft.

10" Douglas fir, 1 scribed
"T26S, R8W, S34 BT"
Bears S61°W, 40.9 ft.

10" Douglas fir, 1 scribed
"T26S, R8W, S35 BT"
Bears S67 1/2°E, 10.3 ft.

Callahan Road

Fd. 1 1/2" iron pipe
Set in mound of stone
Brass washer mkd.
"RS 404" nailed in top
From which a:

20" Douglas fir BT
Face vis.
Bears S58°W, 8.6 ft.

24" Douglas fir BT
Face vis.
Bears N1°W, 42.2 ft.

S0°36'E, 2628.81
(Record N0°02'W, 2640.00)

34 ◉ 35

Set brass cap mkd.
T26S, R8W
1/4S S34, S35 1973
From which a:

52" original Douglas fir BT
I opened face and found scribe "I"
Face burned and axe marks vis.
I rescribed "1/4 S34 BT"
Bears N55°W, 158.4 ft.
(Record 36")

12" Douglas fir, 1 scribed
"1/4 S35 BT"
Bears N44°E, 15.0 ft.

10" Douglas fir, 1 scribed
"1/4 S34 BT"
Bears S53°W, 5.9 ft.

PROPERTY LINE SURVEY BETWEEN SECS. 26, 27, 34 & 35, T. 26 S., R. 8 W., W. M.

For: Hub Lumber Co.
Roseburg, Oregon

By: Shaner Engineering, Roseburg, Oregon

August 16, 1973

300 0 300 600
Scale: 1" = 300'

REGISTERED PROFESSIONAL ENGINEER
4906
B A Shaner
OREGON
JULY 9, 1962
BRUCE A. SHANER

Bearings based on
Solar observation.

LEGEND

- Corner found ◉
- Corner set ◎
- True line marked with blazes and red paint ——
- Random line only, no true line marked ——
- Rocked road ═══
- Dirt road ========
- Stream ~···→

MAP FILE M 49 - 33

COUNTY SURVEYORS FILE DATA
DO NOT REMOVE FROM OFFICE