

NOV 14 1980

COUNTY SURVEYOR
DOUGLAS COUNTY, OREGON

1. $\frac{22}{27} | \frac{23}{26}$ Found 1 1/4" IP with stamped brass pipe cap from which an 18" Spruce (rotten stump) brs. S 32° W, 37.6 ft.; Renewal #1

New bearing trees:

52" Spruce brs. N 50° 30' E, 72.7 ft., scribed
42" Spruce brs. S 57° 15' E, 33.8 ft., scribed
16" Alder brs. S 40° 00' W, 59.8 ft., scribed
10" Hemlock brs. N 10° 00' W, 12.3 ft., scribed

2. 1/4 Corner $\frac{23}{26}$ Set 1 1/4" IP with stamped brass cap from which:
12" Alder brs. N 7° 00' W, 7.9 ft., scribed
12" Fir brs. S 34° 00' W, 5.9 ft., scribed

Note: I made a thorough search for the iron pipe and brass cap as shown being found in CS 51/333 and CS 54/30, but its position was in the head of a draw which has now slid away to bed rock.

3. Witness Cor. to M.C. $\frac{24}{25}$ Set 2" aluminum pipe with stamped aluminum cap on top of dike, left bank of Smith River from which:
60" Spruce brs. N 78° 30' E, 284.4 ft. to 50d nail in the face, scribed
48" double Spruce brs. S 36° 00' E, 197.9 ft. to 50d nail in the face, scribed. BT is on top of river dike.

4. 1/4 Corner $\frac{24}{25}$ Set 2" aluminum pipe with stamped aluminum cap from which:
18" Spruce brs. N 46° 00' W, 4.4 ft., scribed
28" Maple brs. S 39° 15' E, 15.5 ft., scribed

5. E 1/16 $\frac{24}{25}$ Set 2" aluminum pipe with stamped aluminum cap from which:
80" Spruce brs. N 15° 00' E, 56.7 ft. to a 50d nail in the face, scribed
20" Spruce brs. S 64° 00' W, 130.0 ft. to a 50d nail in the root collar, scribed
Corner falls on the East side of a creek bottom.

6. $\frac{24}{25} | \frac{19}{30}$ Found 5/8" I.R.
Renewal #56, M62-1

7. 1/4 Corner $\frac{25}{30}$ Found 5/8" I.R.
Renewal #57, M62-1

8. CE 1/16 Sec. 25 Set 2" aluminum pipe with stamped aluminum cap from which:
62" Fir brs. S 49° 00' E, 22.4 ft., scribed
24" Fir brs. N 12° 00' W, 18.4 ft., scribed

9. Witness Pt. C—C Sec. 25 Set 2" aluminum pipe with stamped aluminum cap from which:
16" Maple brs. N 16° 00' E, 31.2 ft., scribed
42" Spruce brs. S 36° 30' W, 6.1 ft., scribed

10. 1/4 Corner $\frac{26}{25}$ Corner falls on West shoulder of Smith River County Road #48 (not Set)
2" aluminum pipe with stamped aluminum cap brs. N 0° 13' 10" E, 30.00 ft. (reference monument)
2" aluminum pipe with stamped aluminum cap brs. N 89° 46' 50" W, 30.00 ft. (reference monument)

11. Witness Pt. S—S Sec. 25 Set 1 1/4" IP with stamped brass cap from which:
12" Fir brs. N 70° 00' E, 14.3 ft., scribed
16" Fir brs. S 16° 00' E, 4.3 ft., scribed

12. SE 1/16 Sec. 25 Set 1 1/4" IP with stamped brass cap from which:
24" Fir brs. S 55° 00' E, 11.2 ft., scribed
50" Fir brs. S 19° 00' W, 13.0 ft., scribed

13. $\frac{25}{36} | \frac{30}{31}$ Found IP with brass cap, Douglas County Surveyor, 1971, Renewal #26, M42-27

14. 1/4 Corner $\frac{25}{36}$ Set 2" aluminum pipe with stamped aluminum cap from which:
10" Fir brs. N 10° 30' E, 5.8 ft., scribed
6" Fir brs. S 43° 45' E, 5.7 ft., scribed

15. Witness Cor. to M.C. $\frac{25}{36}$ Set 2" aluminum pipe with stamped aluminum cap from which:
16" Fir brs. N 87° 30' E, 31.3 ft., scribed
16" White Fir brs. N 14° 00' W, 18.2 ft., scribed

16. $\frac{28}{33} | \frac{27}{34}$ Found 1" I.R. 3" below ground, Renewal #35, from which:
SE corner of brick chimney brs. N 40° 45' W, 178.7 ft. Formerly given as N 41° W, 162.3 ft.
50d nail on West side of pole $\frac{AE}{1} \frac{34}{D}$ brs. S 36° 15' W, 75.9 ft., formerly given as S 36° 30' W, 76.6 ft.
Set steel fence post 1 ft. North of corner.

17. $\frac{35}{21} | \frac{36}{11}$ Found IP with brass cap, Douglas County Surveyor, Renewal #29, M42-27

18. $\frac{14}{23} | \frac{13}{24}$ Renewal #77, M79-30, Found 2" IP with brass cap

NOTE: All distances are taken to a 50d nail driven in the side of each BT at its approximate center, unless noted. An International Paper Company or Forest Service aluminum bearing tree sign is attached to each BT with a 6" band painted around the tree above the BT sign, and the blazes are also painted. A guard post or posts was set 3 to 5 feet away from the monuments on each line between national forest and private ownership with attached appropriate signs.

Richard J. Hintz, PLS #497
November 3, 1980



CORNER ACCESSORIES
FOR
COOPERATIVE SURVEY
SECTION 25, T21S, R12W
DOUGLAS COUNTY, OREGON
COUNTY SURVEYORS FILE DATA
DO NOT REMOVE FROM OFFICE