

FILED  
RECEIVED

JUN 19 1981

COUNTY SURVEYOR  
DOUGLAS COUNTY, ORE



"A" N.W. CORNER SECTION 30

FD. 1957 G.L.O. BRASS CAP  
21" MAPLE, N 28 1/2° E, 19.1' (OPENED FACE), 1891 B.T.  
16" MAPLE, N 82° E, 37.2' (SCAR VIS.), 1957 B.T.  
17" MAPLE, S 20° E, 5.4' (SCAR VIS.), 1957 B.T.

"B" EAST 1/4 CORNER SECTION 25

FD. 1957 G.L.O. BRASS CAP  
20" MAPLE, S 56° W, 27.1' (SCAR VIS.), 1957 B.T.  
22" MAPLE, N 73 1/2° W, 18.3' (SCAR VIS.), 1957 B.T.

"C" NORTH 1/16 CORNER SECTION 30

SET 1 1/2" x 36" IRON PIPE & BRASS CAP  
26" FIR, S 11° E, 35.4' (SCRIBED)  
28" FIR, N 49° E, 26.0' (SCRIBED)

"D" WEST 1/4 CORNER SECTION 30

FD. 1957 G.L.O. BRASS CAP  
44" FIR STUMP, S 20 1/4° W, 43.0' (SCAR VIS.), 1891 B.T.  
15" MAPLE, N 48 3/4° E, 24.2' (SCRIBE VIS.), 1957 B.T.  
22" HEMLOCK SNAG, S 11 3/4° E, 11.7' (SCRIBE VIS.), 1957 B.T.

"E" CLOSING CORNER SECTIONS 25 & 36

FD. 1957 G.L.O. BRASS CAP  
50" FIR, N 74° W, 18.6' (SCAR VIS.), 1899 B.T.

"F" SOUTH 1/16 CORNER SECTION 30

FD. 1957 G.L.O. BRASS CAP  
7" DOWNED FIR, N 51° E, 16.4' (SCRIBE VIS.), 1957 B.T.  
13" FIR, S 7 1/2° E, 16.4' (SCAR VIS.), 1957 B.T.  
SET 35" FIR, S 72° E, 41.5' (SCRIBED)

"G" NORTH 1/16 CORNER SECTION 36

FD. 1957 G.L.O. BRASS CAP  
15" HEMLOCK, S 80 3/4° W, 23.9' (SCAR VIS.), 1957 B.T.  
24" FIR, N 64 3/4° W, 33.5' (SCAR VIS.), 1957 B.T.

"H" S.W. CORNER SECTION 30

FD. 1957 G.L.O. BRASS CAP  
15" DOWNED FIR, N 66° E, 17.7' (SCAR VIS.), 1891 B.T.  
24" FIR, S 38° E, 16.1' (SCAR VIS.), 1891 B.T.  
18" FIR STUB, N 4 1/2° E, 30.7' (SCRIBE VIS.) 1957 B.T.

"I" EAST 1/4 CORNER SECTION 36

FD. 1957 G.L.O. BRASS CAP  
26" FIR, N 22° W, 9.1' (SCAR VIS.), 1957 B.T.

LOCATION OF 1/2" IRON RODS

1/16 COR.	Distance	Direction
S 1/16 COR.		
W 30-1	200'	NORTH
W 30-2	321'	NORTH
W 30-3	631'	NORTH
W 30-5	990'	NORTH
W 30-6	1145'	NORTH
CLOS. COR.	1177'	NORTH
W 1/4 COR.	1330'	NORTH
W 30-7	184'	NORTH
W 30-8	377'	NORTH
W 30-10	673'	NORTH
W 30-11	870'	NORTH
W 30-12	1015'	NORTH
W 30-14	1172'	NORTH
N 1/16 COR.	1357'	NORTH
W 30-16	1398'	NORTH
W 30-18	1564'	NORTH
W 30-19	1869'	NORTH
W 30-21	2038'	NORTH
W 30-22	2268'	NORTH
E 1/4 COR.	2523'	NORTH
N.W. COR.	2714'	NORTH

NARRATIVE

I, LESLIE ROBERTS, REGISTERED PROFESSIONAL LAND SURVEYOR DO CERTIFY THAT I HAVE CORRECTLY SURVEYED THE WEST LINE OF SECTION 30 IN ACCORDANCE TO THE MANUAL OF INSTRUCTIONS FOR THE SURVEY OF THE PUBLIC LANDS OF THE UNITED STATES. THE NORTH 1/16 CORNER ON THE WEST LINE OF SECTION 30 WAS SET MID-WAY BETWEEN THE N.W. CORNER AND THE WEST 1/4 CORNER OF SAID SECTION 30. LINE FOR SAID NORTH 1/16 CORNER WAS DETERMINED BY THE EAST 1/4 CORNER OF SECTION 25 AND BY THE WEST 1/4 CORNER OF SECTION 30. A CLOSED MEANDER TRANSIT AND E.D.M. TRAVERSE WAS RUN ALONG THE WEST LINE OF SECTION 30. OFFSETS WERE COMPUTED FROM THIS MEANDER TRAVERSE TO THE TRUE PROPERTY LINE.

LEGEND

- CORNERS FOUND AND USED FOR CONTROL
- CORNERS SET
- LINE MARKED WITH RED PAINTED BLAZES, 1/2" x 60" IRON RODS AND RED RIBBON
- ( ) DATA OF RECORD
- BASIS OF BEARING, N 1/2 OF WEST LINE OF SECTION 30 FROM 1957 B.L.M. SURVEY
- DISTANCE TO BEARING TREES ARE CENTER MEASURE
- ALL BEARING TREES ARE SCRIBED
- SCALE 1" = 300'

SURVEY OF THE WEST LINE  
SECTION 30, T 19 S, R 8 W, W.M.  
DOUGLAS COUNTY, OREGON  
FOR  
INTERNATIONAL PAPER COMPANY  
BY  
ROBERTS SURVEYING INC.  
29 WEST 29TH STREET  
EUGENE, OREGON 97405

JUNE 5, 1981

COUNTY SURVEYORS FILE DATA  
DO NOT REMOVE FROM OFFICE

Les Roberts

N 1° 41' 26" W, 190.80'  
(N 0° 24' W, 2.89 CHS., 1957)

