

FILED BS
RECEIVED JH
APR 13 1984

COUNTY SURVEYOR
DOUGLAS COUNTY, ORE.

BS

Correction Survey of the East line of Section 36 in T. 19 S., R. 10 W. W. M.

The purpose of this survey is to correct my previous survey map dated June 3, 1978, Douglas County Survey Reference No. M 71-62. I have eliminated the angle point at the Closing Corner for Townships 19 and 20, Range 9 W. W. M. where they intersect the East line of Sec. 36. I have established an angle point at the 1/4 Corner point to more closely follow the 1920 Retracement Survey by Fred Mensch. I calculated the location of the corrected 1/4 Corner point from my 1978 survey. From my 1978 1/4 Corner point I measure North 43° 24' East 8.06 feet to the corrected 1/4 Corner point and set a 5/8" by 40" iron rod to monument the correct East 1/4 Corner for Section 36.

My 1978 monument marking the 1920 location of the Closing Corner for Townships 19 and 20 remains unchanged.

Scale of map: 1" to 400 ft.

March 30, 1984.

Monuments found in 1978 shown: ⊙
Monuments set in this survey: ○
Basis of bearings shown: My 1978 survey, NE and SE Corners of Sec. 36. Bearing: S. 0° 12' 38" E. 4841.87 ft. Mensch in 1920: S. 0° 12' 54" W. 4891.85 ft. Angle Mensch to Hales Rt. 0° 25' 32"
Client: No client. Fee: No fee. This job was done for my conscience.
April 9, 1984

FORREST J. HALES 1490 N. IVY COQUILLE, OR. 97423

REGISTERED
OREGON
LAND SURVEYOR

OCTOBER 21, 1888
FORREST J. HALES
453

Sec. 25
Fd. Brass Cap and pipe post
40" D. Fir Bys. N. 3 1/2° W. 4.0 ft.
38" Hem. Bys. S 83°
W. 46.9 ft. Note: CORNER
INFORMATION FROM 1978
Sec. 36



2503.28 ft.
S. 0° 29' 40" E.

Mensch 1920 - N. 0° 04' W. 38.32 Ch.
Hales 1978 - N. 0° 22' W. 2509.10 ft.
Straight line partitionment Sec. Cor. to C.C.

Set 5/8" x 40" Iron Rod
From which a 40" Red Cedar
stump bears S. 9° 55' W.
93.8 ft. to face.
Cedar stump bears S. 28° Red
66.9 ft. to face. A 28" Red
Fd. Bys. marked F. J. H. 453
1978 Mon. was removed in logging.

Mensch 1920 - S. 0° 31' W. 27.93 Ch.
Hales 1978 - N. 0° 22' W. 1828.78 ft.
1/4 Cor. to C. C.

Fd. 5/8" Iron Rod
48" D. Fir Bys. N. 32 1/2° E. 49.0 ft. marks plain.
44" D. Fir Bys. S. 53 1/2° E. 18.2 ft. marks plain.
NOTE: CORNER INFORMATION FROM 1978.
Sec. 31, T. 19 S., R. 9 W. W. M.

Sec. 36, T.
19 S., R. 10
W. W. M.

N. 1° 08' 00" E.
504.15 ft.

Sec. 6, T. 20 S., R. 9 W. W. M.
Mensch 1920 - S. 0° 31' W. 7.87 Ch.
Hales 1978 - S. 1° 08' W. 504.15 ft.
1920 C. C. to Sec. Cor.

Fd. 3" pipe post with Brass Cap T. 19 S.,
R. 10 W. S. 36" 18" Alder Bys. S. 45° W. 14. ft.
24" Chinquapin Bys. N. 52° W. 15. ft.

Sec. 1
T. 20 S., R. 10 W.

NOTE: CORNER INFORMATION FROM 1978.