

SURVEYED BY:

REGISTERED  
PROFESSIONAL  
LAND SURVEYOR  
*Lloyd D. Smith*  
OREGON  
JULY 22, 1977  
LLOYD D. SMITH  
1101

FILED  
MAR 2 1990  
COUNTY SURVEYOR  
DOUGLAS COUNTY, OREG.

LLOYD D. SMITH  
300 5TH ST., BAY PARK  
COOS BAY, OREGON

SURVEY NARRATIVE TO COMPLY WITH PARAGRAPH 209.250 OREGON REVISED STATUTES

LEGEND

- OSBF P/C = OREGON STATE BOARD OF FORESTRY 1 1/2" X 36" GALVANIZED IRON PIPE WITH 3" BRONZE CAP
- OSDF P/C = OREGON STATE DEPARTMENT OF FORESTRY 1 1/2" X 36" ALUMINUM PIPE WITH 3 3/4" ALUMINUM CAP WITH MAGNETIC INSERT
- USC P/C = UNITED STATES CADASTRAL 2 1/2" IRON PIPE WITH 3" BRASS CAP
- ⊙ = MONUMENT SET
- ⊙ = MONUMENT FOUND
- WPCP = WHITE PAINTED CEDAR POST
- YMLP = YELLOW METAL LOCATION POSTER
- BTT = BEARING TREE TAG
- BT = BEARING TREE
- IG = IN GROUND
- IR = IRON ROD
- X = CARSONITE BOUNDARY MARKER AND STATION
- CBM = ORANGE CARSONITE BOUNDARY MARKER, CBM 250R
- ESTABLISHED = NEW CORNER SET
- #1 ( ) = RECORD BEARING AND DISTANCE IN CHAINS (WILLIAM H. BYARS, 1881 CONTRACT NO. 420)
- #2 ( ) = RECORD BEARING AND DISTANCE IN CHAINS (UNITED STATES CADASTRAL, 1976, SURVEY GROUP NO. 910)
- #3 ( ) = RECORD BEARINGS AND DISTANCE (HOWARD W. JOHNSTONE, 1989)

BASIS OF BEARING

BASED ON 1976 CADASTRAL RESURVEY OF EAST HALF OF LINE BETWEEN SECTIONS 17 & 20

PURPOSE

TO SEPARATE STATE FOREST LANDS AND PRIVATE LANDS LOCATED IN SECTION 20, TOWNSHIP 32 SOUTH, RANGE 6 WEST, WILLAMETTE MERIDIAN

PROCEDURE

A RANDOM TRAVERSE WAS USED TO CONNECT THE CONTROLLING CORNERS GOVERNING THE SUBDIVISION OF SECTION 20, TOWNSHIP 32 SOUTH, RANGE 6 WEST, WILLAMETTE MERIDIAN. THIS SECTION WAS SUBDIVIDED USING THE PROCEDURES AS OUTLINED IN THE "MANUAL OF INSTRUCTIONS FOR THE SURVEY OF THE PUBLIC LANDS OF THE U. S." ALL ROADS ARE AT APPROXIMATE LOCATIONS UNLESS OTHERWISE INDICATED. NEW CORNERS AND ACCESSORIES MARKED ACCORDING TO THE "MANUAL OF INSTRUCTIONS FOR THE SURVEY OF THE PUBLIC LANDS OF THE U. S." BEARINGS TO ACCESSORIES FOR ESTABLISHED CORNERS WERE TAKEN WITH A STAFF COMPASS SET AT 20° 30' EAST MAGNETIC DECLINATION. DISTANCE MEASURED TO ALUMINUM NAIL IN BT FACE. FOR DETAILED REPORT ON FOUND CORNERS SEE COUNTY RECORDS.

SURVEY FOR :  
STATE OF OREGON - DEPARTMENT OF FORESTRY  
SECTION 20, T. 32S., R. 6W., W. M.

DOUGLAS COUNTY, OREGON  
THEODOLITE AND EDM SURVEY BY : LLOYD D. SMITH  
DRAWN BY : TIM VAN VLEET  
FEBRUARY 6, 1990  
SCALE 1" = 300'

