

COUNTY SURVEYORS FILE DATA  
DO NOT REMOVE FROM OFFICE

FILED  
APR 8 1987  
COUNTY SURVEYOR  
DOUGLAS COUNTY, OREGON  
21-04-02 TL 200

NW COR. SEC. 2, T21S, R4W, W.M.  
Fd. DOUGLAS CO. BRASS CAP (1969)  
FROM WHICH:  
A FIR 16" BRS. N71°W 11.4 FT. W/HEALED BLAZE  
A FIR 9" BRS. N33°E 9.8 FT. W/SCRIBE  
A FIR SNAG 39" BRS. N61°E 48.2 FT. W/SCRIBE  
A FIR 18" BRS. S57°E 17.7 FT. W/HEALED BLAZE  
A FIR STUMP 40" BRS. S19°E 136.0 FT.  
A FIR 14" BRS. S28°W 10.9 FT. W/HEALED BLAZE

LANE COUNTY  
WEY. CO. 1979 = N89°59'10"E 2619.37  
B.L.M. 1971 = S89°36'W 39.64 CH. = 2616.24  
ORIG. G.L.O. = S89°50'W 40.00 CH. = 2640.00

N 1/4 COR. SEC. 2, T21S, R4W, W.M.  
Fd. BLM BRASS CAP (1971) FROM WHICH:  
A FIR 18" BRS. N2 1/2°W 29.9 FT. W/HEALED BLAZE  
A FIR SNAG 20" BRS. N15°W 25.4 FT. W/SCRIBE  
A FIR STUMP 18" BRS. S32°E 19.0 FT. NO SCRIBE VISIBLE

DOUGLAS COUNTY  
T.L. 200  
DEED BOOK 78, PAGE 126, L.C.O.D.R.  
REC. - NOV. 23, 1908  
Fd. 1/2" MONEL PIPE  
1.40 WEST

T.L. 100  
DEED BOOK 84,  
PAGE 358,  
L.C.O.D.R.  
REC. - OCT. 12, 1909

SURVEY FOR  
WEYERHAEUSER CO.

NW 1/4 SECTION 2, T21S, R4W, W.M.  
SCALE - 1" = 400' FEBRUARY 27, 1987  
DOUGLAS COUNTY, OREGON

THE BEARINGS USED HEREIN ARE BASED  
UPON SOLAR OBSERVATION.

SEE SEPARATE NARRATIVE DOCUMENT

W 1/4 COR. SEC. 2, T21S, R4W, W.M.  
SET 1" X 3/8" I. PIPE W/CAP FROM WHICH:  
ROTTED STUMP HOLE N79°E 14.4 FT. W/SCRIBE  
A CHINK 20" BRS. N67°W 6.4 FT. TO NAIL  
A FIR 17" BRS. S72°E 23.9 FT. TO NAIL  
MARKED NEW:  
A FIR 14" BRS. N2°W 14.7 FT. TO "W" NAIL  
SCRIBED "E 1/4 S 3 BT"  
A FIR 11" BRS. S20°E 28.4 FT. TO "W" NAIL  
SCRIBED "W 1/4 S 2 BT"  
ALSO FOUND A STEEL FENCE POST  
BEARING N19°E 0.35 FT.

SE PROP. COR.  
SET 1" X 3/8" I. PIPE W/CAP FROM WHICH:  
A FIR 8" BRS. S27°E 17.6 FT. TO "W" NAIL  
SCRIBED "PCBT"  
A FIR 9" BRS. S66°W 17.3 FT. TO "W" NAIL  
SCRIBED "SE PCBT"

C 1/4 COR. SEC. 2, T21S, R4W, W.M.  
SET 1" X 3/8" I. PIPE W/CAP FROM WHICH:  
A FIR 10" BRS. N40°W 19.8 FT. TO "W" NAIL  
SCRIBED "C 1/4 BT"  
A FIR 10" BRS. S63°W 18.1 FT. TO "W" NAIL  
SCRIBED "C 1/4 S 2 BT"  
ALSO A FENCE CORNER BRS. N54°47'E  
39.4 FT. - FENCE RUNS E, W & N.

E 1/4 COR. SEC. 2, T21S, R4W, W.M.  
Fd. LANE COUNTY BRASS CAP (1979)  
AND BT'S:  
A FIR 11" BRS. N60°W 23.4 FT. (CEN) W/HEALED  
BLAZE  
A YEW 19" BRS. N15 1/2°W 12.1 FT. (CEN) W/"CS BT"  
SHOWING  
A FIR STUMP 42" BRS. N48°W 10.8 FT. W/SCAR  
ALSO A STONE 6" X 9" BRS. NORTH 0.50 FT.  
MARKED "1/4"  
FENCE CORNER N, E & W BRS. EAST 1.50 FT.



- - SET 1" X 3/8" IRON PIPE W/YELLOW PLASTIC CAP MARKED "GUILLE PLS 472".
- ⊙ - FOUND BRASS CAP MONUMENT AS NOTED.
- - POINT NOT SET

— LINE RIBBONED AND BLAZED W/NOTCH AND PAINTED RED.

[ ] - DEED DATA

-x-x- EXISTING FENCE LINE

CS File 63 / 451  
Map File M103-68

REGISTERED  
PROFESSIONAL  
LAND SURVEYOR  
*Charles W. Guile*  
OREGON  
MAY 8, 1980  
CHARLES W. GUILLE  
472

CHARLES W. GUILLE  
& ASSOCIATES, CO.  
Land Surveying  
52 Centennial Loop  
Eugene, OR 97401

M 103-68

CHARLES W GUILLE & ASSOCIATES, C<sup>o</sup> FILED  
LAND SURVEYING

52 CENTENNIAL LOOP  
EUGENE OREGON 97401  
TELEPHONE 343 9855

RESIDENCE OFFICE  
EUGENE OREGON  
TELEPHONE 935 2025

REFERENCE TO SURVEY MAP FOR WEVERHAFUSER CO  
NW 1/4 SECTION 2, T21S, R4W, WM.  
18 X 24 IRACING DATFD FEBRUARY 27, 1987

APR 8 1987  
COUNTY SURVEYOR  
DOUGLAS COUNTY, ORE

NARRATIVE.

THE PURPOSE OF THIS SURVEY WAS TO SURVEY AND BLAZE, FOR OUR CLIENT THE WEST AND SOUTH LINES OF TAX LOT 200 IN SECTION 2, T 21 S, R. 4 W, WM, IN DOUGLAS COUNTY, OREGON THE BLAZES HAVE A SINGLE NOTCH AND WERE PAINTED RED

THE CONTROLLING MONUMENTS WERE AS FOLLOWS. A DOUGLAS COUNTY BRASS CAP AT THE NORTHWEST CORNER, A BIM BRASS CAP AT THE NORTH 1/4 CORNER A LANE COUNTY BRASS CAP AT THE EAST 1/4 CORNER AND A BRASS CAP SET BY A PRIVATE SURVEYOR AT THE SOUTH 1/4 CORNER

THE BASIS OF BEARINGS WAS BASED ON A SOLAR OBSERVATION TAKEN AT A POINT APPROXIMATELY 400 FEET NORTH OF THE NORTH 1/4 OF SECTION 2 ON FEBRUARY 5, 1987

A THEODOLITE AND EDM CLOSED TRAVERSES WAS RAN TO TIE IN THE CONTROLLING CORNERS WITH CLOSED SUB-TRAVERSES RAN TO ESTABLISH THE LINES AS MARKED

TO ESTABLISH THE WEST ONE-QUARTER CORNER OF SAID SECTION 2, WE FOUND TWO PIECES OF FIR WOOD OUT OF A ROTTED FIR HOLE IN GROUND FOR THE ORIGINAL NORTHEAST BEARING TREE WE FOUND THE SCRIBING '1/4" ON ONE PIECE OF WOOD AND THE BOTTOM OF A "B" AND THE TOP OF A "T" ON THE SECOND PIECE OF WOOD THIS EVIDENCE CORRESPONDS WITH THE REPORT OF L E ANDERSON, FORESTER FOR BLM, WHO ON 9/9/60 MADE A REPORT FOR THE CORNER AND STATED THAT HE FOUND A BEARING TREE ONLY ANDERSON STATED THAT "THIS STUMP IS ROTTEN AND SCRIBING IS ON A PIECE OF LOOSE PITCH STICKING OUT OF STUMP". ANDERSON DID NOT DO ANYTHING TO PERPETUATE THE CORNER.

ON MAY 31, 1968, RONALD W VAN DOMELN, PROJECT ENGINEER FOR BLM, MADE A REPORT STATING THAT HE FOUND THE NE BT TO BE A ROTTED STUMP HOLE WITH A RING OF BARK TO DETERMINE THE POSITION AND HE ALSO FOUND THE SCRIBING VAN DOMELN FOUND A STUMP TO THE SOUTHWEST WHICH HE USED FOR SW BT AND HE SET A FENCE POST AT THE CORNER POSITION AND SET SPIKES IN TWO NEW RT'S

WE POSITIONED THE CORNER POSITION FROM TRANSIT TIES TO THE CENTER OF THE REMAINING NE BT AND THE STUMP (WE FOUND NO MARKS) AT THE POSITION OF THE SW BT BY USING THE BROKEN BOUNDARY METHOD THIS POSITION FELI 0 35 FEET SOUTHERLY OF THE FENCE POST SET BY VAN DOMELN.

I AM SUBMITTING THE REPORTS OF ANDERSON AND VAN DOMELN AS EXHIBITS 'A' AND 'B' RESPECTIVELY TO THIS NARRATIVE

THE SOUTH ONE QUARTER CORNER OF SECTION 2 WAS MONUMENTED BY LRS ROBERTS IN 1983 AND REPORTED IN DOUGLAS COUNTY AS REM NO 130 AND IN