

(N 89° 14' 20" E 2649.56')
 N 89° 11' 11" E 2649.04'







((NORTH 2640.00'))
 (N 0° 32' 09" W 2598.81')
 N 0° 30' 57" W 2598.38'

S 89° 36' W - BASIS OF BEARING - 2646.2'
 (S 89° 36' W 2646.01')
 ((S 89° 36' W 2633.4'))

● = CORNERS FOUND
 ◆ = CORNERS SET

FILED
 APR 27 1989
 COUNTY SURVEYOR
 DOUGLAS COUNTY, ORE.

1. - 1/4 COR. BET. 29-32
 FOUND IRON ROD, FROM WHICH:
 A 12" OAK BEARS S 12° E, 108.2' OBT
 A 50" FIR BEARS EAST, 13.0'
2. - W 1/16 COR. BET. 29-32
 SET A 5/8" X 30" I. ROD WITH 2" ALUM. CAP
 MKD. AS SHOWN, FROM WHICH:
 A 27" W. FIR BEARS N 70° W, 12.2'
 MKD. " W 1/16 S 29 BT"
 A 10" FIR BEARS S 5° E, 20.4'
 MKD. " W 1/16 S 32 BT"
3. - SEC. COR. 29-30-31-32
 FOUND A BLM BRASS CAP MKD. AS SHOWN:
 A 23" FIR BEARS N 50° W, 3.2' SHOWS A SCAR
 A 17" FIR BEARS S 43° W, 7.8' SHOWS A SCAR
 A 13" FIR BEARS S 16° E, 13.0' SHOWS A SCAR
 A 16" FIR BEARS N 81° E, 4.8' SHOWS A SCAR
 A 17" FIR BEARS S 33° E, 19.8' SHOWS A SCAR
4. - S 1/16 COR. BET. 29-30
 SET A 5/8" X 30" I. ROD WITH 2" ALUM. CAP
 MKD. AS SHOWN:
 A 18" FIR BEARS S 84° W, 14.4'
 MKD. " S 1/16 S 30 BT"
 A 18" W. FIR BEARS S 81° E, 18.9'
 MKD. " S 1/16 S 29 BT"
5. - SW 1/16 COR. SEC. 29
 SET A 5/8" X 30" I. ROD WITH 2" ALUM. CAP
 MKD. AS SHOWN:
 A 19" FIR BEARS N 43° W, 17.6'
 MKD. " SW 1/16 S 29 BT"
 A 13" FIR BEARS S 47° E, 12.2'
 MKD. " SW 1/16 S 29 BT"
6. - CS 1/16 COR. - SEC. 29
 SET A 5/8" X 30" I. ROD WITH 2" ALUM. CAP
 MKD. AS SHOWN:
 A 15" FIR BEARS S 75° W, 13.6'
 MKD. " CS 1/16 S 29 BT"
 A 10" FIR BEARS N 65° E, 14.2'
 MKD. " CS 1/16 S 29 BT"
7. - C 1/4 COR. - SEC. 29
 FOUND 5/8" I. ROD AND STEEL POST
 A 11" FIR BEARS S 50° W, 18.7' SHOWS A SCAR
 A 25" CED. BEARS S 68° E, 17.3' SHOWS A SCAR
8. - CW 1/16 COR. SEC. 29
 SET A 5/8" X 30" I. ROD WITH 2" ALUM. CAP MKD. AS SHOWN:
 A 21" W. FIR BEARS N 53° W, 18.3'
 MKD. " CW 1/16 S 29 BT"
 A 12" W. FIR BEARS S 25° W, 14.9'
 MKD. " CW 1/16 S 29 BT"
9. - 1/4 COR. BET. 29-30
 FOUND A 5/8" I. ROD AND STEEL POST
 A 14" MAD. BEARS N 81° W, 28.8' SCRIBES VISIBLE
 A 16" FIR BEARS N 79° E, 18.5' SCRIBES VISIBLE



SURVEY OF RECORD
 TO SET ONE-SIXTEENTH CORNERS IN SW 1/4, SEC. 29,
 T 28 S, R 8 W, W.M.
 1" = 200'
 NARRATIVE ATTACHED
 MAR., 1989

() = STUNTNER SURVEY - 1977
 () = GLO SURVEY - 1855
 (()) = GLO SURVEY - 1875

REGISTERED
 PROFESSIONAL
 LAND SURVEYOR
 OREGON
 OCTOBER 4, 1967
 BURTON W. HOLT,
 418

LONE ROCK TIMBER CO.
 P. O. BOX 1127 ROSEBURG, OREGON 503-673-0141
 BY: BURTON W. HOLT
 DATE: MAR 1989 SCALE: 1" = 200' DRAWN BY: B.W.H. SHEET:

COUNTY SURVEYORS FILE DATA
 DO NOT REMOVE FROM OFFICE

FILED 63/5310
 MAR 19 1989

M107-80

SURVEY NARRATIVE

FILED

Handwritten initials

APR 27 1989

SURVEY FOR: Lone Rock Timber Co.
P.O. Box 1127
Roseburg, OR. 97470

COUNTY SURVEYOR
DOUGLAS COUNTY, ORE.

DATE: March, 1989

LOCATION: South-west one-quarter, Section 29,
Township 28 south, Range 8 west of the
Willamette Meridian, Douglas County,
Oregon.

PURPOSE: To set the one-sixteenth corners.

PROCEDURE: I looped a traverse through corners
marking the south-west one-quarter of
Section 29 and then proceeded to calculate
and set the one-sixteenth corners according
to the procedures as set forth in the 1973
"Manual of Surveying Instructions".

EQUIPMENT: This survey was executed with a Lietz Set-4
total station theodolite and an Amdek
System 286 computer.

BASIS OF BEARING: All bearings of this survey are based on
the bearing of the section line between
Sections 29 and 32 as determined by the
General Land Office survey in 1855.

REGISTERED
PROFESSIONAL
LAND SURVEYOR

Handwritten signature of Burton W. Holt

OREGON
OCTOBER 4, 1987
BURTON W. HOLT,
418