

FILED
 SF
 JAN 16 1990 TF
 COUNTY SURVEYOR
 DOUGLAS COUNTY, ORE.
 TF

S9 | S10 | WC
 | | |
 S16 | S15 |
 FD. 3/4" I.R. BURIED 12"
 AS PER DCSO RENEWAL NO. 198
 FROM WHICH:
 A 30" B. OAK BEARS S.31°W., 18.5 FT. WITH HEALED BLAZE.

(STEWART, N.88°26'W., 2379.4 FT.)
 N.88°26'00"W., 2378.14 FT.
 BASIS OF BEARINGS M2-9

1/4 S10
 S15 COR.

FD. 1" I.P. W/BASS CAP PROJECTING 6" ABOVE THE GROUND
 AS PER DCSO RENEWAL NO. 191
 FROM WHICH:
 A 27" W. OAK BEARING TREE BEARS N.78°15'W., 36.3 FT (ROTTED FACE)
 A 29" B. OAK BEARS S.19°00'W. 42.2 FT. (WITH HEALED BLAZE)



NI/16 | S15
 S16 | COR.
 (STEWART, N.87°38'W., 1286.9 FT.)
 N.87°38'52"W., 1273.54 FT.

NWI/16 | S15
 COR.
 (STEWART, N.87°38'W., 1286.9 FT.)
 N.87°36'37"W., 1293.32 FT.

CNI/16 | S15
 COR.

FD. 5/8" I.R. BY RUPPERT IN 1976 PROJECTING 8" ABOVE GROUND
 AS PER M56-54
 FROM WHICH BEARING TREES BY STEWART IN 1922 BEARS:
 A 24" B. OAK BEARS S.32°45'E., 25.3 FT
 (REC.S.33°E., 26.1 FT.)
 A 28" P. PINE BEARS N.71°30'E. 54.8 FT.
 (REC. N.73°E.)

I SET A 5/8X30" I.R W/ALUM. CAP MKD.
 NW 1/16
 S15
 PLS 1941
 FROM WHICH A BEARING TREE BY STEWART IN 1922 BEARS:
 A 24" ROTTED D. FIR BEARS S.87°30'E., 81.3 FT. (WITH PARTIAL SCRIBE VISIBLE)
 I MARK NEW TREE:
 A 26" D. FIR BEARS S.10°30'E., 5.2 FT.(SCRIBED NW 1/16 S15 BT)
 AND A BEARING OBJECT:
 A PP 8L POLE # 152703 BEARS N.39°00'E., 22.47 FT. TO A
 BRASS WASHER MKD. PLS 1941 NAILED INTO THE BASE.

FD. 3/4" I.P. FIRMLY SET BY G.G. STEWART IN 1922
 I REMOVE IT AND REPLACE IN THE EXACT SAME POSITION A 5/8"X30" I.R. W/AL. CAP MKD.

NOTE:
 (RESETTING THE ORIGINAL 3/4" I.P. ON S. EDGE OF MY 5/8" I.R. AND FLUSH WITH THE GROUND)
 FROM WHICH BEARING TREES BY STEWART IN 1922 BEARS:
 A 26" D. FIR BEARS N.18°30'W., 37.5 FT. (WITH HEALED BLAZE)
 A 16" ROTTED D. FIR STUMP BEARS S. 60°E., 5.9 FT. (WITH SCRIBE MARKS VIS.)
 I MARK A NEW TREE
 A 16"D. FIR BEARS N.81°30'E., 36.4 FT. (SCRIBED CN 1/16 S15 BT)

**SURVEY TO RECOVER CORNERS AND POST LINES
 IN THE NW 1/4 OF SECTION 15, T.30S., R.4W., W.M.**
 JANUARY, 1990 SCALE 1" = 200'

SURVEYED FOR:
 ROY COX & JOHN OTT
 11826 TILLER TRAIL HWY.
 DAYS CREEK, OR 97429

SURVEYED BY:
 BAUGHMAN TECHNICAL SERVICE INC.
 433 S.E. MAIN ST.
 ROSEBURG, OR 97470

REGISTERED
 PROFESSIONAL
 LAND SURVEYOR

Kristian O. DeGroot

OREGON
 JULY 17, 1881
 KRISTIAN O. DEGROOT
 1941

NARRATIVE:

THE PURPOSE OF THIS SURVEY WAS TO POST THE NORTH AND EAST LINES OF THE SE 1/4 OF THE NW 1/4 OF SECTION 15, T.30S., R.4W., W.M. THIS SURVEY WAS BASED UPON M2-9, A 1922 SURVEY BY G.G. STEWART. THE WEST HALF OF THE NORTH LINE OF THE SECTION WAS USED AS BASIS OF BEARINGS PER M2-9. I FOUND AND ACCEPTED STEWART'S C 1/4, CN 1/16 AND NW 1/16 CORNERS, AFTER TYING THE 1/4 COR BET. SEC'S 10 & 15 AND THE N 1/16 BET. SEC'S 15 & 16 TO ESTABLISH SEARCH AREAS. WE THEN POSTED THE NORTH & EAST LINES OF THE SE 1/4 OF THE NW 1/4 WITH STEEL FENCE POSTS FOR CUTTING LINES.
 THE FIELD WORK WAS PERFORMED BY K. DEGROOT AND L. FANNING USING A WILD TIAE THEODOLITE AND TOPCON EDM. CALCULATIONS BY K. DEGROOT AND DRAFTING BY G. BAUGHMAN.

CI/4 | S15
 COR.

FD. A 1" I.P. PROJECTING 6" ABOVE THE GROUND AS PER THOMPSON IN 1962 M22-46
 FROM WHICH A BEARING TREE BY STEWART IN 1922 :
 A 60" BURNED & ROTTED D. FIR STUMP BEARS N.38°W., 36.8 FT. (WITH PARTIAL SCRIBE VISIBLE)
 AND A BEARING TREE BY THOMPSON IN 1962:
 A 26" D. FIR BEARS N.42°E., 119.9 FT. (WITH BARK SCRIBE MKD. 3683 C 1/4S BT VIS.)
 I MARK NEW TREES:
 A 8" D. FIR BEARS S.42°30'E., 10.3 FT.(SCRIBED C 1/4 S15 BT)

LAND SURVEYORS ARE TO NOT REMOVE FROM

MAP FILE M109-47