

**COUNTY SURVEYORS FILE DATA
DO NOT REMOVE FROM OFFICE**

**A SURVEY FOR SILVER BUTTE TIMBER CO.
LOCATED IN SECTION 8, T32S, R3W, W.M.,
DOUGLAS COUNTY, OREGON**

FILED

Date: 5-28-96 By: GL
This survey consists of:
Map: M 123-79
Narrative: _____
Corner Rpt: _____

DOUGLAS COUNTY
SURVEYOR

FD. B. CAP
17 1/2" HEMLOCK BEARS N 36°30'E, 12.4'
22 1/2" D. FIR BEARS N 54°45'W, 9.2'
17 1/2" W. FIR BEARS S 39°30'E, 52.0'

FD. ALUM. CAP
ROTTEN STUMP BEARS S 72°W, 10.6'
20" D. FIR BEARS N 85°45'E, 72.9'
17" D. FIR BEARS N 14°40'W, 46.4'

FD. B. CAP
26 1/2" D. FIR BEARS N 39°E, 37.6'
27 1/2" D. FIR BEARS S 35°E, 52.8'
12" D. FIR BEARS S 5°W, 31.7'
23 1/2" SNAG BEARS N 45°W, 13.2'

FD. ALUM. CAP
15" D. FIR BEARS N 8°W, 63.5'
17" D. FIR BEARS S 74°W, 33.6'

- CALCULATED POSITION -
AN OPEN ENDED TRAVERSE WHICH TIED
THE N 1/4 CORNER WAS CLOSED AND ADJUSTED
UPON THIS RECORD POSITION. SAID POSITION
CALCULATED BY DIST.-DIST. INTERSECTION
USING RECORD DISTANCES PER M 83-55.
N 1/4 COR. - FD. B. CAP
33" FIR BEARS N 26°40'W, 46.6'
17" FIR BEARS S 0°05'E, 27.6'
34 1/2" FIR SNAG BEARS S 25°45'E, 10.4'
48" SUGAR PINE STUMP - RECORD N 59°15'W 34.6'

LEGEND:

- △ - CALCULATED POINT
- - FOUND AS NOTED
- - SET 5/8" x 30" I.R. w/PLASTIC CAP MARKED 'LANG SURVEYING'
- +— THIS SYMBOL INDICATES APPROX. LOCATION OF METAL POSTS.
- ==== - LINE PREVIOUSLY POSTED
- () - RECORD PER M83-55

NARRATIVE:

SUBDIVISION OF SECTION 8 USING THE CALCULATED POSITION FOR THE N 1/4 CORNER & FOUND MONUMENTS AS SHOWN.
FIELD CREW: DUANE, MICHAEL, THOMAS & GREG
EQUIPMENT: TM 6 & RED 1 EDM
DRAFTING: BILL WARREN
COMPUTATIONS: GREG LANG

NEW CORNER INFORMATION

- ① SET CS 1/16TH
15" HEMLOCK BEARS N 77°16'E 24.73' (SCRIBED 'CS 1/16 S8' 'BT')
15" HEMLOCK BEARS S 7°27'E 22.40' (SCRIBED 'CS 1/16 S8' 'BT')
- ② SET SW 1/16TH
9" FIR BEARS S 18°51'W 10.97' (SCRIBED 'SW 1/16 S8' 'BT')
6" FIR BEARS N 68°18'W 15.23' (SCRIBED 'SW 1/16 S8' 'BT')
- ③ SET CW 1/16TH
8" FIR BEARS S 53°22'W 17.97' (SCRIBED 'CW 1/16 S8' 'BT')
6" MADRONA BEARS S 58°32'E 17.27' (SCRIBED 'CW 1/16 S8' 'BT')
- ④ SET NW 1/16TH
10 1/2" FIR BEARS N 55°20'E 12.02' (SCRIBED 'NW 1/16 S8' 'BT')
8" FIR BEARS N 16°03'W 34.81' (SCRIBED 'NW 1/16 S8' 'BT')
- ⑤ SET N 1/16TH S7IS8
11" FIR BEARS S 33°53'W 27.83' (SCRIBED 'N 1/16 S7' 'BT')
6" FIR BEARS S 57°35'E 23.08' (SCRIBED 'N 1/16 S8' 'BT')

THESE BEARINGS & DISTANCES ARE TO A SPIKE IN THE FRONT OF EACH TREE NEAR THE BOTTOM OF THE TREE. TREE SIZES TAKEN IN 1993.

1" = 500'
OCTOBER 1993

SURVEYED BY:

GREG LANG
7550 WILLIS CREEK RD.
WINSTON, OREGON 97496



EXPIRES: 12-31-96