

BOUNDARY LINE SURVEY
LOCATED ON THE EAST LINE OF SEC. 36
T.27 S.. R.9 W.. W.M.. COOS CO.. OREGON

FILED

Date: 1-21-97 By: JP

This survey consists of:

Map: M126-26

Narrative: _____

Corner Rpt: _____

DOUGLAS COUNTY
JP SURVEYOR

SURVEY FOR:

GEORGIA-PACIFIC WEST, INC.
P.O. BOX 1528
COOS BAY, OR. 97420

SURVEY BY:

CLYDE F. MULKINS
TIMBER CRUISING & ENGINEERING
P.O. BOX 750
COOS BAY, OR. 97420

SURVEY AMENDED -
SEE M 126 - 72

REGISTERED
PROFESSIONAL
LAND SURVEYOR

Clyde F. Mulkins

OREGON
JULY 16, 1982
CLYDE F. MULKINS
2006

EXPIRES 12-31-98

LEGEND

- FD. CORNERS AS SHOWN
- SET 5/8" X 36" REBAR WITH PLASTIC CAP MARKED "LS 2006"
- LINES FLAGGED AND BLAZED
- () GLO RECORD



BASIS OF BEARING
SOLAR OBSERVATION

SCALE 1" = 600'
JANUARY 6, 1997

FD. A 1957 DOUGLAS CO. BRASS CAP FROM WHICH:
 FD. RECORD 52" DF STUMP N33 1/2°E. 32 lks. - UPROOT
 FD. RECORD 32" CEDAR STUMP WITH SCRIBES BEARS N20°W. 41 lks.
 FD. RECORD 52" CEDAR STUMP BEARS S33°W. 80 lks. - NO MARKS
 FD. 20" DF WITH A HEALED FACE BEARS N3 1/2°E. 15 lks.
 FD. 17" DF WITH A HEALED FACE BEARS N50°W. 86 lks.
 FD. 19" DF WITH A HEALED FACE BEARS S66 1/2°W. 68.5 lks.

S.25 S.30
S.36 S.31

R.9 W.
R.8 W.

COOS COUNTY

(NORTH)
S 0°45'48"W
2690.38
(40.00 CHS.)

DOUGLAS COUNTY

CORNER NOTES FOR 1/4 CORNER BETWEEN SEC.'S 36 AND 31

- 10" DF SCRIBED "1/4 S36 BT" BEARS N17°W. 8.0 FT.
- 15" DF SCRIBED "1/4 S31 BT" BEARS N87°E. 10.7 FT.
- 12" DF SCRIBED "1/4 S31 BT" BEARS S25°E. 12.1 FT.
- 9" DF SCRIBED "1/4 S36 BT" BEARS S28°W. 25.4 FT.

NARRATIVE

THE PURPOSE OF THIS SURVEY WAS TO MARK THE LINES SHOWN FOR FUTURE LOGGING OPERATIONS. COOS COUNTY RECORDS USED FOR CONTROL WERE: CS# 22B15: BK. G55 PG. 190 AND 191.

DOUGLAS COUNTY RECORDS USED FOR CONTROL WERE T.27 S.. R.8 W. CORNER RENEWAL NO. 15 AND 22.

THE 1/4 CORNER BETWEEN SECTIONS 31 AND 36 WAS RE-ESTABLISHED BY PROPORTION MEASUREMENT BETWEEN THE COMMON SECTION CORNERS HOLDING LINE TO THE FOUND G.L.O. LINE TREE (RECORD 2 CHS. SOUTH FROM THE 1/4 CORNER). I SPOKE WITH BOYD PETERSON, CHIEF CADASTRAL SURVEYOR FOR THE BLM COOS BAY DISTRICT, WHO VERIFIED THAT THIS 1/4 CORNER WAS SET IN ACCORDANCE WITH METHODS HIS OFFICE USES PER WRITTEN INSTRUCTIONS FROM THE PORTLAND BLM OFFICE. THE 1973 BLM MANUAL OF SURVEYING INSTRUCTIONS, TO THE CONTRARY, SUGGESTS USING A FOUND LINE TREE AS A MONUMENT FOR PROPORTIONING A LOST 1/4 CORNER POSITION.

THE FIELD WORK WAS PERFORMED BETWEEN OCTOBER 23 AND NOVEMBER 15, 1996. ASSISTING ME WITH THIS SURVEY WERE TROY RAMBO AND RANDY MADDEN.

S0°45'48"E 95.59
(2.00 CHS.)

FD. ORIG. 36" DF
LINE TREE - NOW
A 6' HIGH STUMP

S.36 S.31

1/4 COR.

(NORTH)
S 1°23'53"W
2595.22
(38.00 CHS.)

S.36 S.31

S.1

FD. A 1970 DOUGLAS CO. BRASS CAP FROM WHICH:
 FD. 31" ROTTEN AND BURNED WH STUMP BEARS N68°E. 21.0
 FD. REMAINS OF RECORD 22" YEW - UPROOTED AND BURNED
 I SCRIBED "S36 BT" ON AN 8" DF BEARS N64°W. 22.1 FT.
 I SCRIBED "S36 BT" ON AN 8" DF BEARS N2°W. 4.5 FT.
 I SCRIBED "S31 BT" ON AN 8" DF BEARS N60°E. 21.6 FT.
 I SCRIBED "X BT" ON A 9" DF BEARS S17°W. 8.6 FT.

COUNTY SURVEYORS FILE DATA
DO NOT REMOVE FROM OFFICE