

MAP OF SURVEY

LOCATED in the NW 1/4 of Section 31 & the SE 1/4 of Section 30, T.25S., R.7W., W.M.
in Douglas County, Oregon.

February 21, 2000

FILED

Date: 3-16-2000 By: JP

This survey consists of:

Map: M134-32

Narrative: _____

Corner Rpt: _____

DOUGLAS COUNTY
SURVEYOR

SURVEYED BY: DAVID EDWARDS LAND SURVEYING
P.O. BOX 361
OAKLAND, OREGON 97462
PHONE: (541) 459-0512

SURVEYED FOR: BASCO LOGGING
P.O. BOX 131
WINCHESTER, OREGON

David A. Edwards

EXPIRES 12/31/01

SE 1/16 CORNER SECTION 30
FOUND 1 1/4" DIAM. IRON PIPE
W/TEE FITTING ON TOP
PER M 102-79.

CS 1/16 CORNER SECTION 30
FOUND IRON PIPE W/ALUMINUM
CAP PER M 94-31

M 102-79
(S.89°53'18"E. 1300.78')
S.89°54'51"E. 1295.60'

M 94-31
(N.0°20'23"W. 1373.62')
N.0°25'26"W. 1373.50'

M 102-79
(N.0°34'46"W. 1342.99')
N.0°51'03"W. 1343.62'

SET WEST 1/16 CORNER
FD. 5/8" IRON ROD W/CAP
PER 1994-0032 BRS. S.86°56'21"W. 14.18'
A 2" DIAM. FIR BRS. S.30°W. 19.55'
AN 11" DIAM. FIR BRS. S.64°W. 29.60'
BOTH W/HHEALED BLAZES.

NW 1/16 CORNER
FD. 5/8" DIAM. IRON ROD
W/PLASTIC CAP PER M 119-33
POINT "A"

SET CW 1/16 CORNER AT
COMP. POSITION PER M 119-33.
AN 18" DIAM. FIR SCRIBED
"CW 1/16 S31 BT" BRS. S.51°E. 10.01'
A 6" FIR SCRIBED "CW 1/16 S31 BT"
BEARS S.13°W. 7.93'

SET CENTER 1/4 CORNER AT COMP. POSITION PER M 119-33.

A 25" DIAM. FIR BRS. N.12°E. 36.69'
A 7" DIAM. FIR BRS. S.28°E. 16.81'
A 7" DIAM. FIR BRS. S.10°W. 13.40'
A 6" DIAM. FIR BRS. N.78°W. 20.35'

ALL TREES SCRIBED "C 1/4 S31 BT"

LEGEND

- INDICATES DOUGLAS COUNTY SURVEYOR'S BRASS CAP FOUND PER C.S. 60/29.
- INDICATES 5/8" X 30" STEEL PIN W/RED PLASTIC CAP MKD. "D.A. EDWARDS-LS 2339" SET.
- () DENOTES RECORD DATA PER M 119-33 UNLESS NOTED OTHERWISE.

COMP. = COMPUTED.

SCALE: 1" = 400'

BASIS OF BEARINGS: LINE BETWEEN POINT "A" AND THE NORTH 1/4 CORNER OF SECTION 31 COMPUTED PER M 119-33.
RECORD = N.75°03'24"E., 1348.30' MEAS. = N.75°03'24"E., 1348.42'

————— INDICATES BOUNDARY BLAZED AND FLAGGED THIS SURVEY.

NARRATIVE

THE PURPOSE OF THIS SURVEY IS TO MARK THOSE BOUNDARIES SHOWN AS BOLD LINES HEREON. CLOSED TRAVERSES WERE RUN WHICH TIED IN THE CONTROLLING MONUMENTS AS SHOWN HEREON. IN SECTION 31 THE SUBDIVISION OF THE NW 1/4 WAS FIRST COMPUTED PER M 119-33. AFTER POINT "A" AND THE NORTH 1/4 CORNER WERE TIED TOGETHER, THE RECORD POSITION OF POINT "A" WAS HELD AND THE CW 1/16 AND CENTER 1/4 CORNERS WERE SET AT THE RECORD POSITIONS. AT THE WEST 1/16 CORNER I HELD THE RECORD BEARING AND DISTANCE FROM FOUND POINT "A". THE BEARING TREES SHOWN FOR SAID WEST 1/16 COR. ARE FROM 1994-0032 AND FACE THE FOUND PIN. ALL BEARING TREES SHOWN WERE MEASURED TO CENTER OF TREE AT ROOT CROWN.

FIELD CREW: DAVID EDWARDS, BRANT MILLER AND GABE EDWARDS.

EQUIPMENT: NIKON DTM 430 TOTAL STATION.

COMPS. AND DRAFTING: DAVID EDWARDS.

