

RECORD OF SURVEY
 LOCATED IN
 SECTION 6, T28S, R3W, W.M.
 AND
 SECTION 12, T28S, R4W, W.M.
 FOR
 SENECA-JONES TIMBER COMPANY
 BY
 ROBERTS SURVEYING INC.
 P.O. BOX 7155
 EUGENE, OREGON 97401
 PHONE (541) 345-1112



SCALE: 1" = 500'
 MAY 3, 2001

SEC. COR. 31 & 36
 FD. 1989 BLM 3-1/4"
 BRASS CAP
 BEARING TREES
 6" FIR, N 59°E, 16.2' (SCAR VIS)
 8" FIR, N 41°W, 25.3' (SCAR VIS)

1/4 SECTION 31
 FD. 1989 BLM 3-1/4"
 BRASS CAP
 BEARING TREES
 16" FIR, N 4°W, 22.5' (SCAR VIS)
 24" FIR, N 69°W, 44.5' (SCAR VIS)

SEC. COR. 31 & 32
 FD. 1989 BLM 3-1/4"
 BRASS CAP AND
 1" IRON ROD ALONGSIDE
 BEARING TREES
 10" FIR, N 33°E, 14.6' (SCAR VIS)
 8" FIR, N 83°W, 22.5' (SCAR VIS)

FILED
 Date: 6/5/2001 By: JP
 This survey consists of:
 Map: M138-15
 Narrative:
 Corner Rpt:
 DOUGLAS COUNTY
 SURVEYOR

LEGEND

- MONUMENTS FOUND AS NOTED
- MONUMENTS SET: 5/8" X 36" IRON PINS WITH 2-1/2" ALUM. CAPS STAMPED AS SHOWN
- () DATA OF RECORD
- ~ DENOTES RIDGE
- DENOTES CREEK OR DRAW
- ==== DENOTES GRAVEL OR DIRT ROAD
- LINES BLAZED, PAINTED RED, MARKED WITH RED RIBBON AND RED FENCE POSTS

REGISTERED
 PROFESSIONAL
 LAND SURVEYOR
Ted C. Baker
 OREGON
 JULY 25, 1991
 TED C. BAKER
 2488
 EXPIRES 12-31-2001

REFERENCES

- 1) 1910 G.L.O. SURVEY BY WILLIAM GIBB
- 2) 1989 B.L.M. DEPENDENT RESURVEY BY PETERSON
- 3) 1881 G.L.O. SURVEY BY WILLIAM BYARS

NOTES


- 1) ALL NEW BEARING TREES ARE SCRIBED AND PAINTED RED
- 2) DISTANCES TO BEARING TREES ARE CENTER MEASURE

NARRATIVE

THE PURPOSE OF THIS SURVEY IS TO POST AND BLAZE THE NORTHWEST 1/4 OF SECTION 6, TOWNSHIP 28 SOUTH, RANGE 3 WEST AND THE NORTH SECTION LINE OF SECTION 12, TOWNSHIP 28 SOUTH, RANGE 4 WEST OF THE WILLAMETTE MERIDIAN FOR SENECA-JONES TIMBER COMPANY. THE NORTH 1/4 CORNER OF SECTION 6 WAS ESTABLISHED AT A PROPORTIONATE DISTANCE BETWEEN THE NORTHWEST AND NORTHEAST SECTION CORNERS OF SAID SECTION 6 AND SET ON THE SOUTH SECTION LINE OF SECTION 31, TOWNSHIP 27 SOUTH, RANGE 3 WEST. THE WEST 1/4 CORNER OF SECTION 6 WAS ESTABLISHED AT A PROPORTIONATE DISTANCE BETWEEN THE NORTHWEST AND SOUTHWEST SECTION CORNERS OF SAID SECTION 6 AND SET ON THE EAST SECTION LINE OF SECTION 1, TOWNSHIP 28 SOUTH, RANGE 4 WEST. THE CENTER 1/4 CORNER OF SECTION 6 WAS THEN ESTABLISHED AT THE INTERSECTION OF THE NORTH-SOUTH AND EAST-WEST CENTERLINES OF SAID SECTION 6. THE 1/4 CORNER BETWEEN SECTIONS 1 AND 12 WAS ESTABLISHED AT PROPORTIONATE DISTANCE BETWEEN THE NORTHWEST AND NORTHEAST SECTION CORNERS OF SAID SECTION 12. PROPERTY LINES WERE MARKED WITH RED PAINTED BLAZES, RED RIBBON AND RED METAL FENCE POSTS.

SECTION CORNER

FD. 1957 DOUGLAS CO.
 2-1/2" BRASS CAP
 BEARING TREES
 24" FIR, N 76°W, 5.2' (SCAR VIS.)
 16" FIR, N 50°E, 9.2' (SCAR VIS.)
 28" FIR, S 72°E, 30.0' (SCAR VIS.)
 36" CEDAR, N 55°W, 23.5' (SCAR VIS.)



1/4 CORNER

BEARING TREES
 8" FIR, S 53°W, 48.5'
 12" FIR, N 45°W, 31.8'

SECTION CORNER

FD. 1961 DOUGLAS CO.
 2-1/2" BRASS CAP
 BEARING TREE
 42" FIR SNAG, N 84°W, 16.2' (SCAR VIS.)
 NEW BEARING TREES
 10 W.FIR, N 38°W, 50.1'
 26" CEDAR, S 35°W, 69.1'

