

FILED

Date: 7-11-2005 By: JC

This survey consists of:

Map: M148-7

Name: _____

Corner Rpt: _____

DOUGLAS COUNTY SURVEYOR

BOUNDARY LINE SURVEY
LOCATED ALONG THE WEST LINE OF SECTION 10.
T.31S.. R.8W.. W.M.. DOUGLAS COUNTY, OREGON

4 3
9 10

FD. A 1961 BLM BRASS CAP

THE RECORD 28" FIR - IN GOOD CONDITION
THE RECORD 14" FIR - ROTTEN SNAG
THE RECORD 16" FIR - NOW A LOW STUMP - NO MARKS
THE RECORD 7" HEMLOCK - GONE
THE RECORD 7" FIR(NOW 19") - IN GOOD CONDITION
SCRIBED "S10 BT" ON AN 18" GF - BEARS S3°E. 18.0 FT.
SCRIBED "BT" ON A 7" DF - BEARS S79°W. 23.0 FT.
ALSO CHOPPED AN "X" 4 FT. ABOVE STUMP HEIGHT



BASIS OF BEARING - ASSUMED
PER M91 - 13

JUNE 30, 2005
SCALE 1" = 400'

SURVEY FOR:

SENECA JONES TIMBER COMPANY
P.O. BOX 2129
ROSEBURG, OR 97470

SURVEY BY:

MULKINS & RAMBO, LLC
P.O. BOX 809
NORTH BEND, OR 97459

(N2°23'W)
N2°21'55"W
2561.10
(38.79 CHS.)

REGISTERED
PROFESSIONAL
LAND SURVEYOR

Troy Rambo

OREGON
JULY 14, 1998
TROY J. RAMBO
2865

EXPIRES 12-31-06

FD. A 1961 BLM BRASS CAP

THE RECORD 37" FIR - IN GOOD CONDITION
THE RECORD 45" FIR - IN GOOD CONDITION
THE RECORD 15" FIR - IN GOOD CONDITION
SCRIBED "1/4 S9 BT" ON AN 8" DF - BEARS S83°W. 27.4 FT.

1/4

BASIS OF BEARING
(N1°42'00"E)
2705.22
(40.98 CHS.)

LEGEND

⊙ FD. CORNER AS SHOWN

— LINES FLAGGED, BLAZED, AND MARKED
WITH 5 1/2' STEEL POSTS

X CROSSING POST

NARRATIVE

THE PURPOSE OF THIS SURVEY WAS TO RE-MARK THE LINES AS ESTABLISHED
IN M91 - 13 FOR FUTURE FOREST OPERATIONS. CONTROL WAS BASED ON M91 - 13.
ALL NEW BEARING TREES WERE MEASURED TO A 6" SPIKE AT SIDE CENTER
BASE. BEARINGS WERE MEASURED WITH A HAND COMPASS WITH A DECLINATION
17° EAST.

THE FIELD WORK WAS PERFORMED BY TROY RAMBO, CLYDE MULKINS
JUNE 11 AND JUNE 30, 2005.

ROCKED
ROAD

FD. A 1961 BLM BRASS CAP

THE RECORD 32" FIR - IN GOOD CONDITION
THE RECORD 25" FIR - NOW A 6' STUMP
THE RECORD 13" FIR - GONE
THE RECORD 23" FIR - IN GOOD CONDITION
SET STEEL POST 0.5' NORTH

9 10
16 15