

FILED

Date: 9-19-2007 By: JC

This survey consists of:

Map: H154-22

Narrative: _____

Corner Rpt: _____

DOUGLAS COUNTY SURVEYOR

MAP FILE H154-22

BOUNDARY LINE SURVEY - LOCATED ALONG THE SOUTH LINE OF SECTION 8, T.30S., R.3W., W.M., DOUGLAS COUNTY, OREGON

FD. A 1965 BLM BRASS CAP AND BT'S PER P.I. # 200500

FD. A 1963 D.C.S.O BRASS CAP - BENT - AND RECORD BT'S PER P.I. # 240500

FD. A 1966 D.C.S.O. BRASS CAP AND RECORD BT'S PER P.I. # 300500

718
18117

S89°27'44"W (S89°49'W - G.L.O.)
2638.41 (39.75 CHS.)

1/4

BASIS OF BEARING
(S89°49'00"W - G.L.O.)
2658.59 (39.75 CHS.)

819
17116

SCRIBED "1/4 S17 BT" ON A 10" DF - BEARS S24°W, 20.8 FT. A NEW BT TO THE EAST WAS NOT ADDED DUE TO A VERY ACTIVE YELLOW JACKET NEST



BASIS OF BEARING ASSUMED PER G.L.O.

SCALE 1" = 500'
SEPTEMBER 6, 2007

SURVEY FOR:

SENECA JONES TIMBER COMPANY
P.O. BOX 2129
ROSEBURG, OR 97470

SURVEY BY:

MULKINS & RAMBO, LLC
P.O. BOX 809
NORTH BEND, OR 97459

LEGEND

- FD. CORNER AS SHOWN
- LINE POSTED WITH 5 1/2' STEEL POSTS FLAGGED AND BLAZED
- () RECORD G.L.O. BEARING & DISTANCE

NARRATIVE

THE PURPOSE OF THIS SURVEY WAS TO FIND THE CORNERS AND MARK THE LINES AS SHOWN. CONTROL FOR THIS SURVEY WAS BASED ON: CORNER POINT IDENTIFIER OF T.30S., R.3W., - #200500, #240500 & #300500. POINT IDENTIFIER NO. OF T.31S., R.8W., - #500700 AND #540700. ALL NEW BEARING TREES WERE MEASURED TO A 6" SPIKE AT SIDE CENTER BASE UNLESS OTHERWISE NOTED. BEARINGS WERE MEASURED WITH A HAND COMPASS WITH A DECL. OF 17°E. THE FIELD WORK WAS PERFORMED BETWEEN JULY 23 AND SEPTEMBER 6, 2007 WITH THE ASSISTANCE OF KEVIN TEYLER AND FORREST RAMBO.

REGISTERED PROFESSIONAL LAND SURVEYOR

Troy Rambo

OREGON
JULY 14, 1998
TROY J. RAMBO
2865

EXPIRES 12-31-2008

MAP FILE H154-22