

BOUNDARY LINE SURVEY
LOCATED ALONG THE NORTH - SOUTH CENTERLINE OF
SECTION 36. T.30S.. R.2W.. W.M.. DOUGLAS COUNTY, OREGON

DOUGLAS COUNTY
SURVEYOR

25
36 1/4

FD. BRASS CAP
PER M70 - 15
FD. A 9" DF WITH A HEALED FACE - BEARS S70°W. 9.0 FT.
FD. A 12" DF WITH A HEALED FACE - BEARS N29°W. 5.8 FT.
FD. A FENCE POST WITH A U.S.F.S. SIGN - BEARS N71°W. 4.8 FT.
SCRIBED "1/4 S36 BT" ON A 10" DF - BEARS S31°E. 25.0 FT.



BASIS OF BEARING
SOLAR OBSERVATION

SURVEY FOR:

SENECA JONES TIMBER CO.
P.O. BOX 2129
ROSEBURG, OR 97470

ROSEBURG RESOURCES CO.
P.O. BOX 1088
ROSEBURG, OR 97470

SURVEY BY:

MULKINS & RAMBO, LLC
P.O. BOX 809
NORTH BEND, OR 97459

REGISTERED
PROFESSIONAL
LAND SURVEYOR

Troy Rambo

OREGON
JULY 14, 1998
TROY J. RAMBO
2865

RENEWAL 12-31-10

JUNE 30, 2010
SCALE 1" = 600'

N0°08'12"E
5387.56

LEGEND

- ⊙ FD. CORNER AS SHOWN
- LINE FLAGGED, BLAZED AND POSTED WITH 5 1/2' STEEL POSTS

FD. 1976 D.C.S.O. BRASS CAP 1 BT'S
PER C.S. 59-8
FD. A STEEL FENCE POST WITH A USFS SIGN - BEARS N85°W. 3.2 FT.
FD. A ALUMINUM POST WITH A USFS SIGN - BEARS S4°W. 3.3 FT.
A FENCE CORNER BEARS 1 FT. WEST

36 1/4

NARRATIVE

THE PURPOSE OF THIS SURVEY WAS TO MARK THE LINE BETWEEN THE EXISTING CORNERS, AS SHOWN, FOR FUTURE FOREST OPERATIONS.
THE NEW BEARING TREE WAS MEASURED TO A 40D SPIKE AT SIDE CENTER BASE. THE BEARING WAS MEASURED WITH A HAND COMPASS WITH A DECLINATION OF 17°E.
THE FIELD WORK WAS PERFORMED BETWEEN JUNE 23 AND JUNE 30, 2010 WITH THE ASSISTANCE OF CLYDE MULKINS AND FORREST RAMBO.