

MAP OF SURVEY

LOCATED in Section 10, T. 30 S., R. 5 W., W.M.
in Douglas County, Oregon.

June 11, 2012

FILED
Date: 6/25/2012 By: JC
This survey consists of:
Map: M163-70
Narrative: _____
Corner Rpt: _____
DOUGLAS COUNTY
SURVEYOR

SECTION CORNER
15" FIR N.61 1/4"E., 7.9'
24" FIR S.57 3/4"E., 24.4'
27" FIR S.4 3/4"W., 14.9'
22" FIR N.25 1/2"W., 43.2'
ALL WITH HEALED BLAZES.
SET 6" STEEL POST 2' SOUTH

NORTH 1/16 CORNER
20" FIR N.50"E., 35.3'
25" FIR N.45"W., 56.1'
BOTH WITH HEALED BLAZE.
SET 6" STEEL POST 2' NORTH

NW 1/16 CORNER
BOTH BLM B.T.'S ARE SNAGS.
NEW B.T.'S:
5" DIAM. MADRONE S.52"E., 12.25'
5" DIAM. PINE S.12"E., 12.6'
BOTH SCRIBED
"NW 1/16 SIO BT"

NE 1/16 CORNER
11" FIR S.58"E., 15.8'
6" MADRONE S.14 1/2"E., 16.2'
BOTH WITH HEALED BLAZE.

CTR. 1/4 CORNER
FOUND ALUM. CAP PER M 103-1
16" FIR S.62"W., 18.5'
12" FIR N.46"W., 9.9'
BOTH WITH HEALED BLAZE.

SW 1/16 CORNER
FD. REBAR AND CAP PER M 103-1
12" FIR S.45"E., 12.6'
21" FIR S.18"W., 10.9'
BOTH WITH HEALED BLAZE.
SET 6" STEEL POST 2' WEST.

BASE BEARING
(N.88°59'30"W. 1302.84')
N.88°59'30"W. 1303.10'

S.88°44'57"E. 1308.58'
(N.88°44'00"W. 1308.45')

S.88°44'03"E. 1309.32'
(S.88°44'00"E. 1309.11')

(N.0°50'35"W. 1246.17')
(N.0°50'W. 1245.42')

(N.0°50'W. 1245.42')
(N.0°44'25"W. 1253.12')

(N.0°38'W. 1297.56')
(N.0°53'20"W. 1297.46')

(S.0°43'00"E. 1247.07')
(S.0°42'08"E. 1246.95')

SURVEYED FOR: *SENECA JONES TIMBER CO.*
P.O. BOX 2129
ROSEBURG, OREGON 97470

SURVEYED BY: *DAVID EDWARDS LAND SURVEYING*
P.O. BOX 361
OAKLAND, OREGON 97462
PHONE: (541) 459-0512

REGISTERED
PROFESSIONAL
LAND SURVEYOR
David A. Edwards
OREGON
REG. NO. 229
DAVID A. EDWARDS
RENEWS 12/31/13

LEGEND

- ⊙ INDICATES COUNTY SURVEYOR OR B.L.M. BRASS CAP FOUND UNLESS NOTED OTHERWISE.
 - () DENOTES RECORD DATA PER 1991 B.L.M. SUBDIVISION OF SECTION 10.
 - INDICATES BOUNDARY BLAZED AND POSTED THIS SURVEY.
- SCALE: 1" = 400'
BASIS OF BEARINGS: 1991 B.L.M. SUBDIVISION OF SECTION 10 AS SHOWN.

NARRATIVE

THE PURPOSE OF THIS SURVEY IS TO MARK THOSE BOUNDARIES SHOWN AS BOLD LINES HEREON. THIS WAS ACCOMPLISHED BY BLAZING TREES ON EACH SIDE OF LINE, BY SETTING 6 FOOT STEEL POSTS ALONG THE LINES AT INTERVALS OF 200' OR LESS AND BY HANGING LIBERAL AMOUNTS OF RED FLAGGING ALONG THE TRUE LINES.

FIELD CREW: DAVID EDWARDS, BRANT MILLER & ERIC SPRINKLE.
EQUIPMENT: NIKON TOTAL STATION.
COMPUTATIONS AND DRAFTING: DAVID EDWARDS.



SENECA

JONES

TIMBER

R.R.C.

CO.

B.L.M.

B.L.M.

MAP FILE M163-70

MAP FILE M163-70