

# MAP OF SURVEY

LOCATED in Section 6, T. 25 S., R. 2 W., W.M.  
in Douglas County, Oregon.

July 28, 2013

FILED  
Date: 7-31-2013 By: J.C.  
This survey consists of:  
Map: M165-53  
Narrative: \_\_\_\_\_  
Corner Rpt: \_\_\_\_\_

DOUGLAS COUNTY  
SURVEYOR

SURVEYED FOR: ROSEBURG RESOURCES CO.  
P.O. BOX 1088  
ROSEBURG, OREGON 97470

SURVEYED BY: DAVID EDWARDS LAND SURVEYING  
P.O. BOX 361  
OAKLAND, OREGON 97462  
PHONE: (541) 459-0512

REGISTERED  
PROFESSIONAL  
LAND SURVEYOR

David A. Edwards  
OREGON  
JULY 26, 1988  
DAVID A. EDWARDS  
2339  
RENEWS 12/31/13

SECTION CORNER  
19" HEMLOCK W/HEALED BLAZE BEARS S.68°E., 60.1'  
27" HEMLOCK W/HEALED BLAZE BEARS N.12 1/4°W., 56.1'  
ALL OTHER B.T.'S DOWN OR STUMPS.  
NEW BEARING TREES: AN 8" FIR SCRIBED "T24S R2W S32 BT" BEARS N.72°E., 35.8'  
A 9" FIR SCRIBED "T25S R2W S6 BT" BEARS S.22°W., 32.0'  
SET A 6 FOOT STEEL POST 2' S. 15°28'W.

## LEGEND

- ⊙ INDICATES G.L.O. OR B.L.M. BRASS CAP FOUND.
- INDICATES IRON PIPE FOUND PER C.S. 51/220.
- INDICATES 5/8" X 30" STEEL REBAR WITH 2 1/2" DIAM. ALUMINUM CAP MARKED "SE 1/16 S6" AND "ROSEBURG RESOURCES CO." AND "LS 2339" AND "2013" SET.
- ( ) DENOTES B.L.M. RECORD DATA UNLESS OTHERWISE NOTED.
- INDICATES BOUNDARY BLAZED AND POSTED THIS SURVEY.

SCALE: 1" = 500'

BASIS OF BEARINGS: B.L.M. RESURVEY AS SHOWN.

## NARRATIVE

THE PURPOSE OF THIS SURVEY IS TO MARK THOSE ROSEBURG RESOURCES CO. BOUNDARIES SHOWN AS A BOLD LINE HEREON. TIES WERE MADE TO CONTROLLING CORNERS AND THE SUBDIVISION OF SECTION 6 COMPUTED AS SHOWN. I SOLICITED AN OPINION FROM THE STATE OFFICE OF THE B.L.M. WITH REGARD TO THE NORTH 1/4 CORNER. THEY INDICATED THAT THE B.L.M. WOULD LIKELY SEE THE NORTH 1/4 CORNER OF SECTION 6 AS BEING IDENTICAL TO THE ORIGINAL SOUTH 1/4 CORNER OF SECTION 31, WHICH WAS UTILIZED BY TALLETT AND WHITE AND REMONUMENTED IN 1951. THIS IS THE PROCEDURE THAT I USE IN THIS SURVEY. THE SUBJECT BOUNDARIES WERE MARKED BY BLAZING TREES ON EACH SIDE OF LINE, BY SETTING 6 FOOT STEEL POSTS ALONG THE LINE AT INTERVALS OF 200 FEET OR LESS AND BY HANGING LIBERAL AMOUNTS OF RED FLAGGING ALONG THE TRUE LINE. BEARING TREES ARE SCRIBED ACCORDING TO THE 2009 B.L.M. MANUAL, OR AS NOTED, AND ARE MEASURED TO CENTER OF TREE AT ROOT CROWN.

AT THE SE 1/16 CORNER OF SECTION 6: A 3" DIAM. FIR BEARS S.57°E., 10.65 FEET.  
A 5" DIAM. FIR BEARS N.22°W., 2.55 FEET.

AT THE SOUTH 1/16 CORNER TO SECTIONS 5 AND 6:  
A 24" DIAM. HEMLOCK WITH HEALED BLAZE BEARS S.41°E., 33.3 FEET  
25" DIAM. HEMLOCK STUMP BEARS N.56 3/4°W., 50.0 FEET.  
NEW B.T.: AN 8" DIAM. CHINQUAPIN BEARS N.48°W., 36.0 FEET.  
A 6 FOOT STEEL POST IS SET 2 FEET NORTH.

AT THE EAST 1/16 CORNER TO SECTIONS 6 AND 7:  
A 15" DIAM. CHINQUAPIN WITH HEALED BLAZE BEARS N.55°W., 18.5 FEET.  
NEW B.T.: A 5" DIAM. HEMLOCK BEARS S.18°W., 8.77 FEET.  
A 6 FOOT STEEL POST IS SET 2 FEET NORTH.

AT THE 1/4 CORNER TO SECTIONS 5 AND 6:  
A 42" DIAM. CEDAR WITH ROTTED BLAZE BEARS N.79 1/2°E., 27.1 FEET.  
A 33" DIAM. CEDAR WITH HEALED BLAZE BEARS N.50 3/4°W., 24.4 FEET.

AT THE 1/4 CORNER TO SECTIONS 31 AND 6:  
A 50" DIAM. FIR STUMP BEARS N.54 1/2°W., 54.1 FEET.  
NEW B.T.'S: A 15" DIAM. HEMLOCK BEARS S.85°E., 13.1 FEET.  
A 7" DIAM. HEMLOCK BEARS N.64°W., 20.8 FEET.  
A 10" DIAM. HEMLOCK BEARS N.12°W., 20.1 FEET.  
A 6 FOOT STEEL POST IS SET 2 FEET EAST.

FIELD CREW: BRANT MILLER AND ERIC SPRINKLE.

EQUIPMENT: NIKON TOTAL STATION.

COMPUTATIONS AND DRAFTING: DAVID EDWARDS.

