

MAP OF SURVEY  
LOCATED IN THE SOUTHWEST 1/4, SECTION 36,  
TOWNSHIP 32 SOUTH, RANGE 9 WEST,  
WILLAMETTE MERIDIAN  
DOUGLAS COUNTY, OREGON

FILED  
Date: 12-7-2015 By: JC  
This survey consists of:  
Map: M170-22  
Narrative:  
Corner Rpt:

DOUGLAS COUNTY  
SURVEYOR

SURVEY FOR AND BY:  
OREGON DEPARTMENT OF FORESTRY  
2600 STATE STREET,  
SALEM, OR 97310

DATE SURVEY COMMENCED: OCTOBER 5, 2015  
DATE SURVEY COMPLETED: OCTOBER 23, 2015  
SURVEY COMPLETED BY DAREN CONE AND CHRIS RUDD

NARRATIVE  
THIS SURVEY WAS PERFORMED TO ESTABLISH THE WEST BOUNDARY OF OREGON DEPARTMENT OF FORESTRY LANDS LOCATED IN THE SOUTHWEST 1/4 OF SECTION 36, TOWNSHIP 32 SOUTH, RANGE 9 WEST, WILLAMETTE MERIDIAN. THE STANDARD CORNER FOR SECTIONS 35 & 36 WAS ORIGINALLY ESTABLISHED BY RICHMOND DICKERSON IN 1883 UNDER GLO CONTRACT TO SURVEY THE 7TH STANDARD PARALLEL. FRED MENSCH COMPLETED A RESURVEY OF PORTIONS OF THE 7TH STANDARD PARALLEL AND COMPLETED THE SUBDIVISION OF TOWNSHIP 32 SOUTH, RANGE 9 WEST UNDER GLO CONTRACT IN 1917. MENSCH RELOCATED THE STANDARD CORNER FOR SECTIONS 35 AND 36 AND ESTABLISHED AN ANGLE POINT AT THE LOCATION ESTABLISHED BY DICKERSON. THIS SURVEY TIED TO THE 1917 STANDARD CORNER AND 1/4 CORNERS BETWEEN SECTIONS 35 AND 36 AND THE ANGLE POINT ON THE 7TH STANDARD PARALLEL BETWEEN SECTIONS 36 AND SECTION 1.  
USING A NIKON NPL352 TOTAL STATION, A DOUBLE ANGLE TRAVERSE WAS COMPLETED TYING TO THE MONUMENTS AS NOTED. TRUE LINE WAS POSTED WITH PINK AND BLUE RIBBON AND RED PAINTED BLAZES. 1/2" X 5' LONG WHITE FIBERGLASS RODS WERE SET ON LINE AT 100' TO 300' INTERVALS. I ALSO SET TWO METAL 'T' FENCE POSTS ON LINE ON EACH SIDE OF A RIDGE TOP ROAD AS NOTED.

LEGEND

- FOUND MONUMENTS AS NOTED
- RESTORED MONUMENTS AS NOTED
- ⦿ SET METAL 'T' FENCE POST AS NOTED
- (...) 1917 GLO RECORD BEARING AND DISTANCE
- BC BRASS CAP
- GIP GALVANIZED IRON PIPE
- OD OUTSIDE DIAMETER
- YMLP YELLOW METAL LOCATION POSTER
- DBH DIAMETER AT BREST HEIGHT
- GLO GOVERNMENT LAND OFFICE
- DCSD DOUGLAS COUNTY SURVEYOR OFFICE

SET 5' METAL 'T' FENCE POST  
SET ON LINE  
19.2 FEET NORTH OF RIDGE  
TOP ROAD CENTERLINE,  
COURSE N70°E, AND 571.5'  
SOUTH OF 1/4 CORNER.  
SCRIBED 'PLS 43362' IN  
FLANGE.

SET 5' METAL 'T' FENCE POST  
SET ON LINE  
19.1 FEET SOUTH OF RIDGE  
TOP ROAD CENTERLINE,  
COURSE N70°E, AND 2031.05'  
NORTH OF STANDARD CORNER.  
SCRIBED 'PLS 43362' IN  
FLANGE.

1/4 CORNER SECTIONS 35 & 36  
FOUND 1" OD GIP WITH 2 1/2" BC  
PER 1917 GLO SURVEY. PIPE HAS  
RUSTED OFF AT GROUND LEVEL.  
FOUND BC WITH 14" OF PIPE ATTACHED  
LAYING ON GROUND NEXT TO REMAINING GIP.  
SET A 2" OD X 36" LONG ALUMINUM PIPE OVER  
THE REMAINING GIP, FIRMLY SET WITH 10"  
ABOVE GROUND, WITH 4" ALUMINUM CAP MARKED.

STATE OF OREGON DEPARTMENT OF FORESTRY  
1/4  
S351S36  
10/23/15  
PLS43362

BEARING TREES PER GLO 1917 SURVEY:  
24" DIAMETER FIR BEARS S33°E, 10.6',  
NOW 28" DBH SNAG, SCRIBE HEALED OVER,  
EXISTING YMLP  
50" DIAMETER SUGAR PINE BEARS N21°W, 31.7',  
NOW 55" DIAMETER X 2'TALL STUMP,  
WITH NO DISCERNABLE SCRIBING. EXISTING YMLP  
BEARING TREE ESTABLISHED BY DCSD 1967 RESTORATION:  
18" DIAMETER DOUGLAS-FIR BEARS N58°E, 31.0',  
NOW MISSING (IN OLD CAT FIRE LINE)  
NEW CORNER ACCESSORIES:  
6.7" DBH DOUGLAS-FIR BEARS N8 1/2°E, 10.6',  
SCRIBED 'S36 1/4 BT', NEW YMLP  
10.8" DBH DOUGLAS-FIR BEARS N57 1/2°W, 50.1'  
SCRIBED 'S35 1/4 BT', NEW YMLP  
1/2" DIAMETER X 5' WHITE FIBERGLASS ROD BEARS 1' NORTH  
PLACED 1917 GLO BC AND GIP ALONGSIDE NEW MONUMENT.

NORTH 2640.89'  
(NORTH 2640') BASIS OF BEARINGS

STANDARD CORNER SECTION 35 AND 36  
FOUND 2" OD GIP WITH 2 1/2" BC PER  
1917 GLO RESURVEY. PROTRUDES 14" OUT OF GROUND.  
BEARING TREES PER 1917 GLO RESURVEY  
36" DIAMETER FIR BEARS N14°E, 7.9',  
NOW 32.7" DBH, SCRIBE HEALED OVER, DCSD YMLP  
(ASSUME DIAMETER WAS INCORRECTLY RECORDED IN 1917  
RESURVEY AS BEARING, DISTANCE AND SCRIBE WOUND  
MATCHES)  
26" DIAMETER FIR BEARS N7°W, 40.3'  
NOW 27" DBH, SCRIBE HEALED OVER  
A CREEK 2' WIDE, COURSE SOUTH EAST BEARS NORTH 31' AND  
SOUTH 12'.  
NEW CORNER ACCESSORY:  
1/2" X 5' WHITE FIBERGLASS ROD BEARS NORTH 1'



0 100 200 400 FEET

SCALE: 1" = 200 FEET

REGISTERED  
PROFESSIONAL  
LAND SURVEYOR

*Daren L. Cone*

OREGON  
JUNE 8, 2009  
DAREN L. CONE  
43362PLS  
RENEWS: DEC.31, 2015

SECTION 35  
JOSEPHINE COUNTY

SECTION 36  
DOUGLAS COUNTY

T. 32 S

T. 33 S

SECTION 1 JOSEPHINE COUNTY

S89°40'25"E, 125.82'  
(WEST 1.91 CH = 126.06')

ANGLE POINT ON TOWNSHIP LINE  
FOUND 1" OD GIP WITH 2 1/2" BC  
PER 1917 GLO RESURVEY, PROTRUDES 6" OUT OF GROUND,  
BEARING TREES PER 1917 GLO RESURVEY:  
16" DIAMETER LAUREL BEARS N26°E, 11.22',  
NOW A ROOT HOLE, EXISTING YMLP FOUND ON 6" MADRONE  
STEM ON GROUND NEARBY.  
40" DIAMETER FIR BEARS N49°W, 25.74',  
NOW 50" DBH, SCRIBE HEALED OVER.