

**204-FOUND MONUMENT**

CORNER R-17, (GCDB 500300)  
CORNER OF SECTIONS 22, 23, 26 & 27 T. 28 S., R. 08 W., W.M.

APRIL 12, 1855  
GLO SURVEY BY DENNIS HATHORN, DEPUTY SURVEYOR  
UNDER CONTRACT NO. 57  
(DCSO RECORDS VOL. 14, PAGE 5802)  
SET POST COR. SECS. 22, 23, 26, AND 27, FROM WHICH:  
A FIR 18" DIA., BEARS N 78° E, 29 LKS. DIST.  
A FIR 15" DIA., BEARS S 72° E, 49 LKS. DIST.  
A FIR 6" DIA., BEARS N 70° W, 38 LKS. DIST.  
A FIR 24" DIA., BEARS S 5° W, 62 LKS. DIST.

JULY - AUGUST 1957  
DOUGLAS CO. SURVEYORS OFFICE  
JAMES BYRON, DEPUTY - MILO GODFREY; J. FEE, CREW  
(C.S. FILE 49/5-28)  
FOUND - ORIG. 24" FIR, NOW 4" FIR, SHOWS GOOD BARK SCRIBE  
"T28S R8W S22 S 5° W, 40.9'  
ALL OTHER ORIGINAL BTS DOWN.  
SET BRASS CAP AT COR. MKD:  
COUNTY SURVEYORS OFFICE  
T28S R8W S22 S23 S26 S27 1957

NEW BTS:  
8" R.FIR S 55° W, 37.0'. SCRIBED T28S R8W S27 CS BT  
10" R.FIR N 89° W, 46.0'. SCRIBED T28S R8W S22 CS BT  
10" CEDAR N 21° E, 17.5'. SCRIBED S23 CS BT  
16" MAPLE S 36° E, 58.8'. SCRIBED T28S S26 CS BT

JUNE 1969 - APRIL 1973  
BLM RESURVEY BY LYNN ROSEBERRY; DANIEL BERRY; GORDON POPKEN AND ALBERT GARRISON, CADASTRAL SURVEYORS  
UNDER GROUP NO. 691 AND 764  
(DCSO RECORDS VOL. 36, PAGE 15075)  
FOR THE CORNER OF SECTIONS 22, 23, 26, & 27, PERPETUATED BY JAMES W. BYRON, DEPUTY COUNTY SURVEYOR IN 1957, MONUMENTED WITH AN IRON POST, 1-1/2" DIA., FIRMLY SET, PROTRUDING 10" ABOVE GROUND, WITH BRASS CAP MKD: COUNTY SURVEYORS OFFICE T28S R8W S22 23 26 27 1957  
FROM WHICH THE REMAINS OF THE ORIGINAL BEARING TREES:  
A ROOT HOLE, BEARS N 78° E, 29 LKS. DIST.  
A ROOT HOLE, BEARS S 72° E, 49 LKS. DIST.  
A ROOT HOLE, BEARS S 05° W, 62 LKS. DIST.  
AND BEARING TREES MARKED BY BYRON:  
A CEDAR 20" DIA., BEARS N 18° E, 26 LKS. DIST. WITH HEALED BLAZE  
A MAPLE 19" DIA., BEARS S 36° E, 90 LKS. DIST. WITH HEALED BLAZE  
A FIR 18" DIA., BEARS S 55° W, 55 LKS. DIST. WITH HEALED BLAZE  
A FIR 18" DIA., BEARS N 89-1/2° W, 69 LKS. DIST. WITH HEALED BLAZE

JANUARY 1973  
GLENN BAUGHMAN  
(MAP FILE M70-6)  
FOUND BRASS CAP COUNTY SURVEYORS OFFICE 1957

MAY - JULY 1975  
BLM RESURVEY BY JAMES E. JELLEY, CADASTRAL SURVEYOR  
UNDER GROUP NO. 863  
(DCSO RECORDS VOL. 38, PAGES 15567-68)  
THE CORNER OF SECTIONS 22, 23, 26 & 27, PERPETUATED AND RECORDED BY JAMES W. BYRON, DEPUTY COUNTY SURVEYOR, IN 1957, MONUMENTED WITH AN IRON POST, 1-1/2" DIA., FIRMLY SET, PROJECTING 10" ABOVE GROUND, WITH BRASS CAP MKD:  
COUNTY SURVEYORS OFFICE  
T28S R8W S22 S23 S26 S27 1957  
FROM WHICH THE ORIGINAL BEARING TREES:  
A ROOTHOLE, BEARS N 78° E, 29 LKS. DIST.  
A ROOTHOLE, BEARS S 72° E, 49 LKS. DIST.  
A ROOTHOLE, BEARS S 5° W, 62 LKS. DIST.  
AND BEARING TREES MKD. BY BYRON:  
A CEDAR, 22" DIA., BEARS N 18° E, 26 LKS. DIST., WITH HEALED BLAZE  
A MAPLE, 19" DIA., BEARS S 36° E, 90 LKS. DIST., WITH HEALED BLAZE  
A FIR, 18" DIA., BEARS S 55° W, 55 LKS. DIST., WITH HEALED BLAZE  
A FIR, 18" DIA., BEARS N 89-1/2° W, 69 LKS. DIST., WITH HEALED BLAZE

OCTOBER 1980 - MAY 1984  
BLM RESURVEY BY JAMES E. JELLEY AND WAYNE L. ROGERS, CADASTRAL SURVEYORS  
UNDER GROUP NO. 1028  
(DCSO RECORDS VOL. 45, PAGE 17389)  
THE CORNER OF SECTIONS 22, 23, 26 & 27, MONUMENTED WITH AN IRON POST, 1-1/4" DIA., FIRMLY SET, PROJECTING 14" ABOVE GROUND, WITH BRASS CAP MKD: COUNTY SURVEYORS OFFICE T28S R8W S22 S23 S26 S27 1957  
FROM WHICH THE BEARING TREES MKD. BY JAMES W. BYRON, DEPUTY COUNTY SURVEYOR, IN 1957:  
A CEDAR, 25" DIA., BEARS N 18° E, 26 LKS. DIST., WITH HEALED BLAZE  
A MAPLE, 23" DIA., BEARS S 36° E, 90 LKS. DIST., WITH HEALED BLAZE  
A FIR, 21" DIA., BEARS S 55° W, 55 LKS. DIST., WITH HEALED BLAZE  
A FIR, 21" DIA., BEARS N 89-1/2° W, 69 LKS. DIST., WITH HEALED BLAZE

MAY 15, 2023  
DANIEL E. SAILY  
(MAP FILE M182-25)  
SECTION CORNER FOR SECTIONS 22, 23, 26, & 27 (PLSS 500300)  
FOUND 1957 DCSO BRASS CAP AND IRON PIPE. THE TOP OF THE CAP IS 1.2' ABOVE GROUND ON STEEP EAST FACING SLOPE. SET A GALVANIZED STEEL POST 1' NORTH FROM WHICH:  
A 34" CEDAR BEARS N 18-1/4° E, 17.9' (RECORD N 18° E, 26 LKS.) WITH WELL HEALED FACE AND BLM TAG  
A 36" DOUGLAS FIR BEARS S 89-1/2° W, 45.4' (RECORD N 89-1/2°, 69 LKS) WITH WELL HEALED FACE AND BLM TAG  
A 33" DOUGLAS FIR BEARS S 54-1/4° W, 36.4' (RECORD S 55° W, 55 LKS.) WITH WELL HEALED FACE AND BLM TAG  
NEW 35" DOUGLAS FIR BEARS S 31-1/2° E, 16.9' MKD: T28S R8W S26 BT W/ TAG

JUNE 13, 2023  
GARRETT FINCH AND CREW WITH MINISTER AND GLAESER SURVEYING  
FOUND 2-1/2" COUNTY SURVEYORS OFFICE BRASS CAP, 1.4' ABOVE GROUND FROM WHICH:  
A FIR 36" DIA., BEARS S 31-1/2° E, 17.1' MKD: T28S R8W S26 BT (2023)  
A CEDAR 36" DIA., BEARS N 21° E, 17.8' WITH HEALED BLAZE AND BT SIGNS (1957)  
A FIR 39" DIA., BEARS N 78° W, 46.0' WITH HEALED BLAZE AND BT SIGNS (1957)  
A FIR 34" DIA., BEARS S 70° W, 37.3' WITH HEALED BLAZE AND BT SIGN (1957)  
A MAPLE (DEAD) 22" DIA., BEARS S 30° E, 59.8' WITH HEALED BLAZE (1957)  
(SET CHAINING NAIL AT SIDE CENTER, BT SIGNS ON FRONT AND BACK, AND PAINTED RED BAND FOR EXISTING BT'S)

**205-FOUND MONUMENT**

CORNER Q-17, (GCDB 500320)  
S 1/16 CORNER OF SECTIONS 22 & 23 T. 28 S., R. 08 W., W.M.

MAY - JULY 1975  
BLM RESURVEY BY JAMES E. JELLEY, CADASTRAL SURVEYOR  
UNDER GROUP NO. 863  
(DCSO RECORDS VOLUME 38, PAGE 15568)  
SET AN IRON POST, 28" LONG, 2-1/2" DIA., 24" IN THE GROUND, WITH BRASS CAP MKD: S 1/16 S22 S23 1975  
FROM WHICH:  
A FIR, 9" DIA., BEARS N 77° E, 20 LKS. DIST., MKD. S 1/16 S23 BT  
A FIR, 7" DIA., BEARS N 41-1/2° W, 25-1/2 LKS. DIST. MKD. S 1/16 S22 BT

**205 CONT.**

OCTOBER 1980 - MAY 1984  
BLM RESURVEY BY JAMES E. JELLEY AND WAYNE L. ROGERS, CADASTRAL SURVEYORS  
UNDER GROUP NO. 1028  
(DCSO RECORDS VOLUME 45, PAGE 17390)  
THE S 1/16 SECTION CORNER OF SECTIONS 22 & 23, MONUMENTED WITH AN IRON POST, 2-1/2" DIA., FIRMLY SET, PROJECTING 5" ABOVE GROUND, WITH BRASS CAP MKD: S 1/16 S22 S23 1975  
FROM WHICH BEARING TREES MKD. BY JELLEY:  
A FIR, 13" DIA., BEARS N 77° E, 20 LKS. DIST., WITH HEALED BLAZE  
A FIR, 10" DIA., BEARS N 41-1/2° W, 25-1/2 LKS. DIST., WITH HEALED BLAZE

JULY - OCTOBER 1985  
BLM RESURVEY BY DALE T. BEDELL, CADASTRAL SURVEYOR  
UNDER GROUP NO. 1278  
(DCSO RECORDS VOLUME 48, PAGE 18262)  
THE S 1/16 CORNER OF SECTIONS 22 & 23, MONUMENTED WITH AN IRON POST, 2-1/2" DIA., FIRMLY SET, PROJECTING 6" ABOVE GROUND, WITH BRASS CAP MKD: S 1/16 S22 S23 1975  
FROM WHICH:  
A FIR, 15" DIA., BEARS N 77° E, 20 LKS. DIST., WITH HEALED BLAZE  
A FIR, 12" DIA., BEARS N 41-1/2° W, 25-1/2 LKS. DIST., WITH HEALED BLAZE

JUNE 16, 2023  
GARRETT FINCH AND CREW WITH MINISTER AND GLAESER SURVEYING  
FOUND 3-1/4" BLM BRASS CAP, 0.6' ABOVE GROUND FROM WHICH:  
A FIR 29" DIA., BEARS N 77° E, 13.1' WITH HEALED BLAZE AND BT SIGN (1975)  
A FIR 30" DIA., BEARS N 41-1/2° W, 17.1' WITH HEALED BLAZE (1975)  
(SET CHAINING NAIL AT SIDE CENTER, BT SIGNS ON FRONT AND BACK, AND PAINTED RED BAND FOR EXISTING BT'S)

**206-FOUND MONUMENT**

CORNER R-17, (GCDB 500340)  
1/4 CORNER OF SECTIONS 22 & 23 T. 28 S., R. 08 W., W.M.

APRIL 12, 1855  
GLO SURVEY BY DENNIS HATHORN, DEPUTY SURVEYOR  
UNDER CONTRACT NO. 57  
(DCSO RECORDS VOL. 14, PAGE 5803)  
MARKED A FIR 12" DIA. FOR 1/4 SEC. COR., FROM WHICH  
A FIR 12" DIA., BEARS N 70° E, 30 LKS. DIST.  
A FIR 12" DIA., BEARS N 35° W, 40 LKS. DIST.

MAY - JULY 1975  
BLM RESURVEY BY JAMES E. JELLEY, CADASTRAL SURVEYOR  
UNDER CONTRACT NO. 863  
(DCSO RECORDS VOL. 38, PAGES 15568-69)  
POINT FOR THE 1/4 SEC. COR., AT PROPORTIONATE DISTANCE; THERE IS NO REMAINING EVIDENCE OF THE ORIGINAL CORNER.  
SET AN IRON POST, 28" LONG, 2-1/2" DIA., 24" IN THE GROUND, WITH THE BRASS CAP MKD:  
1/4 S22 S23 T28S R8W 1975  
FROM WHICH:  
A FIR 6" DIA., BEARS N 50-1/2° E, 12 LKS. DIST. MKD. 1/4 S23 BT  
A W.FIR 6" DIA., BEARS N 79° W, 20 LKS. DIST. MKD. 1/4 S22 BT

OCTOBER 1980 - MAY 1984  
BLM RESURVEY BY JAMES E. JELLEY AND WAYNE L. ROGERS, CADASTRAL SURVEYORS  
UNDER GROUP NO. 1028  
(DCSO RECORDS VOL. 45, PAGE 17390)  
THE 1/4 CORNER OF SECTIONS 22 & 23, MONUMENTED WITH AN IRON POST, 2-1/2" DIA., FIRMLY SET, PROJECTING 4" ABOVE GROUND, WITH BRASS CAP MKD: T28S R8W 1/4 S22 S23 1975  
FROM WHICH BEARING TREES MKD. BY JELLEY:  
A FIR, 8" DIA., BEARS N 50-1/2° E, 12 LKS. DIST., WITH HEALED BLAZE  
A GRAND FIR, 8" DIA., BEARS N 79° W, 20 LKS. DIST., WITH HEALED BLAZE

JULY - OCTOBER 1985  
BLM RESURVEY BY DALE T. BEDELL, CADASTRAL SURVEYOR  
UNDER GROUP NO. 1278  
(DCSO RECORDS VOL. 48, PAGE 18262)  
THE 1/4 SECTION CORNER OF SECTION 22 & 23, MONUMENTED WITH AN IRON POST, 2-1/2" DIA., FIRMLY SET, PROTRUDING 4" ABOVE GROUND, WITH BRASS CAP MKD: T28S R8W 1/4 S22 S23 1975  
FROM WHICH THE BEARING TREES MKD. BY JELLEY:  
A FIR, 10" DIA., BEARS N 50-1/2° E, 12 LKS. DIST., WITH HEALED BLAZE  
A FIR, 9" DIA., BEARS N 79° W, 20 LKS. DIST., WITH HEALED BLAZE

JULY 2001  
MARK SMALLLEY - FOR: ROSEBURG RESOURCES  
(MAP FILE M138-50)  
FOUND:  
1975 BLM BRASS CAP ON IRON PIPE  
11" (6") FIR N 50-1/2° E, 7.9' HEALED  
11" (6") FIR N 79° W, 13.2' HEALED  
SCRIBED:  
11" FIR N 53° W, 24.5' "1/4 S BT"  
11" FIR S 87° E, 18.1' "1/4 S BT"

JUNE 13, 2023  
GARRETT FINCH AND CREW WITH MINISTER AND GLAESER SURVEYING  
FOUND 3-1/4" BLM BRASS CAP, 0.6' ABOVE GROUND FROM WHICH:  
A FIR 14" DIA., BEARS N 79° W, 13.1' WITH 2 HEALED BLAZES AND BT SIGN (1975)  
A FIR 16" DIA., BEARS N 53° W, 24.5' WITH HEALED BLAZE AND BT SIGN (2001)  
A FIR 16" DIA., BEARS N 50-1/2° E, 8.0' WITH HEALED BLAZE AND BT SIGN (1975)  
A FIR 14" DIA., BEARS S 87° E, 18.1' WITH HEALED BLAZE AND BT SIGN (2001)  
(SET CHAINING NAIL AT SIDE CENTER, BT SIGNS ON FRONT AND BACK, AND PAINTED RED BAND FOR EXISTING BT'S)

**207-FOUND MONUMENT**

CORNER N-13, (GCDB 400400)  
CORNER OF SECTIONS 15, 16, 21 & 22 T. 28 S., R. 08 W., W.M.

APRIL 12, 1855  
GLO SURVEY BY DENNIS HATHORN, DEPUTY SURVEYOR  
UNDER CONTRACT NO. 57  
(DCSO RECORDS VOL. 14, PAGE 5809)  
SET POST, COR. SEC. 15, 16, 21 AND 22 FROM WHICH:  
A FIR 9" DIA., BEARS S 45° W, 54 LKS. DIST.  
A FIR 12" DIA., BEARS N 70° W, 37 LKS. DIST.  
A FIR 10" DIA., BEARS N 20° E, 89 LKS. DIST. (ERROR ON DCSO COR. RENEWAL)  
A FIR 30" DIA., BEARS S 62° E, 50 LKS. DIST.

1875  
GLO SURVEY BY WINFIELD S. CHAPMAN  
FOUND POST, WITNESS TREES STANDING

**207 CONT.**

JULY - AUGUST 1957  
DOUGLAS CO. SURVEYORS OFFICE  
JAMES BYRON, DEPUTY - MILO GODFREY; J. FEE, CREW  
(C.S. FILE 49/5-1)  
FOUND:

ORIG. SE. BT, NOW 36" SNAG. THIS TREE WAS BARK SCRIBED. BARK WITH SCRIBING "R8" LAYING ON GROUND AT BASE OF TREE.  
FOUND EVIDENCE OF FIR TREE AT RECORD DIST. & BRG. FOR SW. ORIGINAL BT.  
FOUND NO EVIDENCE OF NE. ORIG. BT., NOR SW. ORIG. BT.  
(WHICH WOULD FALL IN CAT ROAD)  
SET BRASS CAP AT COR. MKD:  
COUNTRY SURVEYORS OFFICE  
T28S R8W S16 S15 S21 S22 1957  
FROM WHICH:  
14" W.FIR BEARS N 82° W, 46.7'. SCRIBED T28S R8W S16 CS BT  
30" R.FIR BEARS S 47° W, 39.0'. SCRIBED S21 T28S R8W CS BT  
15" W.FIR BEARS N 86° W, 42.0'. SCRIBED S16 T28S R8W CS BT, DAMAGED SEVERELY  
10" R.FIR BEARS N 73° E, 60.0'. SCRIBED S15 T28S R8W CS BT  
26" HEMLOCK BEARS S 2-1/2° E, 39.5'. SCRIBED S22 T28S R8W CS BT

JUNE 1969 - APRIL 1973  
BLM RESURVEY BY LYNN ROSEBERRY; DANIEL BERRY; GORDON POPKEN AND ALBERT GARRISON, CADASTRAL SURVEYORS  
UNDER GROUP NO. 691 AND 764  
(DCSO RECORDS VOL. 36 PAGES 15077-78)  
THE SEC. COR., PERPETUATED AND RECORDED BY BYRON IN 1957, MONUMENTED WITH AN IRON POST 1-1/2" DIA., FIRMLY SET, PROTRUDING 8" ABOVE GROUND WITH BRASS CAP MKD. IN 1957 FROM WHICH THE REMAINS OF THE ORIGINAL BEARING TREE:  
A ROOT HOLE BEARS S 62° E, 50 LKS. DIST. WITH A DOWN AND DECAYED FIR ALONGSIDE, NO MARKS VISIBLE  
AND BEARING TREES MKD. BY BYRON:  
A FIR 17" DIA., BEARS N 73° E, 87-1/2 LKS. DIST., WITH HEALED DOUBLE BLAZE  
A HEMLOCK 26" DIA., BEARS S 2-1/2° E, 60 LKS. DIST. WITH HEALED DOUBLE BLAZE  
A FIR 30" DIA., BEARS S 45° W, 62 LKS. DIST. WITH HEALED BLAZE  
A SAWED WHITE FIR STUMP 15" DIA., BEARS N 86° W, 64 LKS. DIST., NO MARKS VISIBLE  
A FIR SNAG 14" DIA., BEARS N 83-1/2° W, 71 LKS. DIST., WITH HEALED DOUBLE BLAZE  
AND A BEARING TREE MKD. BY ROSEBERRY IN 1969:  
A FIR 20" DIA., BEARS N 57° W, 141 LKS. DIST., WITH SCRIBE MARKS:  
T28S R8W S16 BT VISIBLE ON PARTIALLY HEALED BLAZE

AUGUST 1972  
BRUCE SHANER WITH SHANER ENGINEERING  
(MAP FILE M42-66)  
FOUND BRASS CAP MKD. COUNTY SURVEYORS OFFICE T28S R8W 16, 15, 21, 22 1957  
FROM WHICH:  
A W.FIR 14" DIA. SNAG, BEARS N 82° W, 46.7' (REC. N 86° W, 42.0')  
A W.FIR 22" DIA., BEARS N 56° W, 94.4' W/ SCRIBING  
A D.FIR 20" DIA., BEARS N 73° E, 58.5' (REC. 60.0')  
A HEMLOCK 26" DIA., BEARS S 2-1/2° E, 39.5'  
A D.FIR 30" DIA., BEARS S 47° W, 40.5' (REC. 39.0')

MAY - JULY 1975  
COR. FD. AND USED IN BLM RESURVEY BY JAMES E. JELLEY, CADASTRAL SURVEYOR  
UNDER GROUP NO. 863  
(DCSO RECORDS VOL. 38 PAGES 15563-84)  
MAY - AUGUST 1987  
BLM RESURVEY BY BOYD W. PETERSON  
UNDER GROUP NO. 1364  
(DCSO RECORDS VOL. 48 PAGE 18404)  
THE SEC. COR., MONUMENTED WITH AN IRON POST 1-1/4" DIA., FIRMLY SET, PROJECTING 6" ABOVE GROUND WITH BRASS CAP MKD. IN 1957 FROM WHICH THE REMAINS OF BEARING TREES MKD. BY BYRON IN 1957:  
A FIR 25" DIA., BEARS N 73° E, 87-1/2 LKS. DIST., WITH HEALED DOUBLE BLAZE  
A HEMLOCK SNAG 26" DIA., BEARS S 3-3/4° E, 60 LKS. DIST., WITH FRAGMENTARY SCRIBING VISIBLE ON PARTIALLY HEALED BLAZE  
A SAWED FIR STUMP 30" DIA., BEARS S 45° W, 62 LKS. DIST., NO MARKS VISIBLE AND NEW BEARING TREES:  
A FIR 6" DIA., BEARS S 52° E, 15 LKS. DIST., MKD. T28S R8W S22 BT  
A FIR 4" DIA., BEARS S 57° W, 20-1/2 LKS. DIST., MKD. X BT  
A FIR 5" DIA., BEARS N 69-1/2° W, 30 LKS. DIST., MKD. T28S R8W S16 BT

JULY 1993  
MARK HEIMBURGER WITH AA SURVEYING SERVICE, INC.  
(MAP FILE M117-37)  
FOUND DCSO BRASS CAP 1957

SEPTEMBER - OCTOBER 2009  
BLM RETRACEMENT BY KENNETH W. SAVELAND, CADASTRAL SURVEYOR  
UNDER GROUP NO. 2300  
(DCSO RECORDS VOL. 56 PAGES 22272-3)  
THE COR. OF SECS. 15, 16, 21, AND 22, ESTABLISHED BY HATHORN IN 1856, PERPETUATED FROM ORIGINAL EVIDENCE NO LONGER EXISTENCE BY JAMES W. BYRON, DEPUTY COUNTY SURVEYOR IN 1957, FILED IN DOUGLAS COUNTY SURVEYOR'S OFFICE, C.S. FILE NO. 49/5, MONUMENTED WITH AN IRON POST, 1-1/4" DIA., FIRMLY SET, PROJECTING 7" ABOVE GROUND, WITH BRASS CAP (PROPERLY) MKD.  
FROM WHICH THE REMAINS OF BTS MKD. BY BYRON, REPORTED BY PETERSON:  
A FIR 32" DIA., BEARS N 73° E, 57.8', WITH A HEALED BLAZE  
A ROOTHOLE BEARS S 3-3/4° E, 39.6', DOWNHILL OF WHICH IS A HEMLOCK SNAG, SIZE INDETERMINATE, WITH NO MARKS VISIBLE ON A HOLLOWED BLAZE  
A SAWED FIR STUMP, 28" DIA., BEARS S 45° W, 40.9', WITH NO MARKS VISIBLE AND A METAL COVER  
AND REMAINING BTS MKD. BY PETERSON:  
A FIR, 10" DIA., BEARS S 57° W, 13.5', WITH A HEALED DOUBLE BLAZE  
A FIR, 13" DIA., BEARS N 69-1/2° W, 19.8', WITH A HEALED BLAZE  
AND A NEW BEARING TREE  
A FIR, 10 INS. DIAM., BEARS S 7-1/2° E, 19.7', MKD. T28S R8W S22 BT

JUNE 16, 2023  
GARRETT FINCH AND CREW WITH MINISTER AND GLAESER SURVEYING  
FOUND 2-1/2" COUNTY SURVEYORS OFFICE BRASS CAP, 0.5' ABOVE GROUND FROM WHICH:  
A FIR 17" DIA., BEARS N 71° W, 19.7' WITH HEALED BLAZE AND BT SIGN (1987)  
A FIR 14" DIA., BEARS S 57° W, 13.7' WITH 2 HEALED BLAZES AND BT SIGN (1987)  
A STUMP 27" DIA., BEARS S 45° W, 40.6' WITH TIN TOP AND BT SIGN (1957)  
A FIR 13" DIA., BEARS S 7-1/2° E, 19.7' WITH HEALED BLAZE AND BT SIGN (2009)  
A FIR 36" DIA., BEARS N 73° E, 56.7' WITH HEALED BLAZE AND BT SIGN (1957)  
A ROTTED STUMP 18" DIA., BEARS S 2-1/2° E, 39.3' (1957)  
(SET CHAINING NAIL AT SIDE CENTER, BT SIGNS ON FRONT AND BACK, AND PAINTED RED BAND FOR EXISTING BT'S)

JUNE 14, 2023  
GARRETT FINCH AND CREW WITH MINISTER AND GLAESER SURVEYING  
FOUND 3-1/4" BLM BRASS CAP, 0.4' ABOVE GROUND FROM WHICH:  
A FIR 18" DIA., BEARS N 44-1/2° W, 15.0' WITH HEALED BLAZE (1987)  
A ROTTED STUMP 16" DIA., BEARS N 79-1/2° E, 31.7' (1987)  
(SET CHAINING NAIL AT SIDE CENTER, BT SIGNS ON FRONT AND BACK, AND PAINTED RED BAND FOR EXISTING BT'S)

MAY - AUGUST 1987  
BLM RESURVEY BY BOYD W. PETERSON  
UNDER GROUP NO. 1364  
(DCSO RECORDS VOLUME 48, PAGE 18413)  
POINT FOR CENTER W 1/16 SECTION CORNER OF SECTION 15, SET A STAINLESS STEEL POST, 28" LONG, 2-1/2" DIA., 26" IN THE GROUND, WITH BRASS CAP MKD: C W 1/16 C S15 1987  
FROM WHICH:  
A FIR 5" DIA., BEARS N 79-1/2° E, 48 LKS. DIST., MKD: X BT  
A FIR 10" DIA., BEARS N 44-1/4° W, 22 LKS. DIST., MKD: CW 1/16 S15 BT  
DEPOSIT WHITE "DEEP-1" MAGNETIC MARKER AT BASE OF STAINLESS STEEL POST

JUNE 14, 2023  
GARRETT FINCH AND CREW WITH MINISTER AND GLAESER SURVEYING  
FOUND 3-1/4" BLM BRASS CAP, 0.4' ABOVE GROUND FROM WHICH:  
A FIR 18" DIA., BEARS N 44-1/2° W, 15.0' WITH HEALED BLAZE (1987)  
A ROTTED STUMP 16" DIA., BEARS N 79-1/2° E, 31.7' (1987)  
(SET CHAINING NAIL AT SIDE CENTER, BT SIGNS ON FRONT AND BACK, AND PAINTED RED BAND FOR EXISTING BT'S)

ESTABLISHED THE FOLLOWING:  
A FIR 21" DIA., BEARS S 54° W, 12.5' MKD: CW 1/16 S15 BT  
(SET CHAINING NAIL AT SIDE CENTER, BT SIGNS ON FRONT AND BACK AND PAINTED RED BAND FOR NEW BT)

**208 CONT.**

MAY 1987 - AUGUST 1987  
BLM DEPENDENT RESURVEY BY BOYD W. PETERSON  
UNDER CONTRACT NO. 1364  
(DCSO RECORDS VOLUME 48, PAGE 18403)  
THE W 1/16 CORNER OF SECTIONS 15 & 22, MONUMENTED WITH AN IRON POST, 1-1/4" DIA., FIRMLY SET, PROJECTING 12" ABOVE GROUND, WITH BRASS CAP MKD: T28S R8W W 1/16 S15 S22 1972  
FROM WHICH BEARING TREES MKD BY SHANER:  
A W.FIR 25" DIA., BEARS N 67° E, 24 LKS. DIST., WITH HEALED BLAZE  
A FIR 18" DIA., BEARS S 67-1/4° W, 128 LKS. DIST., WITH HEALED BLAZE

JUNE 16, 2023  
GARRETT FINCH AND CREW WITH MINISTER AND GLAESER SURVEYING  
FOUND 2-1/2" BRASS CAP, 1' ABOVE GROUND FROM WHICH:  
A ROTTED STUMP 12" DIA., BEARS N 63° E, 14.5' (1972)  
(SET CHAINING NAIL AT SIDE CENTER, BT SIGNS ON FRONT AND BACK, AND PAINTED RED BAND FOR EXISTING BT'S)

ESTABLISHED THE FOLLOWING:  
A FIR 18" DIA., BEARS N 57° E, 9.1' MKD: W 1/16 S15 BT  
A MADRONE 6" DIA., BEARS S 10° W, 19.2' MKD: W 1/16 S22 BT  
(SET CHAINING NAIL AT SIDE CENTER, BT SIGNS ON FRONT AND BACK AND PAINTED RED BAND FOR NEW BT)

**209-FOUND MONUMENT**

CORNER P-13, (GCDB 400340)  
1/4 CORNER OF SECTIONS 21 & 22 T. 28 S., R. 08 W., W.M.

APRIL 12, 1855  
GLO SURVEY BY DENNIS HATHORN, DEPUTY SURVEYOR  
UNDER CONTRACT NO. 57  
(DCSO RECORDS VOL. 14 PAGE(S) 5808)  
SET 1/4 SEC. POST, FROM WHICH  
A FIR 9" DIA., BEARS S 78° E, 7 LKS. DIST.  
A FIR 15" DIA., BEARS N 12° W, 40 LKS. DIST.

JUNE 1969 - APRIL 1973  
BLM RESURVEY BY LYNN ROSEBERRY; DANIEL BERRY; GORDON POPKEN AND ALBERT GARRISON, CADASTRAL SURVEYORS  
UNDER GROUP NO. 691 AND 764  
(DCSO RECORDS VOL. 36, PAGE 15077)  
POINT FOR THE 1/4 SEC. COR., AT PROPORTIONATE DISTANCE; THERE IS NO REMAINING EVIDENCE OF THE ORIGINAL CORNER.  
SET AN IRON POST, 28" LONG, 2-1/2" DIA., 24" IN THE GROUND, WITH BRASS CAP MKD: T28S R8W 1/4 S21 S22 1973  
FROM WHICH:  
A FIR 15" DIA., BEARS N 66° E, 38 LKS. DIST. MKD. 1/4 S22 BT  
A FIR 10" DIA., BEARS N 49° W, 70 LKS. DIST. MKD. 1/4 S21 BT

JULY - OCTOBER 1985  
BLM RESURVEY BY DALE T. BEDELL, CADASTRAL SURVEYOR  
UNDER GROUP NO. 1278  
(DCSO RECORDS VOL. 48, PAGE 18263)  
THE 1/4 SECTION CORNER OF SECTIONS 21 & 22, MONUMENTED WITH AN IRON POST, 2-1/2" DIA., FIRMLY SET, PROJECTING 6" ABOVE GROUND, WITH BRASS CAP MKD: T28S R8W 1/4 S21 S22 1973  
FROM WHICH THE BEARING TREES MKD. BY ROSEBERRY, BERRY, POPKEN AND GARRISON:  
A FIR, 20" DIA., BEARS N 66° E, 38 LKS. DIST., WITH HEALED BLAZE  
A FIR, 12" DIA., BEARS N 49° W, 70 LKS. DIST., WITH HEALED BLAZE

JUNE 1993  
MARK HEIMBURGER WITH AA SURVEYING SERVICE, INC.  
(MAP FILE M117-37)  
FOUND BLM BRASS CAP 1973  
JANUARY 2019  
TONY HOSTETTER- FOR: WEYERHAEUSER CO.  
(C.S. FILE 65/103-4)  
FOUND- 1973 BLM BRASS CAP AS DESCRIBED IN (DCSO VOL. 36, PAGE 15077)  
FROM WHICH:  
27" FIR, FACE EVIDENT, BLM TAG, BEARS; N 66° E, 25.1'. TO CENTER  
18" FIR, FACE EVIDENT, BLM TAG, BEARS; N 49° W, 46.2'. TO CENTER  
NEW BTS:  
9" FIR, MARKED "X", BT TAG, S 4° E, 5.5'. TO SPIKE  
13" FIR, MKD "X", BT TAG, S 51° E, 10.9'. TO SPIKE (TAG READS N 51° E)  
6" CEDAR, MKD "X", BT TAG, N 48° E, 5.9'. TO SPIKE

JUNE 15, 2023  
GARRETT FINCH AND CREW WITH MINISTER AND GLAESER SURVEYING  
FOUND 3-1/4" BLM BRASS CAP, 0.4' ABOVE GROUND FROM WHICH:  
A FIR 10" DIA., BEARS S 04° E, 6.2' (SIDE) MKD. "X" AT BREAST HEIGHT (2019)  
[RECORD 5.5', MONUMENT TO SPIKE AT FACE OF TREE]  
A FIR 14" DIA., BEARS S 51° W, 11.8' (SIDE) MKD. "X" AT BREAST HEIGHT (2019)  
[RECORD S 51° E (TAG N 51° E), 10.9', MONUMENT TO SPIKE AT FACE OF TREE]  
A FIR 28" DIA., BEARS N 66° E, 25.5' MKD. "X" AT BREAST HEIGHT (1973)  
A FIR 18" DIA., BEARS N 49° W, 45.6' WITH HEALED BLAZE AND BT SIGN (1973)  
(SET CHAINING NAIL AT SIDE CENTER, BT SIGNS ON FRONT AND BACK, AND PAINTED RED BAND FOR EXISTING BT'S)

**210-FOUND MONUMENT**

CORNER L-14, (GCDB 420440)  
C-W 1/16 CORNER OF SECTION 15 T. 28 S., R. 08 W., W.M.

MAY - AUGUST 1987  
BLM RESURVEY BY BOYD W. PETERSON  
UNDER GROUP NO. 1364  
(DCSO RECORDS VOLUME 48, PAGE 18413)  
POINT FOR CENTER W 1/16 SECTION CORNER OF SECTION 15, SET A STAINLESS STEEL POST, 28" LONG, 2-1/2" DIA., 26" IN THE GROUND, WITH BRASS CAP MKD: C W 1/16 C S15 1987  
FROM WHICH:  
A FIR 5" DIA., BEARS N 79-1/2° E, 48 LKS. DIST., MKD: X BT  
A FIR 10" DIA., BEARS N 44-1/4° W, 22 LKS. DIST., MKD: CW