

**THIS RESURVEY IS IN COOS COUNTY –  
BUT BORDERS DOUGLAS COUNTY’S WEST LINE**

**UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT**

FIELD NOTES

OF THE

DEPENDENT RESURVEY OF PORTIONS OF THE  
NORTH BOUNDARY (SIXTH STANDARD PARALLEL SOUTH),  
EAST BOUNDARY, AND SUBDIVISIONAL LINES,

**TOWNSHIP 28 SOUTH, RANGE 9 WEST,**

OF THE WILLAMETTE MERIDIAN,

IN THE STATE OF OREGON.

**EXECUTED BY**

***Aaron M. Graham, Cadastral Surveyor***

Under Special Instructions dated March 6, 2002, approved March 7, 2002,  
which provided for the surveys included under Group No. 2012,  
and Assignment Instructions dated March 12, 2002

***Survey commenced April 1, 2002***

***Survey completed March 27, 2003***

## T. 28 S., R. 9 W., Willamette Meridian, Oregon

FEET

The following field notes are those of the dependent resurvey of a portion of the north boundary (Sixth Standard Parallel South), east boundary, and subdivisional lines of township 28 south, range 9 west, Willamette Meridian, Oregon.

The history of surveys that pertain to this survey is as follows:

In 1855, Dennis Hathorn, U.S Deputy Surveyor, surveyed the sixth standard parallel south through range 8 west and the east boundary of T. 28 S., R. 9 W.

In 1875, Winfield S. Chapman, U.S. Deputy Surveyor, surveyed the sixth standard parallel south through range 9 west and subdivisional lines of T. 28 S., R. 9 W.

In 1896, William P. Heydon, U.S. Deputy Surveyor, resurveyed a portion of the sixth standard parallel south through range 8 west and established corners along south boundary of T. 27 S., R. 8 W.

In 1896, Samuel W. Lackland, U.S. Deputy Surveyor, retraced the sixth standard parallel south through range 9 west and established corners along the south boundary of T. 27 S., R. 9 W.

In 1962, Joseph S. Gawron, Cadastral Surveyor, remonumented certain original corner points without survey.

In 1969-73, Lynn M. Roseberry, Daniel L. Berry, Gurdon S. Popken, and Albert J. Garrison, Cadastral Surveyors, resurveyed a portion of the subdivisional lines of T. 28 S., R. 8 W.

In 1977, Harvey E. Wofford, Cadastral Surveyor, resurveyed a portion of the subdivisional lines.

In 1985, John A. Farmer, Cadastral Surveyor, resurveyed a portion of the subdivisional lines.

In 1993, Boyd W. Peterson, Cadastral Surveyor, resurveyed a portion of the subdivisional lines.

In 1999-2000, John A. Farmer, Cadastral Surveyor, resurveyed a portion of the subdivisional lines and rehabilitated certain corner points.

The survey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions dated March 6, 2002, for Group No. 2012, Oregon.

The directions of the lines are based on the true meridian as determined by direct solar observations and were carried forward by means of sustained angulation. All measurements along the lines were derived through the use of electronic measuring equipment.

An analysis of the unadjusted field data assured a closure not exceeding 1:4000 in error. Measured distances and directions have been adjusted by Cadastral Measurement

## T. 28 S., R. 9 W., Willamette Meridian, Oregon

FEET	<p>Management (CMM), computer software that incorporates a least squares adjustment routine. The adjusted bearings and distances are reported to the nearest second and 0.01 foot.</p> <p>Preliminary to the resurvey, the lines of the prior surveys were retraced and search was made for all corners and other calls of record. Identified corners were remonumented in their original positions. Lost corners were reestablished and remonumented at proportionate positions based on the official record. The retracement data were thoroughly verified and only the true line field notes are given herein.</p> <p>Each new bearing tree has a 2½ inch x ¼ inch magnetic nail (Mag Nail) driven at the base on right side center, unless otherwise noted in the corner description.</p> <p>The geographic position (NAD 1983 (91)) of the cor. of secs. 35 and 36, on the S. bdy. of T. 27 S., R. 9 W., as determined by the NAVSTAR Global Positioning System (GPS), by direct occupation, utilizing single frequency, carrier phase GPS receivers (see the Control Data Sheet attached to these field notes following the General Description), is as follows:</p> <p>Latitude: 43° 10' 13.952" N.      Longitude: 123° 43' 24.663" W.</p> <p>The geographic position (NAD 1983 (91)) of the cor. of secs. 10, 11, 14, and 15, as determined by Boyd W. Peterson in 1993, converted from NAD 1927 to (NAD 1983 (91)), is as follows:</p> <p>Latitude: 43° 08' 29.24" N.      Longitude: 123° 44' 28.77" W.</p> <hr/>
------	--

Dependent Resurvey of a Portion of the North Boundary  
 (Sixth Standard Parallel South),  
 T. 28 S., R. 9 W., Willamette Meridian, Oregon

FEET

(Restoring the survey by Chapman in 1875  
 and the resurvey by Lackland in 1896)

Beginning at the point for the cor. of Tps. 28 S., Rs. 8 and 9 W., on the Sixth Standard Parallel South, at proportionate distance, there is no remaining evidence of the original corner.

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.

```

T 27 S R 8 W
  S 31
-----
S 1 | S 6
R 9 W | R 8 W
      T 28 S
  
```

2002

from which

A fir, 10 ins. diam., bears S. 59° E., 7.2 ft. dist., mkd. T28S R8W S6 BT.

A fir, 11 ins. diam., bears S. 14½° W., 19.3 ft. dist., mkd. T28S R9W S1 BT.

Deposit a magnet in a white plastic case at the base of the stainless steel post.

From this point, the ¼ sec. cor. of sec. 31 only, on the S. bdy of T. 27 S., R. 8 W., perpetuated by the Douglas County Surveyor's Office in 1970, C.S. file 54/113, bears N. 89° 19' 14" E., 2198.64 ft. dist. (this control line was retraced and search was made for the intermediate line tree, which was not recovered), monumented with an iron post, 1½ ins. diam., firmly set, projecting 2 ins. above the ground, with brass cap mkd.

```

T 27 S R 8 W
  S 31
  1/4 -----
  T 28 S
  
```

1970

Dependent Resurvey of a Portion of the North Boundary  
 (Sixth Standard Parallel South),  
 T. 28 S., R. 9 W., Willamette Meridian, Oregon

FEEET	<p>from which the remains of the original bearing trees</p> <p style="padding-left: 40px;">A yew stump, 14 ins. diam., bears N. 12¼° E., 15.5 ft. dist., with no scribe marks visible on burned blaze. (Record, N. 40° E., 16.5 ft. dist.)</p> <p style="padding-left: 40px;">A fir stump, 42 ins. diam., bears N. 50° W., 11.2 ft. dist., with fragmentary scribe marks visible on open blaze.</p> <p>and new bearing trees</p> <p style="padding-left: 40px;">A fir, 8 ins. diam., bears N. 18° E., 11.5 ft. dist., mkd. X at breast height and BT at base.</p> <p style="padding-left: 40px;">A fir, 8 ins. diam., bears N. 35¾° W., 23.8 ft. dist., mkd. 1/4 S31 BT.</p> <p>S. 89° 19' 14" W., on the N. bdy. of sec. 1.</p>
80	<p>Creek 5 ft. wide, course S. 80° W., asc. over S. slope.</p>
476.92	<p>The cor. of Tps. 27 S., Rs. 8 and 9 W., restored by C.S. Lehmanowsky, Registered Engineer No. 1768, in 1953, recorded in the Coos County Surveyor's Office book 8, page 154, subsequently rehabilitated by the Douglas County Surveyor's Office in 1970, C.S. file 54/113, subsequently utilized by Jerry Lee Estabrook, Registered Land Surveyor No. 2703, in 1996, recorded in the Coos County Surveyor's Office No. 22b71, further utilized by Clyde F. Mulkins, Registered Land Surveyor No. 2006, in 1997, recorded in the Coos County Surveyor's Office No. 22A185. This point has long been accepted as the corner and is accepted as the best available evidence of the position of the original corner, monumented with an iron post, 1½ ins. diam., firmly set, projecting 5 ins. above the ground, with brass cap mkd.</p> <div style="text-align: center; margin-top: 20px;"> <p>T 27 S</p> <p> </p> <p>R 9 W S 36   S 31 R 8 W</p> <p> </p> <p>S 1</p> <p>T 28 S</p> <p>1970</p> </div>

**Dependent Resurvey of a Portion of the North Boundary  
(Sixth Standard Parallel South),  
T. 28 S., R. 9 W., Willamette Meridian, Oregon**

FEET	
	<p>from which the remains of bearing trees mkd. by Lehmanowsky in 1953</p> <p style="padding-left: 40px;">A hemlock stump, size indeterminate, bears N. 67° E., 22.5 ft. dist., no marks visible.</p> <p style="padding-left: 40px;">A yew stump, 28 ins. diam., bears N. 68° W., 30.0 ft. dist., with axe marks visible.</p> <p>and bearing trees mkd. by Mulkins in 1997</p> <p style="padding-left: 40px;">A fir, 11 ins. diam., bears N. 58½° E., 21.5 ft. dist., with a healed blaze.</p> <p style="padding-left: 40px;">A fir, 12 ins. diam., bears S. 17° W., 8.6 ft. dist., with a healed blaze.</p> <p style="padding-left: 40px;">A fir, 10 ins. diam., bears N. 68° W., 21.6 ft. dist., with a healed blaze.</p> <p style="padding-left: 40px;">A fir, 10 ins. diam., bears N. 5¼° W., 4.6 ft. dist., with a healed blaze.</p> <p>and the remains of a bearing tree mkd. by person(s) unknown</p> <p style="padding-left: 40px;">A fir stump, 72 ins. diam., bears S. 13° W., 26.8 ft. dist., with no marks visible on burned blaze.</p> <hr style="width: 20%; margin: 10px auto;"/> <p style="padding-left: 40px;">S. 89° 45' 13" W., beginning new measurement.</p> <p>Ascend across SE. slope through medium timber and light undergrowth.</p>
1035	Spur, slopes S. 20° W., desc. over SW. slope.
2015	Dirt road, 12 ft. wide, bears N. 45° E. and S. 45° E.
2140	Creek 10 ft. wide, course S. 30° W., asc. over SE. slope.
2149.01	<p>Point for the ¼ sec. cor. of sec. 1 only, on the N. bdy. of the Tp., at proportionate distance, there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

Dependent Resurvey of a Portion of the North Boundary  
 (Sixth Standard Parallel South),  
 T. 28 S., R. 9 W., Willamette Meridian, Oregon

FEET	
	<p style="text-align: center;"> <u>1/4 S 1</u>            T 28 S R 9 W              2002         </p> <p>from which</p> <p style="padding-left: 40px;">An alder, 12 ins. diam., bears S. 19° E., 40.3 ft. dist., mkd. 1/4 S1 BT in bark.</p> <p style="padding-left: 40px;">An alder, 17 ins. diam., bears S. 83¼° W., 41.3 ft. dist., mkd. 1/4 S1 BT in bark.</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
2649.01	<p>The ¼ sec. cor. of sec. 36 only, on the S. bdy. of T. 27 S., R. 9 W., reestablished by proportionate measurement by Jerry Lee Estabrook, Registered Land Surveyor No. 2703, in 1996, recorded in the Coos County Surveyor's Office No. 22b71, and is accepted as the corner. There is no remaining evidence of the original corner; monumented with an iron rod, ¼ in. diam., firmly set, projecting 3 ins. above the ground, with aluminum cap mkd.</p> <p style="text-align: center;"> <u>1/4 S 36</u>  <u>1996</u>            LS 2703         </p> <p>from which bearing trees mkd. by Estabrook in 1996</p> <p style="padding-left: 40px;">A fir, 17 ins. diam., bears N. 54½° E., 21.2 ft. dist., with scribe marks 1/4 S36 BT visible on partially healed blaze.</p> <p style="padding-left: 40px;">A fir, 18 ins. diam., bears N. 79½° E., 27.8 ft. dist., with X at breast height and a healed blaze.</p> <p style="padding-left: 40px;">A fir, 20 ins. diam., bears S. 23° E., 4.6 ft. dist., with X at breast height and a healed blaze.</p> <p style="padding-left: 40px;">An alder, 16 ins. diam., bears N. 61° W., 22.8 ft. dist., with scribe marks 1/4 S36 BT visible in bark.</p> <p style="text-align: center;"> <hr style="width: 20%; margin: 0 auto;"/>           S. 89° 44' 54" W., beginning new measurement.         </p>

Dependent Resurvey of a Portion of the North Boundary  
 (Sixth Standard Parallel South),  
 T. 28 S., R. 9 W., Willamette Meridian, Oregon

FEEET	Ascend SE. slope through medium timber and light undergrowth.				
915	Spur, slopes S., desc. over SW. slope.				
1060	Creek 2 ft. wide, course S. 70° E., asc. over SE. slope.				
2186.38	<p>The cor. of secs. 1 and 2, on the N. bdy of the Tp., perpetuated by C.S. Lehmanowsky, Registered Engineer No. 1768, in 1953, from original evidence no longer in existence, recorded in the Coos County Surveyor's Office No. 26a14, subsequently perpetuated by Clyde F. Mulkins, Registered Land Surveyor No. 2006, in 1993, recorded in the Coos County Surveyor's Office No. 26b62; monumented with an iron rod, 5/8 in. diam., firmly set, projecting 1 in. above the ground, with aluminum cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>LS 2006              T 27 S R 9 W              S 36</p> <hr style="width: 100px; margin: 0 auto;"/> <table style="margin: 0 auto; border-collapse: collapse;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 2</td> <td style="padding: 0 5px;">S 1</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">T 28 S</td> <td style="padding: 0 5px;">R 9 W</td> </tr> </table> <p>1993</p> </div> <p>from which the remains of bearing trees mkd. by Lehmanowsky in 1953</p> <p style="margin-left: 40px;">A fir sump, 22 ins. diam., bears S. 55½° E., 24.9 ft. dist., with scribe marks S 1 BT visible on open blaze.</p> <p style="margin-left: 40px;">A fir stump, 60 ins. diam., bears S. 40¼° W., 69.7 ft. dist., no marks visible.</p> <p>and bearing trees mkd. by Mulkins in 1993</p> <p style="margin-left: 40px;">A fir, 35 ins. diam., bears S. 9° W., 41.2 ft. dist., with a healed blaze.</p> <p style="margin-left: 40px;">A fir stump, 15 ins. diam., bears N. 64° W., 10.7 ft. dist., with scribe mark T visible on partially healed blaze.</p> <hr style="width: 60%; margin: 20px auto;"/> <p style="margin-left: 40px;">N. 89° 21' 11" W., on the N. bdy. of sec. 2</p> <p style="margin-left: 40px;">Across nearly level land over clear cut.</p>	S 2	S 1	T 28 S	R 9 W
S 2	S 1				
T 28 S	R 9 W				

**Dependent Resurvey of a Portion of the North Boundary  
(Sixth Standard Parallel South),  
T. 28 S., R. 9 W., Willamette Meridian, Oregon**

FEET	
462.21	<p>The cor. of secs. 35 and 36, on the S. bdy. of T. 27 S., R. 9 W., perpetuated by Joel Robb, Surveying Technician for the BLM, in 1978, recorded in the Coos County Surveyor's Office book 12, page 289, subsequently perpetuated by Clyde F. Mulkins, Registered Land Surveyor No. 2006, in 1993, recorded in the Coos County Surveyor's Office No. 26b62; monumented with an iron rod, 5/8 in. diam., firmly set, flush with the surface of the ground, from which the remains of an original bearing tree.</p> <p style="padding-left: 40px;">A fir stump, 54 ins. diam., bears N. 62° E., 23.6 ft. dist., with no scribe marks visible on burned blaze. (Record, 21.8 ft. dist.)</p> <p>and bearing trees mkd. by Robb in 1978</p> <p style="padding-left: 40px;">A fir, 15 ins. diam., bears N. 75° E., 19.5 ft. dist., with a healed blaze.</p> <p style="padding-left: 40px;">A fir, 20 ins. diam., bears N. 29° W., 6.8 ft. dist., with a healed blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, directly over the iron rod, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 27 S R 9 W</p> <p style="margin-left: 40px;">S 35   S 36</p> <hr style="width: 10%; margin: 0 auto;"/> <p style="margin-left: 40px;">S 2</p> <p>T 28 S R 9 W</p> <p>2002</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 89° 23' 22" W., beginning new measurement.</p> <p>Descend W. slope along S. edge of heavy timber and N. edge of clear cut.</p>
1745	<p>Creek 8 ft. wide, course S. 20° W., asc. over E. slope through medium timber and light undergrowth.</p>
2093.51	<p>Point for the ¼ sec. cor. of sec. 2 only, on the N. bdy. of the Tp., at proportionate distance. There is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 27 S</p> <hr style="width: 10%; margin: 0 auto;"/> <p style="margin-left: 40px;">1/4 S 2</p> <p>T 28 S R 9 W</p> </div>

Dependent Resurvey of a Portion of the North Boundary  
(Sixth Standard Parallel South),  
T. 28 S., R. 9 W., Willamette Meridian, Oregon

FEEET	<p style="text-align: center;">2002</p> <p>from which</p> <p style="padding-left: 40px;">A fir, 8 ins. diam., bears N. 0¼° E., 30.6 ft. dist., mkd. X at breast height and BT at base.</p> <p>There are no trees available in section 2.</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
2170.47	<p>A point erroneously reestablished as the ¼ sec. cor. of sec. 2 only, by Clyde F. Mulkins, Registered Land Surveyor No. 2006, in 1993, recorded in the Coos County Surveyor's Office No. 26b62. This point is not utilized in this survey; monumented with an iron rod, 5/8 in. diam., firmly set, projecting 3 ins. above the ground, with aluminum cap mkd. 1993 T27S R9W 1/4 S2 T28S LS 2006, from which bearing trees mkd. by Mulkins</p> <p style="padding-left: 40px;">A fir, 10 ins. diam., bears N. 39° E., 19.9 ft. dist., with X at breast height and a healed blaze.</p> <p style="padding-left: 40px;">A fir, 20 ins. diam., bears S. 3½° E., 41.6 ft. dist., with illegible scribe marks visible on partially healed blaze.</p> <p style="padding-left: 40px;">A hemlock, 18 ins. diam., bears S. 86¼° W., 2.7 ft. dist., with illegible scribe marks visible on partially healed blaze.</p> <p style="padding-left: 40px;">A hemlock, 18 ins. diam., bears N. 13¼° W., 7.8 ft. dist., with X at breast height and illegible scribe marks visible on partially healed blaze.</p>

**Dependent Resurvey of a Portion of the North Boundary  
(Sixth Standard Parallel South),  
T. 28 S., R. 9 W., Willamette Meridian, Oregon**

FEET	
2525.34	<p>Point for the ¼ sec. cor. of sec. 35 only, on the S. bdy. of T. 27 S., R. 9 W., at proportionate distance. There is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 27 S R 9 W 1/4 S 35</p> <hr style="width: 50px; margin: auto;"/> <p>2002</p> </div> <p>from which</p> <p style="padding-left: 40px;">A hemlock, 18 ins. diam., bears N. 27° E., 47.0 ft. dist., mkd. X at breast height and BT at base.</p> <p style="padding-left: 40px;">A hemlock, 14 ins. diam., bears N. 51° W., 18.4 ft. dist., mkd. 1/4 S35 BT.</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Ascend E. slope along S. edge of heavy timber and N. edge of brushy clear cut.</p>
3315	<p>Graveled road, 15 ft. wide, bears N. 10° E. and S. 10° W., also ridge, bears same; Desc. W. slope along S. edge of heavy timber and N. edge of clear cut.</p>
4735	<p>Dirt road, 10 ft. wide, bears N. and S.</p>
4801.31	<p>The cor. of secs. 2 and 3, on the N. bdy. of the Tp., perpetuated by Clyde F. Mulkins, Registered Land Surveyor No. 2006, in 1993, recorded in the Coos County Surveyor's Office No. 26b62; monumented with an iron rod, 5/8 in. diam., firmly set, projecting 1 in. above the ground, with aluminum cap mkd.</p> <div style="text-align: center;"> <p>1998</p> <p>T 27 S R 9 W</p> <p style="margin-left: 40px;">S 35</p> <hr style="width: 50px; margin: auto;"/> <p style="margin-left: 20px;">S 3   S 2</p> <p style="margin-left: 40px;">T 28 S</p> <p style="margin-left: 40px;">LS 2006</p> </div> <p>from which the remains of the original bearing trees</p>

**Dependent Resurvey of a Portion of the North Boundary  
(Sixth Standard Parallel South),  
T. 28 S., R. 9 W., Willamette Meridian, Oregon**

<p>F E E T</p>	<p>A fir stump, 46 ins. diam., bears N. 62° E., 26.4 ft. dist., with a healed blaze.</p> <p>A decayed hemlock stump, size indeterminate, bears S. 82° E., 27.7 ft. dist., no marks visible.</p> <p>A cedar stump, 11 ins. diam., bears S. 35° W., 18.5 ft. dist., with scribe marks S3 visible on open blaze.</p> <p>and bearing trees mkd. by Mulkins in 1993</p> <p>A fir, 15 ins. diam., bears N. 18½° E., 24.1 ft. dist., with a healed blaze.</p> <p>A fir, 15 ins. diam., bears S. 56° E., 9.0 ft. dist., with a healed blaze.</p> <p>A fir, 16 ins. diam., bears N. 39° W., 11.4 ft. dist., with a healed blaze.</p> <p>and a bearing tree mkd. by person(s) unknown</p> <p>A fir stump, 58 ins. diam., bears N. 10° E., 24.1 ft. dist., with a healed blaze.</p> <p>and a new bearing tree</p> <p>A fir, 10 ins. diam., bears S. 25½° W., 30.2 ft. dist., mkd. T28S R9W S3 BT.</p> <hr/> <p style="text-align: center;"><b>Dependent Resurvey of a Portion of the East Boundary, T. 28 S., R. 9 W., Willamette Meridian, Oregon</b></p> <hr/> <p style="text-align: center;">(Restoring the survey by Hathorn in 1855)</p> <hr/> <p>From the cor. of secs. 13, 18, 19, and 24, on the E. bdy. of the Tp., monumented with an iron post, 2½ ins. diam., firmly set, projecting 2 ins. above the ground, (alongside an iron pipe, 1½ ins. diam.) with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr> <td colspan="2">T 28 S</td> </tr> <tr> <td>R 9 W</td> <td>R 8 W</td> </tr> <tr> <td>S 13</td> <td>S 18</td> </tr> <tr> <td colspan="2"><hr style="width: 50%; margin: 0 auto;"/></td> </tr> <tr> <td>S 24</td> <td>S 19</td> </tr> </table> <p>1972</p> </div> <p>from which the remains of an original bearing tree</p> <p>A fir stump, 45 ins. diam., bears S. 54° E., 23.8 ft. dist., with a healed blaze (Record, S. 60° E.).</p> <p>and the remains of bearing trees mkd. by Safstrom in 1961, reported by Roseberry et. al. in 1972</p>	T 28 S		R 9 W	R 8 W	S 13	S 18	<hr style="width: 50%; margin: 0 auto;"/>		S 24	S 19
T 28 S											
R 9 W	R 8 W										
S 13	S 18										
<hr style="width: 50%; margin: 0 auto;"/>											
S 24	S 19										

**Dependent Resurvey of a Portion of the East Boundary,  
T. 28 S., R. 9 W., Willamette Meridian, Oregon**

FEET	
	<p>A yew snag, 5 ins. diam., bears N. 71½° E., 12.5 ft. dist., with scribe marks S8 BT visible on partially open blaze.</p> <p>A hemlock, 25 ins. diam., bears S. 21° W., 15.8 ft. dist., with a healed blaze.</p> <p>A hemlock, 17 ins. diam., bears N. 69° W., 15.2 ft. dist., with a healed blaze.</p> <p>and bearing trees mkd. by person(s) unknown</p> <p>A hemlock, 11 ins. diam., bears S. 29½° E., 17.2 ft. dist., with scribe marks T28S R8W S19 BT visible on partially opened blaze.</p> <p>A fir stump, 61 ins. diam., bears S. 5¼° W., 20 ft. dist., with a healed blaze.</p> <p>A hemlock, 26 ins. diam., bears N. 2½° W., 2.4 ft. dist., with a healed blaze.</p> <p>and a new bearing tree</p> <p>A hemlock, 13 ins. diam., bears N. 50¼° E., 26.9 ft. dist., mkd. T28S R8W S18 BT.</p> <p>N. 0° 04' 14" W., bet. secs. 13 and 18.</p> <p>Descend across W. slope along E. edge of heavy timber and W. edge of dense undergrowth.</p>

**Dependent Resurvey of a Portion of the East Boundary,  
T. 28 S., R. 9 W., Willamette Meridian, Oregon**

FEET	
135	Ravine, drains S. 60° W., asc. over NW. slope.
1885	Top of ascent, slopes N. 60° W., desc. over NE. slope.
2624.26	<p>The ¼ sec. cor. of sec. 13 and 18, reestablished by proportionate measurement by Michael S. McDowell, Registered Land Surveyor No 1032, in 1975, recorded in the Coos County Surveyor's Office book 12 page 204, and survey file 26a59. There is no remaining evidence of the original corner, therefore this position is accepted as the corner; monumented with an iron pipe, 2 ins. diam., firmly set, projecting 24 ins. above the ground, from which the remains of bearing trees mkd. by McDowell.</p> <p style="padding-left: 40px;">A fir stump, 36 ins. diam., bears N. 55° E., 27.6 ft. dist., with a healed blaze.</p> <p style="padding-left: 40px;">A yew snag, 9 ins. diam., bears N. 43½° W., 15.4 ft. dist., with scribe marks 1/4 S13 BT visible in bark.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 28 S</p> <p>R 9 W    R 8 W</p> <p>      1/4</p> <p>S 13   S 18</p> <p>      2002</p> </div> <p>from which</p> <p style="padding-left: 40px;">A hemlock, 7 ins. diam., bears N. 39¼° E., 21.4 ft. dist., mkd. 1/4 S18 BT.</p> <p style="padding-left: 40px;">A fir, 8 ins. diam., bears S. 77° W., 16.2 ft. dist., mkd. 1/4 S13 BT.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Remove the 2 in. diam. iron pipe from the area.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0° 03' 17" W., beginning new measurement.</p> <p>Descend across steep NE. slope through medium timber and light undergrowth.</p>
2090	From this point, the NE. cor. of a wood framed building 16' x 30', bears W. 34.9 ft. dist., long side bears NW.
2105	East Fork Coquille River 20 ft. wide, course N. 50° W., over nearly level land.
2600	Coos Bay Wagon Road, asphalt surface to E., graveled surface to W., 24 ft. wide, bears S. 25° E. and N. 25° W.

Dependent Resurvey of a Portion of the East Boundary,  
T. 28 S., R. 9 W., Willamette Meridian, Oregon

FEET									
2623.57	<p>The cor. of secs. 7, 12, 13, and 18, on the E. bdy. of the Tp., perpetuated by Floyd Frear, Deputy County Surveyor, in 1953, from original evidence no longer in existence, recorded in the Douglas County Surveyor's Office C.S. file 41/197, further perpetuated by James W. Byron, Deputy County Surveyor, in 1956, recorded in the Douglas County Surveyor's Office C.S. file 47/90; monumented with an iron post, 2 ins. diam., firmly set., 6 ins. below the surface of the ground, with brass cap mkd.</p> <p style="text-align: center;">T 28 S</p> <table style="margin-left: auto; margin-right: auto; border-collapse: collapse;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">R 9 W S 12</td> <td style="border-right: 1px solid black; padding: 0 5px;">S 7 R 8 W</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px; text-align: center;">S 13</td> <td style="border-right: 1px solid black; padding: 0 5px; text-align: center;">S 18</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px; text-align: center;">Coos Co.</td> <td style="border-right: 1px solid black; padding: 0 5px; text-align: center;">Douglas Co.</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;"></td> <td style="border-right: 1px solid black; padding: 0 5px; text-align: center;">1956</td> </tr> </table> <p>from which the remains of bearing trees mkd. by Frear in 1953</p> <p style="padding-left: 40px;">A fir stump, 66 ins. diam., bears S. 83° E., 23.7 ft. dist., no marks visible.</p> <p style="padding-left: 40px;">A fir stump, 48 ins. diam., bears S. 32° W., 46.2 ft. dist., no marks visible.</p> <p>and the remains of bearing trees mkd. by Byron in 1956</p> <p style="padding-left: 40px;">A fir stump, 60 ins. diam., bears N. 66° E., 87.8 ft. dist., no marks visible.</p> <p style="padding-left: 40px;">A fir stump, 72 ins. diam., bears N. 57° W., 83.8 ft. dist., no marks visible.</p> <p>and new bearing trees</p>	R 9 W S 12	S 7 R 8 W	S 13	S 18	Coos Co.	Douglas Co.		1956
R 9 W S 12	S 7 R 8 W								
S 13	S 18								
Coos Co.	Douglas Co.								
	1956								

**Dependent Resurvey of a Portion of the East Boundary,  
T. 28 S., R. 9 W., Willamette Meridian, Oregon**

FEET

- A fir, 14 ins. diam., bears N.  $30\frac{3}{4}^{\circ}$  E., 44.0 ft. dist.,  
mkd. T28S R8W S7 BT.
- A Fir, 19 ins. diam., bears S.  $50\frac{1}{2}^{\circ}$  E., 49.2 ft. dist.,  
mkd. T28S R8W S18 BT.
- A fir, 23 ins. diam., bears S.  $26\frac{1}{4}^{\circ}$  W., 49.0 ft. dist.,  
mkd. T28S R9W S13 BT.
- A fir, 32 ins. diam., bears N.  $54^{\circ}$  W., 69.4 ft. dist.,  
mkd. T28S R9W S12 BT.

---

From the cor. of secs. 1, 6, 7, and 12, on the E. bdy. of the Tp., perpetuated by Forrest J. LaFlamme, Registered Land Surveyor No. 473, in 1962, recorded in the Coos County Surveyor's Office, Book 10, page 168, subsequently perpetuated by the Douglas County Surveyor's Office, in 1970, C.S. file 54/113, further perpetuated by Harvey M. Christensen, Registered Land Surveyor No. 2603, in 1999, recorded in the Coos County Surveyor's Office book 16, page 103; monumented with an iron post, 1 in. diam., firmly set, projecting 10 ins. above the ground, with brass cap mkd.

T 28 S	
R 9 W	R 8 W
S 1	S 6
S 12	S 7

1970

from which the remains of the original bearing trees

- A root hole, bears N.  $40^{\circ}$  E., 9.2 ft. dist., with a fir log alongside, 40 ins. diam., no marks visible.
- A fir stump, 33 ins. diam., bears S.  $75^{\circ}$  E., 16.5 ft. dist., no marks visible.
- A fir stump, 61 ins. diam., bears S.  $47\frac{3}{4}^{\circ}$  W., 32.5 ft. dist., with scribe marks S12 BT visible on open blaze (Record, S.  $45^{\circ}$  W., 30.4 ft. dist.).
- A fir stump, 25 ins. diam., bears N.  $40^{\circ}$  W., 29.0 ft. dist., no marks visible.

and the remains of bearing trees mkd. LaFlamme in 1962

- A fir stump, 36 ins. diam., bears S.  $35\frac{3}{4}^{\circ}$  E., 38.5 ft. dist., with scribe marks S7 BT 47 visible on open blaze.

and the remains of bearing trees mkd. by the Douglas County Surveyor's Office in 1970

- A fir stump, 53 ins. diam., bears S.  $80\frac{3}{4}^{\circ}$  E., 27.8 ft. dist., with scribe marks T28S R8W S7 C BT visible on partially healed blaze.
- A hemlock, 28 ins. diam., bears S.  $81\frac{1}{2}^{\circ}$  W., 85.5 ft. dist., with a healed blaze.

Dependent Resurvey of a Portion of the East Boundary,  
T. 28 S., R. 9 W., Willamette Meridian, Oregon

FEEET	<p>and bearing trees mkd. by Christensen in 1999</p> <p style="padding-left: 40px;">A fir, 10 ins. diam., bears N. 59° E., 38.2 ft. dist., with scribe marks T28S R8W S6 BT visible on partially healed blaze.</p> <p style="padding-left: 40px;">A fir, 9 ins. diam., bears S. 50½° E., 14.6 ft. dist., with scribe marks T28S R8W S7 BT visible on partially healed blaze.</p> <p style="padding-left: 40px;">A fir, 14 ins. diam., bears N. 53½° W., 39.9 ft. dist., with scribe marks T28S R9W S1 BT visible on partially healed blaze.</p> <p>N. 0° 00' 50" E., bet. secs. 1 and 6.</p> <p>Across nearly level ground, through medium timber and moderate undergrowth.</p>				
2060	Graveled road, 12 ft. wide, bears S. 40° E. and N. 40° W.				
2653.15	<p>The ¼ sec. cor. of secs. 1 and 6, on the E. bdy. of the Tp., perpetuated by the Douglas County Surveyor's Office, in 1982, C.S. file 61/30; monumented with an iron post, 1 in. diam., firmly set, projecting 3 ins. above the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T 28 S R 8 W</p> <p style="margin-left: 40px;">1/4</p> <table style="margin-left: 40px; border-collapse: collapse;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 1</td> <td style="padding: 0 5px;">S 6</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">R 9 W</td> <td style="padding: 0 5px;">1982</td> </tr> </table> </div> <p>from which the remains of the original bearing trees</p>	S 1	S 6	R 9 W	1982
S 1	S 6				
R 9 W	1982				

**Dependent Resurvey of a Portion of the East Boundary,  
T. 28 S., R. 9 W., Willamette Meridian, Oregon**

FEET	
	<p>A chinquapin, 12 ins. diam., bears S. 70° E., 24.1 ft. dist., with illegible scribe marks visible on open blaze. (Record, 39.6 ft. dist.)</p> <p>A root hole, bears S. 85° W., 16.5 ft. dist., with a chinquapin log, size indeterminate alongside, no marks visible.</p> <p>and bearing trees mkd. by the Douglas County Surveyor's Office in 1982</p> <p>A fir, 13 ins. diam., bears S. 5½° W., 18.1 ft. dist., with a healed blaze.</p> <p>A hemlock, 12 ins. diam., bears N. 27° W., 6.2 ft. dist., with a healed blaze.</p> <p>From this point, a point established as the ¼ sec. cor. of secs. 1 and 6, by Floyd Vandervelden, Registered Land Surveyor No. 1047, in 1982, C.S. file 61/33, bears S. 73° 17' 00" E., 8.02 ft. dist., determined by distance-distance intersection from bearing trees mkd. by Vandervelden. This point was erroneously positioned and is not utilized in this survey. From which bearing trees mkd. by Vandervelden.</p> <p>A fir, 13 ins. diam., bears N. 8¼° W., 9.1 ft. dist., with a healed blaze.</p> <p>A fir, 14 ins. diam., bears S. 83° W., 4.2 ft. dist., with a healed blaze.</p> <p>and a bearing tree mkd. by person(s) unknown</p> <p>A hemlock stump, 9 ins. diam., bears N. 58° E., 39.3 ft. dist., with no scribe marks visible on partially open blaze.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 1° 31' 28" E., beginning new measurement.</p> <p>Descend NE. slope through medium timber and moderate undergrowth.</p>
1510	Creek 6 ft. wide, course N. 55° W., asc. over SW. slope.
2105	Top of ascent, slopes S. 60° W., desc. over steep N. slope.

**Dependent Resurvey of a Portion of the East Boundary,  
T. 28 S., R. 9 W., Willamette Meridian, Oregon**

FEET	
2635.12	<p>The cor. of Tps. 28 S., Rs. 8 and 9 W</p> <hr/> <p style="text-align: center;"><b>Dependent Resurvey of a Portion of the Subdivisional Lines, T. 28 S., R. 9 W., Willamette Meridian, Oregon</b></p> <hr/> <p style="text-align: center;">(Restoring the survey by Winfield S. Chapman in 1875)</p> <hr/> <p>From the cor. of secs. 13, 18, 19, and 24, on the E. bdy of the Tp.</p> <p>S. 88° 46' 47" W., bet. secs. 13 and 24.</p> <p>Descend W. slope through heavy timber and moderate undergrowth.</p>
590	Creek, 2 ft. wide, course N. 20° W., asc. over NE. slope.
845	Spur, slopes N. 45° W., desc. over SW. slope.
980	Creek, 4 ft. wide, course N. 40° W., asc. over NE. slope.
1960	Spur, slopes N. 10° E., desc. over NW. slope.
2568.25	<p>The ¼ sec. cor. of secs. 13 and 24, perpetuated by Jack E. LaFlamme, Registered Land Surveyor No. 378, in 1978, recorded in the Coos County Surveyor's Office book 12 page 328, monumented with an iron pipe, 2 ins. diam., firmly set, projecting 6 ins. above the ground, from which the remains of the original bearing trees</p> <p style="padding-left: 40px;">A hemlock snag, 40 ins. diam., bears S. 65° W., 8.6 ft. dist., with no scribe marks visible on rotten blaze.</p> <p style="padding-left: 40px;">A hemlock snag, 23 ins. diam., bears N. 9° W., 35.6 ft. dist., with scribe marks 1/4 S visible on partially healed blaze.</p> <p>and the remains of bearing trees mkd. by LaFlamme in 1978</p> <p style="padding-left: 40px;">A cedar stump, 35 ins. diam., bears N. 71½° E., 51.2 ft. dist., with scribe marks 1/4 S13 BT visible on open blaze.</p> <p style="padding-left: 40px;">A hemlock, 33 ins. diam., bears S. 73¼° W., 53.6 ft. dist., with no scribe marks visible on partially healed blaze.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 28 S., R. 9 W., Willamette Meridian, Oregon

FEET	
	At the corner point
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 28 S R 9 W S 13 1/4 ——— S 24  2002
	from which
	A fir, 13 ins. diam., bears N. 21½° W., 11.1 ft. dist., mkd. 1/4 S13 BT.
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Remove 2 in. diam. iron pipe from the area.
	_____
	S. 89° 47' 29" W., beginning new measurement.
	Descend NW. slope through heavy timber.
370	Creek, 9 ft. wide, course N. 20° W., asc. over NE. slope.
1075	Spur, slopes N. 45° E., desc. over W. slope.
1150	Ravine, drains N. 30° E., asc. over NE. slope.
1665	Spur, slopes N. 65° E., desc. over W. slope.
2657.77	The cor. of secs. 13, 14, 23, and 24, monumented with an iron post, 2½ ins. diam., firmly set, projecting 2 ins. above the ground, with brass cap mkd.
	T 28 S R 9 W S 14   S 13 ———   ——— S 23   S 24  1962
	from which the remains of an original bearing tree

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 28 S., R. 9 W., Willamette Meridian, Oregon**

FEEET	<p style="text-align: center;">A hemlock snag, 34 ins. diam., bears N. 58° W., 31.0 ft. dist., to face, with scribe marks 4 visible on partially healed blaze.</p> <p>and the remains of bearing trees mkd. by person(s) unknown reported by Gawron</p> <p style="text-align: center;">A fir stump, 63 ins. diam., bears S. 12° E., 36.3 ft. dist., with no scribe marks on open blaze.</p> <p style="text-align: center;">A fir, 36 ins. diam., bears S. 51° E., 71.9 ft. dist., no marks visible.</p> <p>and the remains of bearing trees mkd. by Gawron in 1962</p> <p style="text-align: center;">A hemlock stump, 41 ins. diam., bears N. 21° E., 83.5 ft. dist., no marks visible.</p> <p style="text-align: center;">A cedar snag, 40 ins. diam., bears S. 4° W., 101.6 ft. dist., no marks visible.</p> <p>and bearing trees mkd. by person(s) unknown</p> <p style="text-align: center;">A fir, 15 ins. diam., bears N. 32° E., 32.5 ft. dist., with a healed blaze.</p> <p style="text-align: center;">A fir, 11 ins. diam., bears S. 48° E., 31.0 ft. dist., with a healed blaze.</p> <p style="text-align: center;">A fir, 18 ins. diam., bears S. 56¼° W., 13.3 ft. dist., with a healed blaze.</p> <p style="text-align: center;">A fir, 14 ins. diam., bears N. 49¼° W., 15.7 ft. dist., with a healed blaze.</p> <p>From this point, an iron pipe, 1 in. diam., bears North 0.66 ft. dist., reported by Gawron.</p> <hr/> <p>From the cor. of secs. 1, 6, 7, and 12, on the E. bdy. of the Tp.</p> <p>S. 89° 34' 46" W., bet. secs. 1 and 12.</p> <p>Descend gradual W. slope through heavy timber and light undergrowth.</p>
765	Graveled road, 12 ft. wide, bears N. 30° E. and S. 30° W.

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 28 S., R. 9 W., Willamette Meridian, Oregon

FEET	
1210	Ravine, drains N. 50° W., asc. over NE. slope.
1415	Spur, slopes N. 50° W., desc. over NW. slope.
1775	Ravine, drains N. 20° W., across N. slope.
2320	Ravine, drains N. 10° W., asc. over NE. slope.
2634.42	<p>The ¼ sec. cor. of secs. 1 and 12, perpetuated by Forrest J. LaFlamme, Registered Land Surveyor No. 473, in 1962, from original evidence no longer in existence, recorded in the Coos County Surveyor's Office book 10, page 107; monumented with an iron pipe, 2 ins. diam., firmly set, projecting 12 ins. above the ground, from which the remains of a bearing tree mkd. by LaFlamme.</p> <p style="padding-left: 40px;">A fir stump, 52 ins. diam., bears S. 5° W., 49.1 ft. dist., with scribe marks 12 BT visible on open blaze.</p> <p>and bearing trees mkd. by Harvey M. Christiansen, Registered Land Surveyor No. 2603, in 1999, recorded in the Coos County Surveyor's Office book 16 page 104</p> <p style="padding-left: 40px;">A fir, 8 ins. diam., bears N. 42¾° E., 5.9 ft. dist., with illegible scribe marks visible on partially healed blaze.</p> <p style="padding-left: 40px;">A fir, 8 ins. diam., bears S. 37½° E., 4.2 ft. dist., with illegible scribe marks visible on partially healed blaze.</p> <p style="padding-left: 40px;">A fir, 15 ins. diam., bears S. 68½° W., 7.1 ft. dist., with illegible scribe marks visible on partially healed blaze.</p> <p style="padding-left: 40px;">A fir, 9 ins. diam., bears N. 45½° W., 16.8 ft. dist., with illegible scribe marks visible on partially healed blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 28 S R 9 W</p> <p style="margin-left: 100px;">S 1</p> <p style="margin-left: 100px;">1/4 ———</p> <p style="margin-left: 100px;">S 12</p> <p>2002</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Remove the 2 in. diam. iron pipe from the area.</p> <hr/> <p>From the cor. of secs. 1, 2, 11, and 12, perpetuated by Forrest J. LaFlamme, Registered Land Surveyor No. 473, in 1962,</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 28 S., R. 9 W., Willamette Meridian, Oregon**

FEET

recorded in the Coos County Surveyor's Office book 10, page 107, subsequently perpetuated by Clyde F. Mulkins, Registered Land Surveyor No. 2006, in 1993, recorded in the Coos County Surveyor's Office No. 26b62; monumented with an iron rod, 5/8 in. diam., firmly set, projecting 1 in. above the ground, with aluminum cap mkd.

LS 2006			
S	2		S
			1
S 11			S 12
T 28 S			R 9 W
1993			

from which the remains of the original bearing trees

A hemlock stump, size indeterminate, bears S. 20° E.,  
13.9 ft. dist., no marks visible.

A hemlock snag, size indeterminate, bears N. 14° W.,  
19.8 ft. dist., no marks visible.

and the remains of a bearing tree mkd. by LaFlamme in 1962

A fir stump, 50 ins. diam., bears S. 32° W.,  
33.2 ft. dist., with scribe marks S11 BT visible on open  
blaze.

and bearing trees mkd. by Mulkins in 1993

A hemlock, 14 ins. diam., bears N. 25° E., 6.4 ft. dist.,  
with scribe marks T28S R9W S1 BT visible on partially  
healed blaze.

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 28 S., R. 9 W., Willamette Meridian, Oregon**

FEET	
	<p>A fir, 18 ins. diam., bears S. 77¼° E., 17.1 ft. dist., with a healed blaze.</p> <p>A fir, 14 ins. diam., bears N. 29° W., 30.7 ft. dist., with a healed blaze.</p> <p>and a new bearing tree</p> <p>A hemlock, 14 ins. diam., bears S. 59° W., 5.6 ft. dist., mkd. T28S R9W S11 BT.</p> <p>N. 0° 18' 28" E., bet. secs. 1 and 2.</p> <p>Descend NE. slope along W. edge of heavy timber and E. edge of clear cut.</p>
295	Creek, 3 ft. wide, course N. 50° W., asc. over SW. slope.
750	Spur, slopes S. 80° W., desc. over N. slope.
1140	Creek, 30 ft. wide, course S. 50° W., asc. over S. slope.
1430	Dirt road, 18 ft. wide, bears E. and W.
2150	Ridge, bears N. 75° E. and S. 75° W., desc. over N. slope.
2663.40	<p>The ¼ sec. cor. of secs. 1 and 2, perpetuated by C.S. Lehmanowsky, Registered Engineer No. 1768, in 1949, recorded in the Coos County Surveyor's Office No. 26A9, further perpetuated by Forrest J. LaFlamme, Registered Land Surveyor No. 473, in 1962, recorded in the Coos County Surveyor's Office book 10, page 107, subsequently perpetuated by Clyde F. Mulkins, Registered Land Surveyor No. 2006, in 1993, recorded in the Coos County Surveyor's Office No. 26b62; monumented with an iron pipe, 1½ ins. diam., firmly set, projecting 1 in. above the ground, from which the remains of an original bearing tree.</p> <p>A root hole, bears N. 78¼° E., 14.5 ft. dist., with fir log along side, 65 ins. diam., no marks visible.</p> <p>and the remains of a bearing tree mkd. by Lehmanowsky in 1949</p> <p>A fir stump, 48 ins. diam., bears N. 24° W., 50.3 ft. dist., no marks visible.</p> <p>and a bearing tree mkd. by Mulkins in 1993</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 28 S., R. 9 W., Willamette Meridian, Oregon

FEET	
	<p>A fir, 15 ins. diam., bears S. 35° W., 29.8 ft. dist., with a healed blaze.</p> <p>and bearing trees mkd. by person(s) unknown</p> <p>A fir, 23 ins. diam., bears N. 14° E., 4.8 ft. dist., with a healed blaze.</p> <p>A hemlock, 30 ins. diam., bears N. 28° E., 49.5 ft. dist., with no scribe marks visible on partially healed blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 28 S R 9 W</p> <p>1/4</p> <p>S 2   S 1</p> <p>2002</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Remove iron pipe from area.</p> <hr/> <p>N. 0° 21' 01" W., beginning new measurement.</p> <p>Descend NW. slope through heavy timber and light undergrowth.</p>
1110	Creek, 20 ft. wide, course S. 50° W.
1190	Dirt road, 18 ft. wide, bears N. 65° E. and S. 65° W., asc. over steep S. slope.
2637.90	The cor. of secs. 1 and 2, on the N. bdy. of the Tp.
	<hr/> <p>From the cor. of secs. 14, 15, 22, and 23, monumented with an iron post, 2½ ins. diam., firmly set, projecting 8 ins. above the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 28 S R 9 W</p> <p>S 15   S 14</p> <hr/> <p>S 22   S 23</p> <p>1962</p> </div>

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 28 S., R. 9 W., Willamette Meridian, Oregon**

FEET	
	<p>from which the remains of the original bearing trees</p> <p>A fir stump, 75 ins. diam., bears N. 61° E., 35.3 ft. dist., with scribe marks S4 BT visible on open blaze.</p> <p>A fir stump, 60 ins. diam., bears S. 25½° E., 9.6 ft. dist., with scribe marks 23 BT visible on open blaze.</p> <p>A fir stump, 50 ins. diam., bears S. 63° W., 18.9 ft. dist., with scribe marks S22 BT visible on open blaze.</p> <p>A hemlock stump, size indeterminate, bears N. 19° W., 38.6 ft. dist., no marks visible.</p> <p>and the remains of bearing trees mkd. by Gawron in 1962</p> <p>A hemlock stump, size indeterminate, bears N. 55° E., 13.9 ft. dist., with scribe marks T28S R9W S visible on open blaze.</p> <p>A hemlock stump, size indeterminate, bears S. 59° E., 76.6 ft. dist., no marks visible.</p> <p>and bearing trees mkd. by Farmer in 1999</p> <p>A hemlock, 15 ins. diam., bears N. 29½° E., 25.2 ft. dist., with scribe marks T28S R9W S14 BT visible on partially healed blaze. (Record, N. 33° E.)</p> <p>A fir, 8 ins. diam., bears S. 74° E., 24.9 ft. dist., with scribe marks T28S R9W S23 BT visible on partially healed blaze. (Record, S. 68½° E.)</p> <p>A fir, 14 ins. diam., bears S. 23° W., 16.4 ft. dist., with scribe marks T28S R9W S22 BT visible on partially healed blaze. (Record, S. 26½° W.)</p> <p>A fir, 12 ins. diam., bears N. 29¼° W., 29.5 ft. dist., with scribe marks T28S R9W S15 BT visible on partially healed blaze. (Record, N. 31° W.)</p> <p>N. 0° 02' 34" W., bet. secs. 14 and 15.</p> <p>Ascend S. slope through heavy timber and light undergrowth.</p>
480	Graveled road, 20 ft. wide, bears N. 65° E. and S. 65° W.
1435	Top of ascent, slopes S. 80° W., desc. over N. slope.
2651.94	The ¼ sec. cor. of secs. 14 and 15, reestablished by proportionate measurement by John L. Safstrom, Registered Land Surveyor No. 477, in 1961, recorded in the Coos County Surveyor's Office book 10 pages 61 and 62 and is accepted as the corner. There is no remaining evidence of the original corner; monumented with an iron pipe, 1½ ins. diam., firmly set,

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 28 S., R. 9 W., Willamette Meridian, Oregon

FEEET	<p>projecting 5 ins. above the ground, from which the remains of bearing trees mkd. by Safstrom.</p> <p style="padding-left: 40px;">A cedar stump, 33 ins. diam., bears East, 59.8 ft. dist., with scribe marks 1/4 S14 BT visible on open blaze.</p> <p style="padding-left: 40px;">A fir stump, 58 ins. diam., bears N. 50° W., 8.9 ft. dist., with scribe marks 1/4 S15 BT 477 visible on open blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, directly over the iron pipe, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T 28 S R 9 W</p> <p style="margin-left: 100px;">1/4</p> <p style="margin-left: 80px;">S 15   S 14</p> <p style="margin-left: 100px;">2002</p> </div> <p>from which</p> <p style="padding-left: 40px;">A fir, 15 ins. diam., bears N. 18¾° E., 35.9 ft. dist., mkd. 1/4 S14 BT.</p> <p style="padding-left: 40px;">A hemlock, 16 ins. diam., bears S. 74¾° W., 17.8 ft. dist., mkd. 1/4 S15 BT.</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0° 02' 42" W., beginning new measurement.</p> <p>Ascend across SW. slope through heavy timber.</p>
145	<p>Top of ascent, slopes S. 80° W., desc. over NW. slope.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 28 S., R. 9 W., Willamette Meridian, Oregon

FEET									
1390	Graveled road, 15 ft. wide, bears N. 75° E. and S. 75° W.								
1765	Power transmission line, bears N. 70° W. and S. 70° E.								
2085	Graveled road, 10 ft. wide, bears N. 75° W. and S. 75° E. Also Power transmission line, bears same.								
2430	Creek, 4 ft. wide, course N. 68° W.								
2651.77	The cor. of secs. 10, 11, 14, and 15, monumented with an iron post, 2½ ins. diam., firmly set, projecting 2 ins. above the ground, with brass cap mkd.								
	<table style="margin-left: auto; margin-right: auto;"> <tr> <td>T 28 S</td> <td>R 9 W</td> </tr> <tr> <td>S 10</td> <td>S 11</td> </tr> <tr> <td colspan="2" style="text-align: center;">-----</td> </tr> <tr> <td>S 15</td> <td>S 14</td> </tr> </table> <p style="text-align: center;">1993</p>	T 28 S	R 9 W	S 10	S 11	-----		S 15	S 14
T 28 S	R 9 W								
S 10	S 11								
-----									
S 15	S 14								
	from which the remains of an original bearing tree								
	<p style="margin-left: 40px;">A hemlock snag, 43 ins. diam., bears N. 69° E., 26.1 ft. dist., with fragmentary scribe marks visible on open blaze.</p>								
	and bearing trees mkd. by Safstrom in 1961								
	<p style="margin-left: 40px;">A hemlock, 45 ins. diam., bears S. 74° E., 55.1 ft. dist., with a healed blaze.</p>								
	<p style="margin-left: 40px;">A hemlock, 28 ins. diam., bears N. 43° W., 21.8 ft. dist., with a healed blaze.</p>								
	and bearing trees mkd. by Peterson in 1993								
	<p style="margin-left: 40px;">A fir, 6 ins. diam., bears N. 40° E., 23.8 ft. dist., with a healed blaze.</p>								
	<p style="margin-left: 40px;">A fir, 8 ins. diam., bears S. 18° W., 18.5 ft. dist., with a healed blaze.</p>								
	<hr style="width: 60%; margin-left: 0;"/> <p>N. 0° 33' 22" E., bet. secs. 10 and 11.</p>								
	Descend steep NW slope through heavy timber.								

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 28 S., R. 9 W., Willamette Meridian, Oregon**

FEET	
630	East Fork Coquille River, 15 ft. wide, course N. 80° W., asc. over S. slope.
700	Coos Bay Wagon Road, graveled surface, 23 ft. wide, bears S. 80° E. and N. 80° W; Asc. steep S. slope through medium timber and light undergrowth.
2582.05	<p>The ¼ sec. cor. of secs. 10 and 11, reestablished by proportionate measurement by Clyde F. Mulkins, Registered Land Surveyor No. 2006, in 1994, recorded in the Coos County Surveyor's Office No. 26b70, and is accepted as the corner. There is no remaining evidence of the original corner; monumented with an iron rod, 5/8 in. diam., firmly set, projecting 1 in. above the ground, with aluminum cap mkd.</p> <div style="text-align: center;"> <p>LS 2006 T 28 S 1/4 S 10   S 11 R 9 W 1994</p> </div> <p>from which the remains of bearing trees mkd. by Mulkins</p> <p style="padding-left: 40px;">A fir, 11 ins. diam., bears N. 61½° E., 22.7 ft. dist., with illegible scribe marks visible on partially healed blaze.</p> <p style="padding-left: 40px;">A fir stump, 12 ins. diam., bears S. 2½° W., 27.6 ft. dist., with scribe marks 1/4 S10 BT visible on partially healed blaze.</p> <p style="padding-left: 40px;">A fir, 12 ins. diam., bears S. 15½° W., 25.9 ft. dist., with scribe marks 1/4 S10 BT visible on partially healed blaze.</p> <p style="padding-left: 40px;">A fir stump, 17 ins. diam., bears S. 76° W., 24.6 ft. dist., with scribe marks 1/4 S10 BT visible on partially healed blaze.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0° 34' 26" E., beginning new measurement.</p> <p>Descend broken N. slope along W. edge of medium timber and E edge of clear cut.</p>
1160	Dirt road, 18 ft. wide, bears N. 4° E. and S. 22° W.

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 28 S., R. 9 W., Willamette Meridian, Oregon**

FEET													
2300	Graveled road, 18 ft. wide, bears E. and W.												
2582.02	<p>The cor. of secs. 2, 3, 10, and 11, monumented with an iron post, 2½ ins. diam., firmly set, projecting 6 ins. above the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr> <td colspan="2">T 28 S</td> <td colspan="2">R 9 W</td> </tr> <tr> <td style="border-right: 1px solid black;">S 3</td> <td style="border-right: 1px solid black;"></td> <td style="border-right: 1px solid black;">S 2</td> <td></td> </tr> <tr> <td colspan="2" style="border-top: 1px solid black; border-right: 1px solid black;">S 10</td> <td colspan="2" style="border-top: 1px solid black; border-right: 1px solid black;">S 11</td> </tr> </table> <p>1977</p> </div> <p>from which the remains of an original bearing tree</p> <p style="padding-left: 40px;">A fir snag, 48 ins. diam., bears N. 63° E., 13.2 ft. dist., no marks visible.</p> <p>and bearing trees mkd. by Wofford, in 1977</p> <p style="padding-left: 40px;">A hemlock, 15 ins. diam., bears N. 31¼° E., 16.5 ft. dist., with a healed blaze.</p> <p style="padding-left: 40px;">A cedar, 9 ins. diam., bears S. 68¼° E., 16.8 ft. dist., with a healed blaze. (Record, 15.2 ft. dist.)</p> <p style="padding-left: 40px;">A hemlock, 30 ins. diam., bears N. 1° W., 8.8 ft. dist., with a healed blaze. (Record, 9.2 ft. dist.)</p> <p>and a new bearing tree</p> <p style="padding-left: 40px;">A fir, 16 ins. diam., bears S. 33° W., 33.3 ft. dist., mkd. T28S R9W S10 BT.</p> <hr/> <p>From the cor. of sec. 1, 2, 11, and 12.</p> <p>S. 88° 33' 22" W., bet. secs. 2 and 11.</p> <p>Across broken N. slope, along N. edge of medium timber and S. edge of clear cut.</p>	T 28 S		R 9 W		S 3		S 2		S 10		S 11	
T 28 S		R 9 W											
S 3		S 2											
S 10		S 11											
365	Creek, 8 ft. wide, course N. 10° E., asc. over NE. slope.												
555	Spur, slopes N. 20° E., desc. over NW. slope.												
2571.10	<p>The ¼ sec. cor. of secs. 2 and 11, perpetuated by Clyde F. Mulkins, Registered Land Surveyor No. 2006, in 1993, recorded in the Coos County Surveyor's Office 26b62, monumented with an iron rod, 5/8 in. diam., firmly set, projecting 8 ins. above the ground, with aluminum cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr> <td colspan="2">LS 2006</td> </tr> <tr> <td style="border-right: 1px solid black;">S 2</td> <td></td> </tr> <tr> <td colspan="2" style="border-top: 1px solid black;">1/4</td> </tr> <tr> <td style="border-right: 1px solid black;"></td> <td>S 11</td> </tr> </table> <p>T 28 S R 9 W 1993</p> </div> <p>from which the remains of an original bearing tree</p>	LS 2006		S 2		1/4			S 11				
LS 2006													
S 2													
1/4													
	S 11												

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 28 S., R. 9 W., Willamette Meridian, Oregon**

FEET	
	<p>A hemlock stump, 30 ins. diam., bears N. 24° E., 29.0 ft. dist., with fragmentary scribe marks visible on open blaze.</p> <p>and the remains of bearing trees mkd. by Mulkins in 1993</p> <p>A fir, 15 ins. diam., bears N. 5° E., 14.9 ft. dist., with a healed blaze.</p> <p>A hemlock, 14 ins. diam., bears N. 21° E., 26.4 ft. dist., with scribe marks 4 S2 BT visible on partially healed blaze.</p> <p>A root hole, bears S. 34° E., 21.7 ft. dist., with fir log alongside, 15 ins. diam., with scribe marks 1/4 S11 BT visible on partially healed blaze.</p> <p>A fir, 21 ins. diam., bears S. 68½° W., 16.8 ft. dist., with a healed blaze.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 88° 29' 23" W., beginning new measurement.</p> <p>Ascend NE. slope along N. edge of medium timber and S. edge of clearcut.</p>
610	Spur, slopes N. 30° E., desc. over NW. slope.
1140	Creek, 3 ft. wide, course N. 20° W., asc. over NE. slope.
1410	Spur, slopes N. 30° W., desc. over NW. slope.
1705	Graveled road, 18 ft. wide, bears N. 15° E. and S. 22° W.
2345	Ravine, drains N. 35° W., asc. over NE. slope.

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 28 S., R. 9 W., Willamette Meridian, Oregon**

FEET	
2415	Spur, slopes N. 20° E., desc. over NW. slope.
2596.58	The cor. of secs. 2, 3, 10, and 11. <hr/>
	N. 0° 45' 08" W., bet. secs. 2 and 3. Descend N. slope through heavy timber.
220	Lost Creek, 30 ft. wide, course N. 76° W., asc. extremely steep, precipitous S. slope.
1930	Graveled road, 15 ft. wide, bears N. 55° E. and S. 20° W.; Desc. across broken NW. slope.
2588.48	The ¼ sec. cor. of secs. 2 and 3, perpetuated by Clyde F. Mulkins, Registered Land Surveyor No. 2006, in 1993, recorded in the Coos County Surveyor's Office 26b62, monumented with an iron rod, 5/8 in. diam., firmly set, projecting 3 ins. above the ground, with aluminum cap mkd.  <div style="text-align: center;">           1993            1/4            S 3   S 2            LS 2006         </div> from which the remains of the original bearing trees  A fir stump, 36 ins. diam., bears N. 33° E., 32.0 ft. dist., no marks visible. (Record, 30.4 ft. dist.).  A root hole, bears N. 50° W., 2.0 ft. dist., with uprooted fir stump alongside with fragmentary scribe marks visible on open blaze.  and bearing trees mkd. by Mulkins in 1993  A fir, 20 ins. diam., bears S. 53° E., 4.5 ft. dist., with a healed blaze.  A fir, 14 ins. diam., bears S. 82° W., 9.1 ft. dist., with a healed blaze.  A fir, 17 ins. diam., bears N. 51½° W., 21.1 ft. dist., with a healed blaze.  <hr/>

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 28 S., R. 9 W., Willamette Meridian, Oregon**

FEET	
	N. 1° 18' 35" W., beginning new measurement.
	Descend across broken NW. slope along E. edge of heavy timber and W. edge of clear cut.
1385	Dirt road, 10 ft. wide, bears N. 60° E. and S. 60° W.
1590	Creek, 2 ft. wide, course W., asc. over S. slope.
1745	Spur, slopes W., desc. over NW. slope.
2605	Creek, 2 ft. wide, course W., asc. over SW. slope.
2903.32	The cor. of secs. 2 and 3, on the N. bdy. of the Tp.
<hr/>	
	From the cor. of secs. 14, 15, 22, and 23.
	N. 87° 48' 04" W., bet. secs. 15 and 22.
	Ascend across SE. slope through medium timber and light undergrowth.
275	Spur, slopes S. 30° E., desc. over SW. slope.
570	Creek, 6 ft. wide, course S. 30° E., asc. over SE. slope.
1365	Spur, slopes S., desc. over SW. slope.
2085	Graveled road, 15 ft. wide, bears S. 30° E. and N. 30° W.
2619.41	The ¼ sec. cor. of secs. 15 and 22, monumented with an iron post, 2½ ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd.
	T 28 S R 9 W S 15 1/4 ——— S 22  1962
	from which the remains of an original bearing tree
	A decayed fir stump, size indeterminate, bears S. 40° W., 11.2 ft. dist., no marks visible.

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 28 S., R. 9 W., Willamette Meridian, Oregon**

FEET	<p>and a bearing tree mkd. by C.S. Lehmanowsky, Registered Engineer No. 1768, in 1959, recorded in the Coos County Surveyor's Office Book 9, page 238</p> <p style="padding-left: 40px;">A hemlock, 32 ins. diam., bears S. 20° W., 10.5 ft. dist., with a healed blaze.</p> <p>and bearing trees mkd. by Gawron in 1962</p> <p style="padding-left: 40px;">A yew, 17 ins. diam., bears N. 64½° E., 13.5 ft. dist., with a healed blaze. (Record, N. 62° E., 14.5 ft. dist.).</p> <p style="padding-left: 40px;">A yew, 11 ins. diam., bears S. 47½° E., 12.5 ft. dist., with a healed blaze. (Record, S. 45° E.).</p> <hr/> <p>From the ¼ sec. cor. of secs. 15 and 16, perpetuated from original evidence no longer in existence by C.S. Lehmanowsky, Registered Engineer No. 1768, in 1952, recorded in the Coos County Surveyor's Office No. 26a13, subsequently perpetuated by Forrest J. LaFlamme, Registered Land Surveyor No. 473, in 1962, recorded in the Coos County Surveyor's Office book 10 page 169, further perpetuated by Larry LaFlamme, in 1977, recorded in line book 53 page 70, record held at Plum Creek Timber Co. office in Coos Bay, Oregon; monumented with an iron post, ¼ in. diam., firmly set, projecting 2 ins. above the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin-left: auto; margin-right: auto;"> <tr> <td style="padding: 0 5px;">G</td> <td style="padding: 0 5px;">P</td> </tr> <tr> <td style="padding: 0 5px;">¼ 16</td> <td style="padding: 0 5px;">  15</td> </tr> <tr> <td style="padding: 0 5px;"></td> <td style="padding: 0 5px;">28-9</td> </tr> <tr> <td style="padding: 0 5px;"></td> <td style="padding: 0 5px;">1977</td> </tr> </table> </div> <p>from which the remains of a bearing tree mkd. by Lehmanowsky in 1952</p> <p style="padding-left: 40px;">A hemlock snag, 27 ins. diam., bears S. 79¼° E., 11.0 ft. dist., with scribe marks 1/4 B visible on partially healed blaze.</p> <p>and a bearing tree mkd. by LaFlamme in 1962</p> <p style="padding-left: 40px;">A fir, 43 ins. diam., bears N. 19° W., 29.3 ft. dist., with no scribe marks visible on decayed blaze.</p> <p>and new bearing trees</p>	G	P	¼ 16	15		28-9		1977
G	P								
¼ 16	15								
	28-9								
	1977								

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 28 S., R. 9 W., Willamette Meridian, Oregon

FEET																	
	<p>A fir, 5 ins. diam., bears N. 82¾° E., 30.1 ft. dist., mkd. 1/4 S15 BT.</p> <p>A fir, 7 ins. diam., bears N. 67½° W., 40.2 ft. dist., mkd. 1/4 S16 BT.</p> <p>N. 0° 19' 10" E., bet. secs. 15 and 16.</p> <p>Ascend S. slope through medium timber and moderate undergrowth.</p>																
885	Ridge, bears N. 65° E. and S. 65° W., desc. over N. slope.																
1675	Power transmission line, bears S. 75° E. and N. 75° W.																
2594.15	<p>The cor. of secs. 9, 10, 15, and 16, perpetuated by person(s) unknown, subsequently perpetuated by Larry LaFlamme, in 1977, recorded in line book 53, page 70, record held at Plum Creek Timber Co. office in Coos Bay, Oregon; monumented with an iron pipe, 1 in. diam., firmly set, projecting 8 ins. above the ground, from which the remains of the original bearing trees</p> <p>A badly decayed hemlock stump, size indeterminate, bears N. 80° E., 6.5 ft. dist., with no scribe marks visible on decayed blaze. (Record, S. 85° E., 5.9 ft. dist.)</p> <p>A root hole, bears N. 70° W., 12.5 ft. dist., with down chinquapin log alongside with no scribe marks visible on decayed blaze.</p> <p>and bearing trees mkd. by LaFlamme in 1977</p> <p>A fir, 14 ins. diam., bears S. 49° E., 13.0 ft. dist., with a healed blaze.</p> <p>A fir, 16 ins. diam., bears S. 34° W., 22.4 ft. dist., with an X at breast height and a healed blaze.</p> <p>A fir, 16 ins. diam., bears N. 89° W., 36.6 ft. dist., with a healed blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, directly over the iron pipe, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr> <td colspan="2">T 28 S</td> <td colspan="2">R 9 W</td> </tr> <tr> <td>S 9</td> <td> </td> <td>S 10</td> <td></td> </tr> <tr> <td colspan="2">-----</td> <td colspan="2">-----</td> </tr> <tr> <td>S 16</td> <td> </td> <td>S 15</td> <td></td> </tr> </table> <p>2002</p> </div> <p>from which</p> <p>A fir, 11 ins. diam., bears N. 39° E., 5.2 ft. dist., mkd. T28S R9W S10 BT.</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <hr/>	T 28 S		R 9 W		S 9		S 10		-----		-----		S 16		S 15	
T 28 S		R 9 W															
S 9		S 10															
-----		-----															
S 16		S 15															

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 28 S., R. 9 W., Willamette Meridian, Oregon**

FEET	
	From the cor. of secs. 10, 11, 14, and 15.
	S. 89° 56' 22" W., bet. secs. 10 and 15.
	Descend across NW. slope through heavy timber and moderate undergrowth.
390	Creek, 10 ft. wide, course N. 10° E., asc. over steep E. slope.
1210	Spur, slopes N. 45° W., desc. over NW. slope.
2170	Creek, 6 ft. wide, course N., asc. over NE. slope.
2608.09	The ¼ sec. cor. of secs. 10 and 15, perpetuated by Clyde F. Mulkins, Registered Land Surveyor No. 2006 in 1995, recorded in the Coos County Surveyor's Office No. 26b70; monumented with an iron rod, 5/8 in. diam., firmly set, projecting 2 ins. above the ground, with aluminum cap mkd.
	LS 2006 T 28 S S 10 1/4 ——— S 15 R 9 W 1994
	from which the remains of the original bearing trees
	A decayed hemlock stump, size indeterminate, bears S. 53° W., 27.1 ft. dist., no marks visible.
	A hemlock stump, 32 ins. diam., bears N. 13° W., 38.3 ft dist., with a healed blaze.
	and bearing trees mkd. by Mulkins
	A fir, 17 ins. diam., bears N. 47½° E., 33.8 ft. dist., with illegible scribe marks visible on partially healed blaze.
	A fir, 19 ins. diam., bears S. 82° E., 41.5 ft. dist., with a healed blaze.
	A fir, 9 ins. diam., bears S. 33° W., 19.6 ft. dist., with a healed blaze.
	A fir, 18 ins. diam., bears S. 88° W., 7.6 ft. dist., with a healed blaze.
	—————
	N. 89° 26' 56" W., beginning new measurement.
	Descend over NW. slope through heavy timber and light undergrowth.
1125	Ravine, drains N. 10° W., asc. over NE. slope.
2648.98	The cor. of secs. 9, 10, 15, and 16.
	—————

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 28 S., R. 9 W., Willamette Meridian, Oregon**

FEEET

From the cor. of secs. 16, 17, 20, and 21, monumented with an iron rod, 1 in. diam., firmly set, projecting 3 ins. above the ground, with aluminum cap mkd.

G P	
17	16
20	21
T 28	R 9
1977	

from which the remains of the original bearing trees

A cedar, 43 ins. diam., bears S. 55° W., 38.3 ft. dist., with a healed blaze.

A fir stump, 48 ins. diam., bears N. 66° W., 13.9 ft. dist., with a healed blaze.

and the remains of a bearing tree mkd. by Gearhart

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 28 S., R. 9 W., Willamette Meridian, Oregon

FEET	
	<p>A cedar stump, size indeterminate, bears N. 36¼° E., 33.8 ft. dist., no marks visible.</p> <p>and bearing trees mkd. by Farmer in 1999</p> <p>A fir, 11 ins. diam., bears N. 74¼° E., 43.5 ft. dist., with illegible scribe marks visible on partially healed blaze.</p> <p>A fir, 10 ins. diam., bears S. 53° E., 11.0 ft. dist., with illegible scribe marks visible on partially healed blaze.</p> <p>and a bearing tree mkd. by Farmer in 1999, not recorded in the field notes</p> <p>A fir, 10 ins. diam., bears N. 52° W., 13.0 ft. dist., with illegible scribe marks visible on partially healed blaze.</p> <p>N. 1° 10' 25" W., bet. secs. 16 and 17.</p> <p>Ascend SE. slope through medium timber and light undergrowth.</p>
720	Graveled road, 18 ft. wide, bears S. 30° E. and N. 30° W.
1040	Ridge, bears E. and W., desc. over NW. slope.
2619.93	<p>The ¼ sec. cor. of secs. 16 and 17, perpetuated by Larry LaFlamme, in 1977, recorded in line book 53, page 70, record held at Plum Creek Timber Co. office in Coos Bay, Oregon; monumented with an iron post, ¾ in. diam., firmly set, projecting 6 ins. above the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>G P</p> <p>1/4 17   16</p> <p>T 28 R 9</p> <p>1977</p> </div> <p>from which the remains of an original bearing tree</p> <p>A decayed hemlock stump, 35 ins. diam., bears S. 88° W., 7.9 ft. dist., with scribe marks 1/4 visible on partially healed blaze.</p> <p>and a bearing tree and a bearing object mkd. by LaFlamme in 1977</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 28 S., R. 9 W., Willamette Meridian, Oregon**

FEET	
	<p>A point on bedrock outcrop, 10' x 10', bears S. 7½° E., 19.1 ft. dist., to PK nail in sec. tag.</p> <p>An alder, 19 ins. diam., bears N. 4¼° W., 26.0 ft. dist., with X at breast height.</p> <hr/> <p>From the cor. of secs. 16, 17, 20, and 21.</p> <p>S. 87° 49' 13" W., bet. secs. 17 and 20.</p> <p>Ascend steep SE. slope through medium timber and light undergrowth.</p>
165	Spur, slopes S. 40° W., desc. over SW. slope.
390	Creek, 4 ft. wide, course S. 10° W., asc. over SE. slope.
515	Spur, slopes S. 10° W., desc. over SW. slope.
665	Ravine, drains S., asc. over E. slope.
910	Spur, slopes S. 15° E., desc. over SW. slope.
1270	Ravine, drains S., asc. over steep E. slope.
1980	Spur, slopes S., desc. over SW. slope.
2560	Ravine, drains S. 10° E., asc. over steep SE. slope.
2863.89	<p>The ¼ sec. cor. of secs. 17 and 20, perpetuated by Larry LaFlamme, in 1990, recorded in line book 23, page 40, record held at Plum Creek Timber Co. office in Coos Bay, Oregon, monumented with an iron post, ¾ in. diam., firmly set, projecting 1 in. above the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>G P</p> <p>S 17</p> <p>1/4 COR ———</p> <p>S 20</p> <p>T 28 R 9</p> <p>1990</p> </div> <p>from which the remains of an original bearing tree</p> <p>A fir snag, 74 ins. diam., bears N. 11° E., 61.4 ft. dist., to face, no marks visible.</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 28 S., R. 9 W., Willamette Meridian, Oregon**

F E E T	<p>and the remains of bearing trees mkd. by LaFlamme in 1990</p> <p style="padding-left: 40px;">A cedar snag, 24 ins. diam., bears N. 44¾° E., 30.3 ft. dist., with X at breast height.</p> <p style="padding-left: 40px;">A cedar stump, 20 ins. diam., bears S. 20° W., 44.5 ft. dist., no marks visible.</p> <p style="padding-left: 40px;">A cedar stump, 22 ins. diam., bears S. 82½° W., 37.4 ft. dist., with X at breast height.</p> <p>and new bearing trees</p> <p style="padding-left: 40px;">A cedar, 9 ins. diam., bears N. 37° E., 17.3 ft. dist., mkd. 1/4 S17 BT.</p> <p style="padding-left: 40px;">A fir, 11 ins. diam., bears N. 16½° W., 19.4 ft. dist., mkd. 1/4 S17 BT.</p> <hr style="width: 60%; margin: 20px auto;"/> <p style="text-align: center;"><b>GENERAL DESCRIPTION</b></p> <p>The lands encompassed within this survey are located in Coos County, Oregon, eight miles East of the community of Sitkum. Access to this area is by the Coos Bay Wagon Road, various Bureau of Land Management maintained roads, and numerous dirt and gravel logging roads. Elevations in the area range from about 1400 feet above sea level to almost 2800 feet.</p> <p>The area is drained by Camas Creek, Lost Creek, Lauch Creek, and various unnamed tributaries, all of which flow into the East Fork Coquille River. The soil in this region is composed of rocky clay. Vegetation in the area is consistent with western Oregon rainforest, with timber of fir, hemlock, cedar, yew, alder, maple, and myrtle. The undergrowth consists of vine maple, salmonberry, blackberry, Oregon grape, nettles, poison oak, various ferns, and young timber.</p> <p>The ruggedness of this area makes these lands prime habitat for various animals such as Roosevelt elk, black-tail deer, black bear, and coyotes.</p> <p>The area has been used primarily for timber production. There were no mineral deposits or evidence of mining noted during this survey.</p> <p>The mean magnetic declination is 18° East, as shown on the United States Geological Survey, 7½ minute quadrangle "SITKUM, OREGON," provisional edition, dated 1990.</p>
---------	---