TOWNSHIP 20 RANGE 08 POINT IDENTIFIER # 100678

PRIMARY CORNER DESCRIPTION East ¼ Corner Sec. 1 only, T20-9

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

BLM dependent resurvey by Thomas A. Tillman & Joseph S Gawron, under Group # 306, Surveyed May 1953 - Oct. 1954 (DCSO recs Vol. 29 Page(s) 12480

Point for the ¼ sec. cor. of sec. 1 only, at proportionate distance on th E bdy of sec. 1.
Set an iron post, 3 ft. long, 1" dia., 28" in the ground, with brass cap marked: ?

¼ S1?
1953

from which
A maple, 16" dia., bears S.67?W., 24 lks., mkd: ¼ S1 BT.
A maple, 13" dia., bears N.12¼?W., 82 lks., mkd: ¼ S1 BT.

Ronald L Rice - For: Oxbow Timber 1 LLC - Mar 2015 - M169-27

Found - 1953 GLO brass cap, With the following accessories:
24" maple bears S.67°W., 15.8' healed face.
22" maple bears N.12¼°W., 54.1' - healed face.

Jerry Estabrook - For: Roseburg Resources Co. - 8/2020 - M177-40

Found - A 1" iron pipe with 2 1/2" brass cap marked "¼ S1 1953" per 1953 BLM survey.
Set - New steel post along side.
Fd BTs - A 25" Maple with healed face and tag bears S.67°W., 15.8'.
A 25" Maple with healed face & tag bears N.12°15'W., 54.1'.
LAT. AND LONG. PER GARMIN ETREX HAND HELD GPS: NOT SURVEY GRADE N: 43°51'47.8" W: 123°42'12.0"