

TOWNSHIP 30 RANGE 02 POINT IDENTIFIER # 100640

PRIMARY CORNER DESCRIPTION W. 1/4 Cor. Sec. 6 only

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Fred Mensch, Deputy Surveyor, under Contract #782, dated Dec. 1, 1908 - (DCSO records Vol. 16 Page(s) 6791)

-----

A Fir 36" dia., for ¼ sec. cor. on W. bdy. of sec. 6. I mark ¼ S6 on E. side, from which

A Fir 30" dia., bears N.56°E., 68 lks. dist. mkd. ¼ S6 BT.

A Fir 24" dia., bears S.5°E., 93 lks. dist. mkd. ¼ S6 BT.

Douglas Co. Surveyors Office - James Byron, Deputy - Mike Darby; Wm. Stoffel, crew - Dec. 1962 - C.S. File 52/126-88

-----

Found Orig. corner tree and both original BTs. Each shows good scars and check OK.

Set brass cap at corner along East edge of corner tree and marked: County Surveyors Office

T	30	S
R	1/4	R
3	S 6	2
W		W

West

1962

New BT - 7" R.Fir, bears S.38°E., 41.9', scribed ¼ S6 CS BT.

BLM resurvey by Peter Peterson and Daniel Berry under Group #749, surveyed July/Aug. 1971 (DCSO records Vol. 36 Page(s) 14914-15)

-----

The ¼ sec.cor. of sec. 6 only, perpetuated and recorded by Byron in 1962, monumented by a Fir 40" dia., with healed blaze on W. face, from which the original bearing trees:

A Fir 42" dia., bears N.56°E., 68 lks. dist., with healed blaze.

A Fir 34" dia., bears S.5°E., 93 lks. dist., with healed blaze.

and a bearing tree and reference monument by Byron:

A Fir 8" dia., bears S.38°E., 65 lks. dist. with healed blaze.

An Iron post 1½" dia., firmly set, protruding 18" above ground, bears East, 3 lks. dist., with brass cap properly marked.

Fd. OK, Nov. 1984 by H. Johnstone - M 97-65