

Dependent Resurvey of the Sub. of T. 25 S., R. 3 W.

CHAINS

A fir, 40 ins. diam., bears N.84½°E., 110 lks. dist., with partial scribe marks visible on portion of old blaze which has been previously uncovered. (A bearing tree marked by the county surveyor in 1914.)

Other bearing trees marked by the county surveyor in 1939, the blazes on which are covered with pitch and almost overgrown, stand as follows:

A fir, 14 ins. diam., bears N.35¼°E., 41 lks. dist.

A fir, 24 ins. diam., bears S.35½°E., 177 lks. dist.

A fir, 54 ins. diam., bears S.2½°W., 121 lks. dist.

A fir, 10 ins. diam., bears N.57½°W., 33 lks. dist.

Land, mountainous.

Soil, sandy loam and rocky clay; 2d and 3d rate.

Timber, fir, hemlock, cedar, alder, maple, pine, yew, chinquapin, madrona, and dogwood.

Undergrowth, vinemaple, willow, slickleaf, manzanita, salmonberry, arrowwood, bracken, hazel, and lilac.

From the cor. of secs. 3, 4, 9, and 10

S. 84° 12' W., bet. secs. 4 and 9.

Asc. 12 ft. over NE. slope, through heavy timber and dense undergrowth in logged area.

4.00 A spur, slopes N.15°W.; desc. 73 ft. over NW. slope.

10.00 A branch, 20 lks. wide, course N.15°W.; asc. 81 ft. over NE. slope.

19.00 A spur, slopes N.15°W.; desc. 153 ft. over rolling broken W. slope.

47.60 The ¼ sec. cor., a dead red cedar, 6 ins. diam., mkd. ¼ S 4 C S on N., and S 9 on S. side.

I remove this dead cedar tree and at point for corner,

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for ¼ sec. cor., with brass cap mkd.

¼  $\frac{S4}{S9}$   
1944

from which

A cedar, 8 ins. diam., bears N.40°E., 6 lks. dist., mkd. ¼ S 4 T 25 S R 3 W C S B T. (A county surveyor's B.T.)

A cedar, 6 ins. diam., bears S.32°W., 11 lks. dist., mkd. ¼ S 9 T 25 S R 3 W C S B T. (A county surveyor's B.T.)

This ¼ sec. cor. was established in 1940 by the county surveyor and duly recorded. I therefore accept it for control of this dependent resurvey.

Thence

S. 84° 32' W., with new measurement.

Desc. 63 ft. over SW. slope.