

Recorded
By H. L. Eppstein
see V. 17 E. 36
Witness
G. G. Stewart
Apr. 18, 1936
by Arthur Beyer P.C.S.
wit. S. W. Cook.
Joe Winniford

4 Cor. Bet 17 & 20; Stake set by G. G. Stewart on
Jan. 25, 1923. Marked ^{14" Fir N 66° W 29° feet}
6" W.O.S 9° W 17 1/2 "

1/2 Sec. Cor 28, 29, 32 & 33 Reset from stump of orig BT.

in Sec 32- other BT's destroyed. Marked new B.T.'s as

follows W. Oak, 12" N. 75° E. 32 ft. 12" B. Oak S 44° W 9.4 ft.
W. Oak, 8" S 16° E 11.4 ft 13" Fir N. 30° W 34.4 ft.

N.W. Corner of the E. Williamson D.L.C. No 48
Location identified from an oak stake bearing correct scribe
marks. This is evidently the corner as renewed by surveyor
Briggs in 1892, although the bearing trees are down & butt section
burned off. Checks for bearing & distance. Drove a 3/4" iron pipe
along side. Blazed & scribed an Oak 42" diam S 60° W 44.0 ft.

#####

S.E. Cor. of the E Williamson D.L.C.
All evidence of the original corner destroyed or obliterated
A 3/4" x 36" iron pipe set for corner by proportional measurements
between the S.W. cor of D.L.C. #48 & the N.E. Cor of D.L.C. 59
No trees or objects available for reference.

#####

N.W. Corner of the E Williamson D.L.C. #48
All evidences of the original corner & of the corner set by
surveyor Briggs in 1892 have been destroyed or obliterated.
A 3/4" x 36" iron pipe driven for the corner using proportion distance
as obtained & computed through the tie given in the deed of the
property (S.W. Cor.) now owned by C. A. Goff & distances as called
for in the original descriptions of D.L.Cs. No 46, 47 & 48. An ash 16" diam
bears N 87° W 92.7 ft. & an ash 16" diam bears S 25° W 26.7 ft, both
blazed & scribed C 147 & 48 & C.S. B.T.

#####

Interior Angle Corner on the West Boundary of the E Williamson
D.L.C. No 48. This corner is located at an anchor post & fence corner
The bearing trees as set by Surv. Briggs were identified & checked for
bearing & distance. One had been cut & sprouted but when the old
stump was chopped out the scribe marks were plain. Drove a 3/4" x 36" iron pipe
for the corner from which an Oak 8" diam bears S 24° E. 16.6 ft. & an Oak
18" diam, bears N 13° W 23 ft. both blazed & scribed C 148 C.S. B.T. This
is identical with Ext. angle corner on the South Boundary of D.L.C. 47

#####

Exterior Angle Corner on West Boundary of the E Williamson
D.L.C. No 48.

All traces of this corner have been destroyed. Its position
comes in the edge of a prune orchard & was located by
measuring 54.1 feet. (82 lks) North of the N.E. corner of the
Jas Cline D.L.C. No 49 which is a sandstone 5" x 12" x 12" above
the ground as described in the original field notes. Drove
a 3/4" x 36" iron pipe for corner. There were no trees available
which were suitable for use as bearing trees

Ben. B. Irving Dep Co Surveyor
Witness { NE RIC HARADSON
Jas McHugh II

Recd - V 15 E 11

25-6

Ben B. Irving D.C.S.
Witness { NE Richardson
Jas Mc Hugh 11

✓ E 11
✓ Rec'd ✓

✓ N.E. Corner of the Jos C line D.L.C. No 49.

The Sandstone 32"x12"x12" above ground was in place as described in the original field notes. No suitable bearing trees were available. Drove a 3/4"x36" iron pipe along side the corner Rock. This corner is located in a fence an mile along side the County road between Oakland & Elkton on the West side of Calapooia Creek.

#####

✓ N.W. Corner of the J.W. Knott D.L.C. No 58.

Original stone in place, all bearing trees destroyed. Drove an iron pipe 3/4" dia. alongside stone. An ash 8" diam. bears N 50° E 35 ft. blazed & scribed NE Cor C158 C.S.B.T.

#####

✓ S.W. Corner of the J.H. Medley D.L.C. No ~~48~~ 56

All evidence of the original corner destroyed or obliterated. A 3/4" x 36" iron pipe set for the corner using a tie given in the deed of property to G.M. Leeper from bearing tree (now down & rotten) given as the corner on the south boundary of the County Road. An Oak 10" diam. bears N 8° E 94 ft. Blazed & scribed SW Cor C146 C, S, B, T.

#####

✓ 1/4 Cor N. Side Sec. 5, T25S; R.6.W. = 1/4 Sec cor bet 32/5, 24" Alder S. 50° 20' W. 49.5 still standing but partly decayed, - Found 5"x5"x18" Rock - New trees set, 8" Fir N. 72° W. 37.7 ft. & 8" Forked Ash S. 57° E. 35.3 ft.

✓ 1/4 Cor bet sec's 4 & 5, T25S; R6W - Set 1/2" Iron Bar - Marked New trees - 18" Black Oak S 27° E 131.5 ft. & 18" White Oak N 85 1/2° E. 145.0 (ft)

✓ Cen. Sec. 5, T25S; R6W. Set 1/2" G.I. Pipe 0 ft. wh. 26" Fir brs. S. 8° E. 72.2 ft. & 26" Fir brs. N 37 1/2° E. 63. ft.

183.

Willis M. Asstland
ore. State by.
Jan. 1942