

Douglas County Surveyor's Record of
Government Corners Renewed

T 25 1/2 S T. S. R 3 E R. W. W. M.

MOORE-CHAPMAN CO., EUGENE, ORE. 97101

Kristian DeGroot,
PLS 1941
For: USFS
Crew Les Fanning,
Matt Dixon,
& Aaron Fanning
March 1998 -
C.S. File 65/20-8 & 9

1/4 Cor. Sec. 35 & Sec. 2, T26-3E 1
Found - Original corner tree, a 35" Fir snag, ± 22 ft. tall with healed faces on the North and South sides.
27" Fir bears N.8°E., 53.5 ft. with a healed blaze. 1931
34" Fir snag ± 20 ft. tall bears S.15°E., 34.0 ft. with a healed blaze (Rec. S.21°E.) 1931
Set - 2 1/2"x30" alum. pipe, 24" in the ground in a 48" dia. mound of stone, base to top with a 3 1/4" alum. cap stamped:
U.S. DEPT. OF AGRICULTURE FOREST SERVICE
T26S R3E
1/4 S2 RM
N.86°22'W
← 15.00 FT.
bears S.86°22'E., 15.00 ft.
10" Fir bears S.10°W., 18.0 ft. scribed "1/4 S2 B1" with a brass washer stamped "PLS 1941" nailed into the lower blaze
Paint a 6" red band and BT face red and nail USFS "BEARING TREE" and "LAND SURVEY MONUMENT" signs to all BTs.

Cor. Secs. 35 & 36; & Secs. 1 & 2, T26-3E 2
Found - 2" O.D. iron pipe, firmly set, projecting 8" above the ground with a 2 1/2" brass cap properly stamped. GLO 1930
34" Fir bears N.10°E., 50.8 ft. with a healed blaze. 1931
22" Fir bears S.18°E., 150.5 ft. with illegible scribe marks visible on a partially healed blaze.
A root hole bears S.55°W., 30.4 ft.
12" Fir snag bears N.30°W., 6.6 ft. with illegible scribe marks visible on a partially healed blaze.
New BTs - 12" Fir bears N.61°W., 19.4 ft. scribed: "T25 1/4 S R3E S35 BT" on a double blaze with a brass washer stamped "PLS 1941" nailed into the lower face.
13" Fir bears S.17°W., 6.8 ft. scribed: "T26S R3E S2 BT" on a double blaze with a brass washer stamped "PLS 1941" nailed into the lower face.
Paint a 6" red band and BT face red and nail USFS "BEARING TREE" and "LAND SURVEY MONUMENT" signs to all BTs.