

Douglas County Surveyor's Record of
Government Corners Renewed

T. 30 S. T. S. R. 8 W. R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

(continued)

New BT's: 8" Cedar S.13°E. 35.6 ft. Mkd: T30S R8W S27 CS BT.
16" D.Fir N.26°E. 16.6 ft. Mkd: T30S R8W S22 CS BT.
Orig. 16" D.Fir S.25°W. 18.5 ft. Mkd: T30S R8W S28 CS BT.

1/4 Section Corner to Sections 25 and 36.

Found - Rock Mkd: "1/4" on N. face, 14"x13"x8", as called for.
Orig. 8", now 37" Fir S.33°W. 52.8 ft., open & shows
good "S" scribe.

No trace of other BT.

Set - Brass Cap at Cor. Mkd: County Surveyor's T30S R8W 1/4 S 25
Set Rock alongside. Office, 1965 S 36

New BT's: 9" D.Fir S.8°W. 8.7 ft. Mkd: 1/4 S36 CS BT.
8" D.Fir N.30°W. 9.0 ft. Mkd: 1/4 S25 CS BT.

Note - This corner lies approx. 25.0 ft. East of top of small spur,
ridge sloping S.20°E.

Section Corner to Sections 25 - 26 - 35 - 36.

Found - Orig. 16", now 24" Fir Snag N.36°E. 49.5 ft., dirt fill
around base make it impossible to open.

Orig. 12", now 15", Snag, S.60°E. 28.4 ft., open & shows "T30S".

Set - Brass Cap at Cor. Mkd: County Surveyor's T30S R8W S 26 S 25
Office, 1965 S 35 S 36

New BT's: 16" W.Fir N.50°W. 20.4 ft. Mkd: T30S R8W S26 CS BT.

14" W.Fir N.24°E. 46.6 ft. Mkd: T30S R8W S25 CS BT.

12" W.Fir S. 3°W. 51.6 ft. Mkd: T30S R8W S35 CSBT.

No tree close in section 36.

Note - From our Brass Cap, R. H. Gee's I.P., recorded in Ren. #6,
bears N.49°W. 10.2 ft. & also BT., 8" W.Fir bears S.60°W.
41.5 ft. from 5/8" I.P., not S.57 1/4°E.

Section Corner to Sections 26 - 27 - 34 - 35 Ren. # 5.

Found - 46" D.Fir N.84°E. 75.1 ft., shows "T30SR8S26 RE2741 BT",
30" D.Fir N.43 1/2°W. 19.5 ft., blaze mostly healed over.
24" D.Fir S.19°W. 19.6 ft., partial scribe visible on pitched
over blaze.

33" D.Fir S.42 1/2°E. 80.7 ft., shows "T30SR8 S35 RE2741BT",
bark scribe. ALL FOUR BT'S ABOVE, Rec. in Ren. #5.

No original BT's evident at this time.

Set - Brass Cap at Cor. Mkd: County Surveyor's T30S R8W S 27 S26
Office, 1965 S 34 S35

No New BT's required. Corner lies in cutting corner area
cut off in Section 26. - 7/12/68 - SEARCHED FOR, NOT FOUND?

J.M.P.

Section Corner to Sections 5 - 6 - 7 - 8.

Found - Orig. 15", now 24" Chinquapin N.55°E. 4.0 ft., now badly
rotted stump, no scribe found.

Orig. 14", now 24" Fir S.56°E. 5.8 ft., now snag, shows "
"T3RW S8BT", bark scribe in poor condition.

Orig. 15", now 24" Fir S.44°W. 47.5 ft., turned out, no scribe.
No trace of other BT.

Set - Brass Cap at Cor. Mkd: County Surveyor's T30S R8W S 6 S 5
Office, 1965 S 7 S 8

New BT's: 16" Cedar N.51°W. 28.4 ft. Mkd: T30S R8W S6 CS BT.

5" D.Fir S.82°W. 5.8 ft. Mkd: S 7 CS BT.

8" W.Fir S.18°E. 12.9 ft. Mkd: T30S R8W S8 CS BT.

5" Chinquapin N.53°E. 8.4 ft. Mkd: S 5 CS BT.

Note - Corner is approximately 40.0 ft. south of old logging road
on top of ridge.

1/4 Section Corner to Sections 6 and 5.

Found - Orig. 15", now 26" Fir N.74°E. 21.8 ft., turned out, has "1/4"
bark scribe, appears very old.

12", now 15" Fir Stump S.62°W. 7.9 ft., badly decayed, no scribe.

Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1965

New BT's: 9" W.Fir N.72°W. 10.0 ft. Mkd: 1/4 S 6 S 5 -Corner lies on top spur
6" W.Fir S.72°E. 21.0 ft. Mkd: 1/4 S5 CS BT. -sloping N. E.

(#57)

58

144

59

FOOK D Edwards
2/2005 CS 65/55-1
set 6' post 2' west

Vernon "Ray" Tracy
Mike Darby & Jack Barnett
April & May 1965
C. S. File No. 53/67

60

RE-RENEWED CORNER NO. #135

SEARCHED FOR, NOT FOUND?
Look again in
there 1-29-82(H.I.)

61

RE-RENEWED CORNER NO. #142

62

#146