Douglas County Surveyor's Record of Government Corners Renewed

T. 30 S. T. S. R. 8 W. R.W.W.M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21681

103

Center 1/4 Corner of Section 28.
Set - 1" Iron Pipe, from which:
36 Fir/Tag N.65° E. 38 feet.
30" I. Cedar N. 7°E. 71.7 feet.

Stuntzner, R. E.
For: Westbrook
C.S. 55/287

April 23, 1973 M 48 - 29

104

West 1/16 Corner between Sec. 17 and 20.
Set - Brass cap mkd. W 1/16 S17, S20 1973.
BT's - 12" Douglas Fir, bears N.32°W., 13.6 ft. Scribed "W 1/16 S17 BT"
6" Douglas Fir, Brars S.7°W., 5.8 ft. scribed "W 1/16 S20 BT"

105

NW 1/16 Sec. 20.
Set - Brass Cap mkd. NW 1/16 S20 1973.
BT's - 10" Cedar, bears N.35°W., 48.2 ft. scribed"NW 1/16 S20 BT"
6" Douglas Fir, bears S.41°E., 25.7 ft. scribed "NW 1/16 S20 BT"

106

North 1/16 center Sec. 20.
Set - Brass cap mkd. N 1/16 C/C S20 1973.
BT's - 8" Cedar, bears N.35°W., 8.5 ft. scribed "CN 1/16 S20 BT."
8" Douglas Fir, bears S.24°E., 32.9 ft., scribed "CN 1/16 S20 BT."

Bruce A. Shaner Engineering
For Moore Mill and Lumber Co.
M 49 - 25
June 1973

107

West 1/16 Center sec. 20.
Set - Brass cap mkd. W 1/16 C-C S20 1973.
BT's - 36" Douglas Fir, bears N.82½°E., 42.5 ft. scribed "CW 1/16 S20 BT".
28" Red Cedar, bears S.16°W., 36.0 ft. scribed "CW 1/16 S20 BT."

108

Center ¼ Section 20.
Set - Brass cap mkd. C¼ S20 1973.
BT's - 16" Douglas Fir, bears S.36°W., 25.5 ft. scribed "C ¼ S20 BT."
8" Douglas Fir, bears N.26½°E., 9.5 ft. scribed "C ¼ S20 BT".

109

Southwest 1/16 Corner Sec. 20.
Set - Brass cap mkd. SW 1/16 S20 1973.
BT's - 8" Cedar, bears N.20½° W., 7.2 ft. scribed "SW 1/16 S20 BT."
10" Douglas Fir, bears S23°E., 17.1 ft. scribed "SW 1/16 S20 BT."

110

South 1/16 corner Section 20.
Set - Brass cap mkd. S 1/16 C/C S20 1973.
BT's - 12" Douglas Fir, bears S.39°E., 18.3 ft. scribed "CS 1/16 S20 BT".
12" Douglas Fir, bears S.30°W., 36.2 ft. scribed "CS 1/16 S20 BT."

111

1/4 Corner for Secs. 30 and 31
Found - Orig. 9" now 14" forked B. Oak with scribing "1/4" visible on newly opened blaze.
19" live oak, blazed portion rotten and burnt-out, no marks found.
No trace of original stone.
Set - Brass cap mkd:
COUNTY SURVEYORS OFFICE 1974
T 30 S R 8 W
1/4 S 30 / S 31
at record bearing and distance from original NW bearing tree (N.62°W., 29.0 ft.)
The aforementioned 19" live oak bears S.22°W., 19.0 ft. (rec. S.22°W., 22.4 ft.) Note The slope distance to this tree is 22.4 ft at 32°. I do not mark this tree.
New BT - 8" D.Fir bears N.70°E., 15.2 ft. scribed "1/4 S30 CS BT"
This corner lies approx. 75 ft. south of a rock bluff, course NW-SE.

Gary Langlitz, Surveyors Office
P. Earle
C.S. 56/49
3/26/74