

Douglas County Surveyor's Record of  
Government Corners Renewed

T 30

T. S.

R 8

R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

120

Howard Johnstone  
For: Roseburg Lum-  
ber Company  
Nov. 17, 1976  
M 56 - 61

1/4 Corner for Sections 32 and 31  
Set - 5/8" x 36" Iron Rod & Aluminum cap.  
BT's - 20" Cedar, N.21 1/2°E., 27.3 ft.  
14" Cedar, N.82°W., 31.6 ft.

11/17/76

3/77  
JAN 28  
1-

121

Section corner for Secs. 4 and 5; and Secs. 32 & 33 T.29-8  
Found - 1958 County Surveyor BCIP. Ren. #21  
36" Cedar, S.23°W., 25.0 ft. (1882 survey)  
36" Fir, N.3°E., 25.0 ft.  
56" Fir snag, S.13°E., 50.0 ft. (Boyer ?)

122

Closing corner for Secs. 3 and 4 only.  
Found - 1967 County Surveyor BCIP. Ren. #81  
Set - 5/8" x 36" I.R. and Alum. cap. South 5.30 ft. on true Tp. line.  
BT's - 16" Fir S.79°E., 8.6 ft.  
14" Fir, S.18°W., 18.5 ft.  
12" Fir, N.7°E., 19.1 ft.

123

Section corner for Secs. 33 and 34 only, T.29-8  
Set - 5/8" x 48" I.R. and Alum. cap.  
BT's - 22" Fir, N.60 1/2°W., 16.7 ft.  
14" Fir, N.28°E., 46.6 ft.  
26" Fir, S.20°E., 44.9 ft.

124

South 1/4 Corner for 34 only, T.29-8  
Set - 5/8" x 48" I.R. and Alum. cap.  
BT's - 22" Fir N.77°E., 41.6 ft.  
15" Fir S.42°E., 19.5 ft.  
Found 1" I.P. N.12°02'22"E., 17.14 ft. Not of Record.

125

Closing corner for Secs. 2 and 1 only.  
Found - 1970 County Surveyor BCIP. (Record, 1967, Ren. #82)  
30" Cedar, S.59°W., 40.3 ft. Orig. Rec. (Ren. #82 rec. S.67°W.,  
43.8 ft.)  
New BT - 12" Maple S.50°E., 57.4 ft. 5.81 ft. North of Tp. line.

126

1/4 Corner for Secs. 3 and 2.  
Set - 5/8" x 30" I.R. and Alum. cap.  
BT's - 33" Fir, N.30°W., 27.8 ft.  
21" Fir, N.32°E., 7.7 ft.

1/9/80

127

Section corner for Secs. 14, 15, 22 and 23.  
Found - 1964 BLM brass cap on 2 1/2" I.P. in good condition  
marked: T30S R8W S14 S14 S22 S23 196-.  
Orig. 38" burnt stump, no scribe marks visible bears N.44°E.,  
29.0 ft.  
Orig. BT, 45" Fir, burnt, no scribe marks visible bears S.35°E.,  
15.2 ft.  
Orig. SW BT gone.  
Found root fragments from orig. BT bears N.14°W., 27.7 ft.  
1964 BLM BT, 10" Fir stump with scribed T visible bears N.80 1/2°E  
77.2 ft.  
1964 BLM BT, 22" Fir stump with well healed face bears S.26°W.,  
54.8 ft.  
1964 BLM BT, 8" now 9" Fir, dead and burnt with scribed T30S  
W S15 BT visible in single blaze, bears N.81 1/2°W., 27.1 ft.  
New Accessories:  
14" Fir bears N.81 1/2°E., 148.7 ft. scribed T30S R8W S14 CS BT  
in double blaze.  
32" Fir bears S.57°E., 100.6 ft. scribed T30S R8W S23 CS BT in  
double blaze. (upper scribe is in blaze.)  
Boat spike in 18" Fir stump bears S.49°W., 42.5 ft.  
Boat spike in 36" Fir stump bears N.24°W., 58.0 ft.

Greg Quibell, Deputy  
Doug. Co. Surveyors  
Office  
Terrie Plouff  
Feb. 4, 1981  
C.S. 16/19

Howard W. Johnstone  
For: Roseburg Lumber  
Company  
January 9, 1980  
M 79 - 15