

TOWNSHIP 24 RANGE 03 POINT IDENTIFIER # 500140

PRIMARY CORNER DESCRIPTION 1/4 Cor Secs 34 & 35

Alias _____	Description _____
Alias _____	Description <u>DCRS CANYONVILLE COTTAGE GROVE COORDS</u>
Alias _____	Description _____
Alias _____	Description <u>220967.881 N</u>
	<u>244512.875 E</u>

GLO survey by L.H. Wheeler under Contract No. 467 dated April 7, 1883 (DCSO records Vol. 7 Page(s) 2987)

On ridge, course E & W set cedar post 3 ft. long, 3" sq., 24" in the ground for 1/4 sec. cor. marked 1/4 sec. cor. mkd. 1/4 S on W face from which

A fir, 20" dia., bears N.17°E., 55 lks., mkd: 1/4 S BT.

A hemlock, 36" dia., bears S.25°W., 91 lks., mkd: 1/4 S BT.

Douglas Co. Surveyors Office - V.R. Tracy - 9/1967 - C.S. File 54/27

Not found
Corner pro old logging.

Burton Ho 1981 - M90-16

Set - 5/8" 11" 9" from which:
ft. mkd: "1/4 S34 BT"
"1/4 S35 BT"
S.89°27'37"W., appr.

New - Se

Note- Th W rock road.

ADD COORDINATES IS ALL THATS NEEDED

Fd. Ok

Douglas Lorsung Stephen Flause & Jeff - C.S. File 67/51-34

Found - W., 21.2 ft. (rec. S.27°30'W., 21.2 ft. mostly burnt away.

8"x5' D.Fir snag S.86½°E., 15.8' (Rec. S.83°E.) Mostly burnt away.

New - Replace 5/8"x10" bent I.Rod with 5/8"x30" Iron Rod with DCSO yellow plastic cap, proj 6" above ground.

23"x1" sawn Fir stump 4" mag nail top center N.6½°W., 45.7 ft.

30"x¾" I.D. iron pipe with 5/8" I.Rod in center projecting 4", N.25½°E., 41.1 ft.

Note - Corner is approx 18' south of rock road.
Area burnt in Archie Cr Fire 9/2020
Compass decl. 14½°E.
See sketch in file.

CS 67/41-45